

Problem 730: Count Different Palindromic Subsequences

Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given a string s , return

the number of different non-empty palindromic subsequences in

s

. Since the answer may be very large, return it

modulo

10

9

+ 7

.

A subsequence of a string is obtained by deleting zero or more characters from the string.

A sequence is palindromic if it is equal to the sequence reversed.

Two sequences

a

1

, a

2

, ...

and

b

1

, b

2

, ...

are different if there is some

i

for which

a

i

$\neq b$

i

.

Example 1:

Input:

```
s = "bccb"
```

Output:

6

Explanation:

The 6 different non-empty palindromic subsequences are 'b', 'c', 'bb', 'cc', 'bcb', 'bccb'. Note that 'bcb' is counted only once, even though it occurs twice.

Example 2:

Input:

[illegible]

Output:

104860361

Explanation:

There are 3104860382 different non-empty palindromic subsequences, which is 104860361 modulo 10

9

+ 7.

Constraints:

```
1 <= s.length <= 1000
```

s[i]

is either

'a'

,

'b'

,

'c'

, or

'd'

.

Code Snippets

C++:

```
class Solution {  
public:  
    int countPalindromicSubsequences(string s) {  
  
    }  
};
```

Java:

```
class Solution {  
    public int countPalindromicSubsequences(String s) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def countPalindromicSubsequences(self, s: str) -> int:
```

Python:

```
class Solution(object):  
    def countPalindromicSubsequences(self, s):  
        """  
        :type s: str  
        :rtype: int  
        """
```

JavaScript:

```
/**  
 * @param {string} s  
 * @return {number}  
 */  
var countPalindromicSubsequences = function(s) {  
  
};
```

TypeScript:

```
function countPalindromicSubsequences(s: string): number {  
  
};
```

C#:

```
public class Solution {  
    public int CountPalindromicSubsequences(string s) {  
  
    }  
}
```

C:

```
int countPalindromicSubsequences(char* s) {  
  
}
```

Go:

```
func countPalindromicSubsequences(s string) int {
```

```
}
```

Kotlin:

```
class Solution {  
    fun countPalindromicSubsequences(s: String): Int {  
  
    }  
}
```

Swift:

```
class Solution {  
    func countPalindromicSubsequences(_ s: String) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn count_palindromic_subsequences(s: String) -> i32 {  
  
    }  
}
```

Ruby:

```
# @param {String} s  
# @return {Integer}  
def count_palindromic_subsequences(s)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param String $s  
     * @return Integer  
     */  
}
```

```
function countPalindromicSubsequences($s) {

}

}
```

Dart:

```
class Solution {
  int countPalindromicSubsequences(String s) {

  }
}
```

Scala:

```
object Solution {
  def countPalindromicSubsequences(s: String): Int = {

  }
}
```

Elixir:

```
defmodule Solution do
  @spec count_palindromic_subsequences(s :: String.t) :: integer
  def count_palindromic_subsequences(s) do

  end
end
```

Erlang:

```
-spec count_palindromic_subsequences(S :: unicode:unicode_binary()) ->
integer().
count_palindromic_subsequences(S) ->
.
```

Racket:

```
(define/contract (count-palindromic-subsequences s)
  (-> string? exact-integer?)
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Count Different Palindromic Subsequences
 * Difficulty: Hard
 * Tags: string, dp
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
public:
    int countPalindromicSubsequences(string s) {

    }
};
```

Java Solution:

```
/**
 * Problem: Count Different Palindromic Subsequences
 * Difficulty: Hard
 * Tags: string, dp
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
    public int countPalindromicSubsequences(String s) {

    }
}
```

Python3 Solution:


```

"""
Problem: Count Different Palindromic Subsequences
Difficulty: Hard
Tags: string, dp

Approach: String manipulation with hash map or two pointers
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) or O(n * m) for DP table
"""

class Solution:
    def countPalindromicSubsequences(self, s: str) -> int:
        # TODO: Implement optimized solution
        pass

```

Python Solution:

```

class Solution(object):
    def countPalindromicSubsequences(self, s):
        """
        :type s: str
        :rtype: int
        """

```

JavaScript Solution:

```

/**
 * Problem: Count Different Palindromic Subsequences
 * Difficulty: Hard
 * Tags: string, dp
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
 * @param {string} s
 * @return {number}
 */
var countPalindromicSubsequences = function(s) {

```

```
};
```

TypeScript Solution:

```
/**
 * Problem: Count Different Palindromic Subsequences
 * Difficulty: Hard
 * Tags: string, dp
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

function countPalindromicSubsequences(s: string): number {

};
```

C# Solution:

```
/*
 * Problem: Count Different Palindromic Subsequences
 * Difficulty: Hard
 * Tags: string, dp
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

public class Solution {
    public int CountPalindromicSubsequences(string s) {

    }
}
```

C Solution:

```
/*
 * Problem: Count Different Palindromic Subsequences
 * Difficulty: Hard
```

```

* Tags: string, dp
*
* Approach: String manipulation with hash map or two pointers
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) or O(n * m) for DP table
*/

int countPalindromicSubsequences(char* s) {

}

```

Go Solution:

```

// Problem: Count Different Palindromic Subsequences
// Difficulty: Hard
// Tags: string, dp
//
// Approach: String manipulation with hash map or two pointers
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

func countPalindromicSubsequences(s string) int {

}

```

Kotlin Solution:

```

class Solution {
    fun countPalindromicSubsequences(s: String): Int {

    }
}

```

Swift Solution:

```

class Solution {
    func countPalindromicSubsequences(_ s: String) -> Int {

    }
}

```

Rust Solution:

```
// Problem: Count Different Palindromic Subsequences
// Difficulty: Hard
// Tags: string, dp
//
// Approach: String manipulation with hash map or two pointers
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

impl Solution {
    pub fn count_palindromic_subsequences(s: String) -> i32 {

    }
}
```

Ruby Solution:

```
# @param {String} s
# @return {Integer}
def count_palindromic_subsequences(s)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param String $s
     * @return Integer
     */
    function countPalindromicSubsequences($s) {

    }
}
```

Dart Solution:

```
class Solution {
    int countPalindromicSubsequences(String s) {
```

```
}  
}
```

Scala Solution:

```
object Solution {  
  def countPalindromicSubsequences(s: String): Int = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec count_palindromic_subsequences(s :: String.t) :: integer  
  def count_palindromic_subsequences(s) do  
  
  end  
end
```

Erlang Solution:

```
-spec count_palindromic_subsequences(S :: unicode:unicode_binary()) ->  
integer().  
count_palindromic_subsequences(S) ->  
.
```

Racket Solution:

```
(define/contract (count-palindromic-subsequences s)  
  (-> string? exact-integer?)  
)
```