

Problem 2969: Minimum Number of Coins for Fruits II

Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are at a fruit market with different types of exotic fruits on display.

You are given a

1-indexed

array

prices

, where

prices[i]

denotes the number of coins needed to purchase the

i

th

fruit.

The fruit market has the following offer:

If you purchase the

i

th

fruit at

prices[i]

coins, you can get the next

i

fruits for free.

Note

that even if you

can

take fruit

j

for free, you can still purchase it for

prices[j]

coins to receive a new offer.

Return

the

minimum

number of coins needed to acquire all the fruits

.

Example 1:

Input:

prices = [3,1,2]

Output:

4

Explanation:

You can acquire the fruits as follows: - Purchase the 1

st

fruit with 3 coins, and you are allowed to take the 2

nd

fruit for free. - Purchase the 2

nd

fruit with 1 coin, and you are allowed to take the 3

rd

fruit for free. - Take the 3

rd

fruit for free. Note that even though you were allowed to take the 2

nd

fruit for free, you purchased it because it is more optimal. It can be proven that 4 is the minimum number of coins needed to acquire all the fruits.

Example 2:

Input:

prices = [1,10,1,1]

Output:

2

Explanation:

You can acquire the fruits as follows: - Purchase the 1

st

fruit with 1 coin, and you are allowed to take the 2

nd

fruit for free. - Take the 2

nd

fruit for free. - Purchase the 3

rd

fruit for 1 coin, and you are allowed to take the 4

th

fruit for free. - Take the 4

t

h

fruit for free. It can be proven that 2 is the minimum number of coins needed to acquire all the fruits.

Constraints:

$1 \leq \text{prices.length} \leq 10$

5

$1 \leq \text{prices}[i] \leq 10$

5

Code Snippets

C++:

```
class Solution {
public:
    int minimumCoins(vector<int>& prices) {

    }
};
```

Java:

```
class Solution {
    public int minimumCoins(int[] prices) {

    }
}
```

Python3:

```
class Solution:
    def minimumCoins(self, prices: List[int]) -> int:
```

Python:

```

class Solution(object):
    def minimumCoins(self, prices):
        """
        :type prices: List[int]
        :rtype: int
        """

```

JavaScript:

```

/**
 * @param {number[]} prices
 * @return {number}
 */
var minimumCoins = function(prices) {

};

```

TypeScript:

```

function minimumCoins(prices: number[]): number {

};

```

C#:

```

public class Solution {
    public int MinimumCoins(int[] prices) {

    }
}

```

C:

```

int minimumCoins(int* prices, int pricesSize) {

}

```

Go:

```

func minimumCoins(prices []int) int {

}

```

Kotlin:

```
class Solution {  
    fun minimumCoins(prices: IntArray): Int {  
  
    }  
}
```

Swift:

```
class Solution {  
    func minimumCoins(_ prices: [Int]) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn minimum_coins(prices: Vec<i32>) -> i32 {  
  
    }  
}
```

Ruby:

```
# @param {Integer[]} prices  
# @return {Integer}  
def minimum_coins(prices)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param Integer[] $prices  
     * @return Integer  
     */  
    function minimumCoins($prices) {  
  
    }  
}
```

```
}
```

Dart:

```
class Solution {  
  int minimumCoins(List<int> prices) {  
  
  }  
}
```

Scala:

```
object Solution {  
  def minimumCoins(prices: Array[Int]): Int = {  
  
  }  
}
```

Elixir:

```
defmodule Solution do  
  @spec minimum_coins(prices :: [integer]) :: integer  
  def minimum_coins(prices) do  
  
  end  
end
```

Erlang:

```
-spec minimum_coins(Prices :: [integer()]) -> integer().  
minimum_coins(Prices) ->  
.
```

Racket:

```
(define/contract (minimum-coins prices)  
  (-> (listof exact-integer?) exact-integer?)  
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Minimum Number of Coins for Fruits II
 * Difficulty: Hard
 * Tags: array, dp, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
public:
    int minimumCoins(vector<int>& prices) {

    }
};
```

Java Solution:

```
/**
 * Problem: Minimum Number of Coins for Fruits II
 * Difficulty: Hard
 * Tags: array, dp, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
    public int minimumCoins(int[] prices) {

    }
}
```

Python3 Solution:

```
"""
Problem: Minimum Number of Coins for Fruits II
Difficulty: Hard
Tags: array, dp, queue, heap
```

```

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) or O(n * m) for DP table
"""

class Solution:
    def minimumCoins(self, prices: List[int]) -> int:
        # TODO: Implement optimized solution
        pass

```

Python Solution:

```

class Solution(object):
    def minimumCoins(self, prices):
        """
        :type prices: List[int]
        :rtype: int
        """

```

JavaScript Solution:

```

/**
 * Problem: Minimum Number of Coins for Fruits II
 * Difficulty: Hard
 * Tags: array, dp, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
 * @param {number[]} prices
 * @return {number}
 */
var minimumCoins = function(prices) {

};

```

TypeScript Solution:

```

/**
 * Problem: Minimum Number of Coins for Fruits II
 * Difficulty: Hard
 * Tags: array, dp, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

function minimumCoins(prices: number[]): number {

};

```

C# Solution:

```

/*
 * Problem: Minimum Number of Coins for Fruits II
 * Difficulty: Hard
 * Tags: array, dp, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

public class Solution {
    public int MinimumCoins(int[] prices) {

    }
}

```

C Solution:

```

/*
 * Problem: Minimum Number of Coins for Fruits II
 * Difficulty: Hard
 * Tags: array, dp, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table

```

```

*/

int minimumCoins(int* prices, int pricesSize) {

}

```

Go Solution:

```

// Problem: Minimum Number of Coins for Fruits II
// Difficulty: Hard
// Tags: array, dp, queue, heap
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

func minimumCoins(prices []int) int {

}

```

Kotlin Solution:

```

class Solution {
    fun minimumCoins(prices: IntArray): Int {

    }
}

```

Swift Solution:

```

class Solution {
    func minimumCoins(_ prices: [Int]) -> Int {

    }
}

```

Rust Solution:

```

// Problem: Minimum Number of Coins for Fruits II
// Difficulty: Hard
// Tags: array, dp, queue, heap

```

```
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

impl Solution {
    pub fn minimum_coins(prices: Vec<i32>) -> i32 {

    }
}
```

Ruby Solution:

```
# @param {Integer[]} prices
# @return {Integer}
def minimum_coins(prices)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $prices
     * @return Integer
     */
    function minimumCoins($prices) {

    }
}
```

Dart Solution:

```
class Solution {
    int minimumCoins(List<int> prices) {

    }
}
```

Scala Solution:

```
object Solution {  
  def minimumCoins(prices: Array[Int]): Int = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec minimum_coins(prices :: [integer]) :: integer  
  def minimum_coins(prices) do  
  
  end  
end
```

Erlang Solution:

```
-spec minimum_coins(Prices :: [integer()]) -> integer().  
minimum_coins(Prices) ->  
.
```

Racket Solution:

```
(define/contract (minimum-coins prices)  
  (-> (listof exact-integer?) exact-integer?)  
)
```