

# Problem 515: Find Largest Value in Each Tree Row

## Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

Given the

root

of a binary tree, return


an array of the largest value in each row

of the tree

(0-indexed)

.

Example 1:



Input:

root = [1,3,2,5,3,null,9]

Output:

[1,3,9]

Example 2:

Input:

root = [1,2,3]

Output:

[1,3]

Constraints:

The number of nodes in the tree will be in the range

[0, 10

]

.

-2

31

<= Node.val <= 2

31

- 1

## Code Snippets

### C++:

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *   int val;
 *   TreeNode *left;
 *   TreeNode *right;
 *   TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *   TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *   TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
right(right) {}
 * };
 */
class Solution {
public:
    vector<int> largestValues(TreeNode* root) {

    }
};
```

### Java:

```

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     int val;
 *     TreeNode left;
 *     TreeNode right;
 *     TreeNode() {}
 *     TreeNode(int val) { this.val = val; }
 *     TreeNode(int val, TreeNode left, TreeNode right) {
 *         this.val = val;
 *         this.left = left;
 *         this.right = right;
 *     }
 * }
 */
class Solution {
    public List<Integer> largestValues(TreeNode root) {

    }
}

```

### Python3:

```

# Definition for a binary tree node.
# class TreeNode:
#     def __init__(self, val=0, left=None, right=None):
#         self.val = val
#         self.left = left
#         self.right = right
class Solution:
    def largestValues(self, root: Optional[TreeNode]) -> List[int]:

```

### Python:

```

# Definition for a binary tree node.
# class TreeNode(object):
#     def __init__(self, val=0, left=None, right=None):
#         self.val = val
#         self.left = left
#         self.right = right
class Solution(object):
    def largestValues(self, root):
        """

```

```

:type root: Optional[TreeNode]
:rtype: List[int]
"""

```

## JavaScript:

```

/**
 * Definition for a binary tree node.
 * function TreeNode(val, left, right) {
 *   this.val = (val===undefined ? 0 : val)
 *   this.left = (left===undefined ? null : left)
 *   this.right = (right===undefined ? null : right)
 * }
 */
/**
 * @param {TreeNode} root
 * @return {number[]}
 */
var largestValues = function(root) {

};

```

## TypeScript:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   val: number
 *   left: TreeNode | null
 *   right: TreeNode | null
 *   constructor(val?: number, left?: TreeNode | null, right?: TreeNode | null) {
 *     this.val = (val===undefined ? 0 : val)
 *     this.left = (left===undefined ? null : left)
 *     this.right = (right===undefined ? null : right)
 *   }
 * }
 */

function largestValues(root: TreeNode | null): number[] {

};

```

## C#:

```
/**
 * Definition for a binary tree node.
 * public class TreeNode {
 * public int val;
 * public TreeNode left;
 * public TreeNode right;
 * public TreeNode(int val=0, TreeNode left=null, TreeNode right=null) {
 * this.val = val;
 * this.left = left;
 * this.right = right;
 * }
 * }
 */
public class Solution {
public IList<int> LargestValues(TreeNode root) {

}

}
```

## C:

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 * int val;
 * struct TreeNode *left;
 * struct TreeNode *right;
 * };
 */
/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* largestValues(struct TreeNode* root, int* returnSize) {

}
```

## Go:

```
/**
 * Definition for a binary tree node.
 * type TreeNode struct {
```

```

* Val int
* Left *TreeNode
* Right *TreeNode
* }
*/
func largestValues(root *TreeNode) []int {

}

```

## Kotlin:

```

/**
 * Example:
 * var ti = TreeNode(5)
 * var v = ti.`val`
 * Definition for a binary tree node.
 * class TreeNode(var `val`: Int) {
 *     var left: TreeNode? = null
 *     var right: TreeNode? = null
 * }
 */
class Solution {
    fun largestValues(root: TreeNode?): List<Int> {

    }
}

```

## Swift:

```

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     public var val: Int
 *     public var left: TreeNode?
 *     public var right: TreeNode?
 *     public init() { self.val = 0; self.left = nil; self.right = nil; }
 *     public init(_ val: Int) { self.val = val; self.left = nil; self.right = nil; }
 *     public init(_ val: Int, _ left: TreeNode?, _ right: TreeNode?) {
 *         self.val = val
 *         self.left = left
 *         self.right = right
 *     }
 * }
 */

```

```

* }
* }
*/

class Solution {
func largestValues(_ root: TreeNode?) -> [Int] {

}

}

```

## Rust:

```

// Definition for a binary tree node.
// #[derive(Debug, PartialEq, Eq)]
// pub struct TreeNode {
//     pub val: i32,
//     pub left: Option<Rc<RefCell<TreeNode>>>,
//     pub right: Option<Rc<RefCell<TreeNode>>>,
// }
//
// impl TreeNode {
//     #[inline]
//     pub fn new(val: i32) -> Self {
//         TreeNode {
//             val,
//             left: None,
//             right: None
//         }
//     }
// }

use std::rc::Rc;
use std::cell::RefCell;

impl Solution {
    pub fn largest_values(root: Option<Rc<RefCell<TreeNode>>>) -> Vec<i32> {

    }

}

```

## Ruby:

```

# Definition for a binary tree node.
# class TreeNode
#   attr_accessor :val, :left, :right

```



```

# def initialize(val = 0, left = nil, right = nil)
# @val = val
# @left = left
# @right = right
# end
# end
# @param {TreeNode} root
# @return {Integer[]}
def largest_values(root)

end

```

## PHP:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 * public $val = null;
 * public $left = null;
 * public $right = null;
 * function __construct($val = 0, $left = null, $right = null) {
 * $this->val = $val;
 * $this->left = $left;
 * $this->right = $right;
 * }
 * }
 */
class Solution {

/**
 * @param TreeNode $root
 * @return Integer[]
 */
function largestValues($root) {

}

}

```

## Dart:

```

/**
 * Definition for a binary tree node.

```

```

* class TreeNode {
*   int val;
*   TreeNode? left;
*   TreeNode? right;
*   TreeNode([this.val = 0, this.left, this.right]);
* }
*/
class Solution {
List<int> largestValues(TreeNode? root) {

}
}

```

### Scala:

```

/**
 * Definition for a binary tree node.
 * class TreeNode(_value: Int = 0, _left: TreeNode = null, _right: TreeNode =
null) {
 *   var value: Int = _value
 *   var left: TreeNode = _left
 *   var right: TreeNode = _right
 * }
 */
object Solution {
def largestValues(root: TreeNode): List[Int] = {

}
}

```

### Elixir:

```

# Definition for a binary tree node.
#
# defmodule TreeNode do
#   @type t :: %__MODULE__{
#     val: integer,
#     left: TreeNode.t() | nil,
#     right: TreeNode.t() | nil
#   }
#   defstruct val: 0, left: nil, right: nil
# end

```

```

defmodule Solution do
  @spec largest_values(root :: TreeNode.t | nil) :: [integer]
  def largest_values(root) do

  end
end

```

## Erlang:

```

%% Definition for a binary tree node.
%%
%% -record(tree_node, {val = 0 :: integer(),
%% left = null :: 'null' | #tree_node{},
%% right = null :: 'null' | #tree_node{}}).

-spec largest_values(Root :: #tree_node{} | null) -> [integer()].
largest_values(Root) ->
.

```

## Racket:

```

; Definition for a binary tree node.
#|

; val : integer?
; left : (or/c tree-node? #f)
; right : (or/c tree-node? #f)
(struct tree-node
  (val left right) #:mutable #:transparent)

; constructor
(define (make-tree-node [val 0])
  (tree-node val #f #f))

|#

(define/contract (largest-values root)
  (-> (or/c tree-node? #f) (listof exact-integer?))
)

```

## Solutions

### C++ Solution:

```
/*
 * Problem: Find Largest Value in Each Tree Row
 * Difficulty: Medium
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     TreeNode *left;
 *     TreeNode *right;
 *     TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *     TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *     TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
 *     right(right) {}
 * };
 */
class Solution {
public:
    vector<int> largestValues(TreeNode* root) {

    }
};
```

### Java Solution:

```
/**
 * Problem: Find Largest Value in Each Tree Row
 * Difficulty: Medium
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
```

```

*/

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     int val;
 *     TreeNode left;
 *     TreeNode right;
 *     TreeNode() {}
 *     TreeNode(int val) { this.val = val; }
 *     TreeNode(int val, TreeNode left, TreeNode right) {
 *         this.val = val;
 *         this.left = left;
 *         this.right = right;
 *     }
 * }
 */
class Solution {
    public List<Integer> largestValues(TreeNode root) {

    }
}

```

## Python3 Solution:

```

"""
Problem: Find Largest Value in Each Tree Row
Difficulty: Medium
Tags: array, tree, search

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(h) for recursion stack where h is height
"""

# Definition for a binary tree node.
# class TreeNode:
#     def __init__(self, val=0, left=None, right=None):
#         self.val = val
#         self.left = left
#         self.right = right

```

```

class Solution:
    def largestValues(self, root: Optional[TreeNode]) -> List[int]:
        # TODO: Implement optimized solution
        pass

```

## Python Solution:

```

# Definition for a binary tree node.
# class TreeNode(object):
#     def __init__(self, val=0, left=None, right=None):
#         self.val = val
#         self.left = left
#         self.right = right
class Solution(object):
    def largestValues(self, root):
        """
        :type root: Optional[TreeNode]
        :rtype: List[int]
        """

```

## JavaScript Solution:

```

/**
 * Problem: Find Largest Value in Each Tree Row
 * Difficulty: Medium
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * function TreeNode(val, left, right) {
 *     this.val = (val===undefined ? 0 : val)
 *     this.left = (left===undefined ? null : left)
 *     this.right = (right===undefined ? null : right)
 * }
 */

```

```

* @param {TreeNode} root
* @return {number[]}
*/
var largestValues = function(root) {

};

```

### TypeScript Solution:

```

/**
 * Problem: Find Largest Value in Each Tree Row
 * Difficulty: Medium
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   val: number
 *   left: TreeNode | null
 *   right: TreeNode | null
 *   constructor(val?: number, left?: TreeNode | null, right?: TreeNode | null)
 *   {
 *     this.val = (val===undefined ? 0 : val)
 *     this.left = (left===undefined ? null : left)
 *     this.right = (right===undefined ? null : right)
 *   }
 * }
 */

function largestValues(root: TreeNode | null): number[] {

};

```

### C# Solution:

```

/*
 * Problem: Find Largest Value in Each Tree Row
 * Difficulty: Medium
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 * public int val;
 * public TreeNode left;
 * public TreeNode right;
 * public TreeNode(int val=0, TreeNode left=null, TreeNode right=null) {
 * this.val = val;
 * this.left = left;
 * this.right = right;
 * }
 * }
 */
public class Solution {
public IList<int> LargestValues(TreeNode root) {

}

}

```

## C Solution:

```

/*
 * Problem: Find Largest Value in Each Tree Row
 * Difficulty: Medium
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**

```



```

* Definition for a binary tree node.
* struct TreeNode {
*   int val;
*   struct TreeNode *left;
*   struct TreeNode *right;
* };
*/
/**
* Note: The returned array must be malloced, assume caller calls free().
*/
int* largestValues(struct TreeNode* root, int* returnSize) {

}

```

### Go Solution:

```

// Problem: Find Largest Value in Each Tree Row
// Difficulty: Medium
// Tags: array, tree, search
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

/**
* Definition for a binary tree node.
* type TreeNode struct {
*   Val int
*   Left *TreeNode
*   Right *TreeNode
* }
*/
func largestValues(root *TreeNode) []int {

}

```

### Kotlin Solution:

```

/**
* Example:
* var ti = TreeNode(5)

```

```

* var v = ti.`val`
* Definition for a binary tree node.
* class TreeNode(var `val`: Int) {
*   var left: TreeNode? = null
*   var right: TreeNode? = null
* }
*/
class Solution {
fun largestValues(root: TreeNode?): List<Int> {

}
}

```

### Swift Solution:

```

/**
* Definition for a binary tree node.
* public class TreeNode {
*   public var val: Int
*   public var left: TreeNode?
*   public var right: TreeNode?
*   public init() { self.val = 0; self.left = nil; self.right = nil; }
*   public init(_ val: Int) { self.val = val; self.left = nil; self.right =
nil; }
*   public init(_ val: Int, _ left: TreeNode?, _ right: TreeNode?) {
*     self.val = val
*     self.left = left
*     self.right = right
*   }
* }
*/
class Solution {
func largestValues(_ root: TreeNode?) -> [Int] {

}
}

```

### Rust Solution:

```

// Problem: Find Largest Value in Each Tree Row
// Difficulty: Medium

```

```

// Tags: array, tree, search
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

// Definition for a binary tree node.
// #[derive(Debug, PartialEq, Eq)]
// pub struct TreeNode {
//     pub val: i32,
//     pub left: Option<Rc<RefCell<TreeNode>>>,
//     pub right: Option<Rc<RefCell<TreeNode>>>,
// }
//
// impl TreeNode {
//     #[inline]
//     pub fn new(val: i32) -> Self {
//         TreeNode {
//             val,
//             left: None,
//             right: None
//         }
//     }
// }

use std::rc::Rc;
use std::cell::RefCell;
impl Solution {
    pub fn largest_values(root: Option<Rc<RefCell<TreeNode>>>) -> Vec<i32> {

    }
}

```

## Ruby Solution:

```

# Definition for a binary tree node.
# class TreeNode
#   attr_accessor :val, :left, :right
#   def initialize(val = 0, left = nil, right = nil)
#     @val = val
#     @left = left
#     @right = right
#   end
# end

```

```

# end
# end
# @param {TreeNode} root
# @return {Integer[]}
def largest_values(root)

end

```

### PHP Solution:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 * public $val = null;
 * public $left = null;
 * public $right = null;
 * function __construct($val = 0, $left = null, $right = null) {
 * $this->val = $val;
 * $this->left = $left;
 * $this->right = $right;
 * }
 * }
 */
class Solution {

/**
 * @param TreeNode $root
 * @return Integer[]
 */
function largestValues($root) {

}

}

```

### Dart Solution:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 * int val;
 * TreeNode? left;

```

```

* TreeNode? right;
* TreeNode([this.val = 0, this.left, this.right]);
* }
*/
class Solution {
List<int> largestValues(TreeNode? root) {

}
}

```

### Scala Solution:

```

/**
 * Definition for a binary tree node.
 * class TreeNode(_value: Int = 0, _left: TreeNode = null, _right: TreeNode =
null) {
 *   var value: Int = _value
 *   var left: TreeNode = _left
 *   var right: TreeNode = _right
 * }
 */
object Solution {
def largestValues(root: TreeNode): List[Int] = {

}
}

```

### Elixir Solution:

```

# Definition for a binary tree node.
#
# defmodule TreeNode do
#   @type t :: %__MODULE__{
#     val: integer,
#     left: TreeNode.t() | nil,
#     right: TreeNode.t() | nil
#   }
#   defstruct val: 0, left: nil, right: nil
# end

defmodule Solution do

```

```

@spec largest_values(root :: TreeNode.t | nil) :: [integer]
def largest_values(root) do

end

end

```

## Erlang Solution:

```

%% Definition for a binary tree node.
%%
%% -record(tree_node, {val = 0 :: integer(),
%% left = null :: 'null' | #tree_node{},
%% right = null :: 'null' | #tree_node{}}).

-spec largest_values(Root :: #tree_node{} | null) -> [integer()].
largest_values(Root) ->
.

```

## Racket Solution:

```

; Definition for a binary tree node.
#|

; val : integer?
; left : (or/c tree-node? #f)
; right : (or/c tree-node? #f)
(struct tree-node
  (val left right) #:mutable #:transparent)

; constructor
(define (make-tree-node [val 0])
  (tree-node val #f #f))

|#

(define/contract (largest-values root)
  (-> (or/c tree-node? #f) (listof exact-integer?))
  )

```