

Problem 3592: Inverse Coin Change

Problem Information

Difficulty: Medium

Acceptance Rate: 50.78%

Paid Only: No

Tags: Array, Dynamic Programming

Problem Description

You are given a **1-indexed** integer array `numWays`, where `numWays[i]` represents the number of ways to select a total amount `i` using an **infinite** supply of some **fixed** coin denominations. Each denomination is a **positive** integer with value **at most** `numWays.length`.

However, the exact coin denominations have been **lost**. Your task is to recover the set of denominations that could have resulted in the given `numWays` array.

Return a **sorted** array containing **unique** integers which represents this set of denominations.

If no such set exists, return an **empty** array.

Example 1:

Input: `numWays = [0,1,0,2,0,3,0,4,0,5]`

Output: `[2,4,6]`

Explanation:

Amount	Number of ways	Explanation
1	0	There is no way to select coins with total value 1.
2	1	The only way is <code>[2]</code> .
3	0	There is no way to select coins with total value 3.
4	2	The ways are <code>[2, 2]</code> and <code>[4]</code> .
5	0	There is no way to select coins with total value 5.
6	3	The ways are <code>[2, 2, 2]</code> , <code>[2, 4]</code> , and <code>[6]</code> .
7	0	There is no way to select coins with total value 7.
8	4	The ways are <code>[2, 2, 2, 2]</code> , <code>[2, 2, 4]</code> , <code>[2, 6]</code> , and <code>[4, 4]</code> .
9	0	There is no way to select coins with total value 9.

way to select coins with total value 9. 10 | 5 | The ways are `[2, 2, 2, 2, 2]`, `[2, 2, 2, 4]`, `[2, 4, 4]`, `[2, 2, 6]`, and `[4, 6]`. **Example 2:**

Input: numWays = [1,2,2,3,4]

Output: [1,2,5]

Explanation:

Amount | Number of ways | Explanation ---|---|--- 1 | 1 | The only way is `[1]`. 2 | 2 | The ways are `[1, 1]` and `[2]`. 3 | 2 | The ways are `[1, 1, 1]` and `[1, 2]`. 4 | 3 | The ways are `[1, 1, 1, 1]`, `[1, 1, 2]`, and `[2, 2]`. 5 | 4 | The ways are `[1, 1, 1, 1, 1]`, `[1, 1, 1, 2]`, `[1, 2, 2]`, and `[5]`. **Example 3:**

Input: numWays = [1,2,3,4,15]

Output: []

Explanation:

No set of denomination satisfies this array.

Constraints:

* `1` <= numWays.length <= 100 * `0` <= numWays[i] <= 2 * 108`

Code Snippets

C++:

```
class Solution {
public:
    vector<int> findCoins(vector<int>& numWays) {

    }
};
```

Java:

```
class Solution {  
    public List<Integer> findCoins(int[] numWays) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def findCoins(self, numWays: List[int]) -> List[int]:
```