

Problem 1472: Design Browser History

Problem Information

Difficulty: Medium

Acceptance Rate: 78.05%

Paid Only: No

Tags: Array, Linked List, Stack, Design, Doubly-Linked List, Data Stream

Problem Description

You have a **browser** of one tab where you start on the `homepage` and you can visit another `url`, get back in the history number of `steps` or move forward in the history number of `steps`.

Implement the `BrowserHistory` class:

```
* `BrowserHistory(string homepage)` Initializes the object with the `homepage` of the browser.
* `void visit(string url)` Visits `url` from the current page. It clears up all the forward history.
* `string back(int steps)` Move `steps` back in history. If you can only return `x` steps in the history and `steps > x`, you will return only `x` steps. Return the current `url` after moving back in history at most `steps`.
* `string forward(int steps)` Move `steps` forward in history. If you can only forward `x` steps in the history and `steps > x`, you will forward only `x` steps. Return the current `url` after forwarding in history at most `steps`.
```

Example:

Input:

```
["BrowserHistory","visit","visit","visit","back","back","forward","visit","forward","back","back"] [["leetcode.com"],["google.com"],["facebook.com"],["youtube.com"],[1],[1],[1],["linkedin.com"],[2],[2],[7]]
Output: [null,null,null,null,"facebook.com","google.com","facebook.com",null,"linkedin.com","google.com","leetcode.com"]
Explanation: BrowserHistory browserHistory = new BrowserHistory("leetcode.com"); browserHistory.visit("google.com"); // You are in "leetcode.com". Visit "google.com" browserHistory.visit("facebook.com"); // You are in "google.com". Visit "facebook.com" browserHistory.visit("youtube.com"); // You are in "facebook.com". Visit "youtube.com" browserHistory.back(1); // You are in "youtube.com", move back to "facebook.com" return "facebook.com" browserHistory.back(1); // You are in "facebook.com", move back to "google.com" return "google.com" browserHistory.forward(1); //
```

You are in "google.com", move forward to "facebook.com" return "facebook.com"
browserHistory.visit("linkedin.com"); // You are in "facebook.com". Visit "linkedin.com"
browserHistory.forward(2); // You are in "linkedin.com", you cannot move forward any steps.
browserHistory.back(2); // You are in "linkedin.com", move back two steps to "facebook.com"
then to "google.com". return "google.com" browserHistory.back(7); // You are in "google.com",
you can move back only one step to "leetcode.com". return "leetcode.com"

****Constraints:****

* `1` <= homepage.length <= 20 * `1` <= url.length <= 20 * `1` <= steps <= 100 * `homepage`
and `url` consist of `.` or lower case English letters. * At most `5000` calls will be made to
`visit`, `back`, and `forward`.

Code Snippets

C++:

```
class BrowserHistory {
public:
    BrowserHistory(string homepage) {

    }

    void visit(string url) {

    }

    string back(int steps) {

    }

    string forward(int steps) {

    }
};

/**
 * Your BrowserHistory object will be instantiated and called as such:
 * BrowserHistory* obj = new BrowserHistory(homepage);
 * obj->visit(url);
 * string param_2 = obj->back(steps);
 */
```

```
* string param_3 = obj->forward(steps);  
*/
```

Java:

```
class BrowserHistory {  
  
    public BrowserHistory(String homepage) {  
  
    }  
  
    public void visit(String url) {  
  
    }  
  
    public String back(int steps) {  
  
    }  
  
    public String forward(int steps) {  
  
    }  
}  
  
/**  
 * Your BrowserHistory object will be instantiated and called as such:  
 * BrowserHistory obj = new BrowserHistory(homepage);  
 * obj.visit(url);  
 * String param_2 = obj.back(steps);  
 * String param_3 = obj.forward(steps);  
 */
```

Python3:

```
class BrowserHistory:  
  
    def __init__(self, homepage: str):  
  
  
    def visit(self, url: str) -> None:
```

```
def back(self, steps: int) -> str:
```

```
def forward(self, steps: int) -> str:
```

```
# Your BrowserHistory object will be instantiated and called as such:
```

```
# obj = BrowserHistory(homepage)
```

```
# obj.visit(url)
```

```
# param_2 = obj.back(steps)
```

```
# param_3 = obj.forward(steps)
```