

Problem 3470: Permutations IV

Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given two integers,

n

and

k

, an

alternating permutation

is a permutation of the first

n

positive integers such that no

two

adjacent elements are both odd or both even.

Return the

k -th

alternating permutation

sorted in

lexicographical order

. If there are fewer than

k

valid

alternating permutations

, return an empty list.

Example 1:

Input:

$n = 4, k = 6$

Output:

[3,4,1,2]

Explanation:

The lexicographically-sorted alternating permutations of

[1, 2, 3, 4]

are:

[1, 2, 3, 4]

[1, 4, 3, 2]

[2, 1, 4, 3]

[2, 3, 4, 1]

[3, 2, 1, 4]

[3, 4, 1, 2]

← 6th permutation

[4, 1, 2, 3]

[4, 3, 2, 1]

Since

$k = 6$

, we return

[3, 4, 1, 2]

.

Example 2:

Input:

$n = 3, k = 2$

Output:

[3,2,1]

Explanation:

The lexicographically-sorted alternating permutations of

[1, 2, 3]

are:

[1, 2, 3]

[3, 2, 1]

← 2nd permutation

Since

$k = 2$

, we return

[3, 2, 1]

.

Example 3:

Input:

$n = 2, k = 3$

Output:

[]

Explanation:

The lexicographically-sorted alternating permutations of

[1, 2]

are:

[1, 2]

[2, 1]

There are only 2 alternating permutations, but

$k = 3$

, which is out of range. Thus, we return an empty list

[]

.

Constraints:

$1 \leq n \leq 100$

$1 \leq k \leq 10$

15

Code Snippets

C++:

```
class Solution {
public:
    vector<int> permute(int n, long long k) {

    }
};
```

Java:

```
class Solution {
    public int[] permute(int n, long k) {

    }
}
```

Python3:

```

class Solution:
    def permute(self, n: int, k: int) -> List[int]:

```

Python:

```

class Solution(object):
    def permute(self, n, k):
        """
        :type n: int
        :type k: int
        :rtype: List[int]
        """

```

JavaScript:

```

/**
 * @param {number} n
 * @param {number} k
 * @return {number[]}
 */
var permute = function(n, k) {

};

```

TypeScript:

```

function permute(n: number, k: number): number[] {

};

```

C#:

```

public class Solution {
    public int[] Permute(int n, long k) {

    }
}

```

C:

```

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */

```

```
int* permute(int n, long long k, int* returnSize) {  
  
}
```

Go:

```
func permute(n int, k int64) []int {  
  
}
```

Kotlin:

```
class Solution {  
    fun permute(n: Int, k: Long): IntArray {  
  
    }  
}
```

Swift:

```
class Solution {  
    func permute(_ n: Int, _ k: Int) -> [Int] {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn permute(n: i32, k: i64) -> Vec<i32> {  
  
    }  
}
```

Ruby:

```
# @param {Integer} n  
# @param {Integer} k  
# @return {Integer[]}  
def permute(n, k)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param Integer $n  
     * @param Integer $k  
     * @return Integer[]  
     */  
    function permute($n, $k) {  
  
    }  
}
```

Dart:

```
class Solution {  
  List<int> permute(int n, int k) {  
  
  }  
}
```

Scala:

```
object Solution {  
  def permute(n: Int, k: Long): Array[Int] = {  
  
  }  
}
```

Elixir:

```
defmodule Solution do  
  @spec permute(n :: integer, k :: integer) :: [integer]  
  def permute(n, k) do  
  
  end  
end
```

Erlang:

```
-spec permute(N :: integer(), K :: integer()) -> [integer()].  
permute(N, K) ->
```



```
.
```

Racket:

```
(define/contract (permute n k)
  (-> exact-integer? exact-integer? (listof exact-integer?))
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Permutations IV
 * Difficulty: Hard
 * Tags: array, graph, math, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    vector<int> permute(int n, long long k) {

    }
};
```

Java Solution:

```
/**
 * Problem: Permutations IV
 * Difficulty: Hard
 * Tags: array, graph, math, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */
```

```

class Solution {
public int[] permute(int n, long k) {

}

}

```

Python3 Solution:

```

"""
Problem: Permutations IV
Difficulty: Hard
Tags: array, graph, math, sort

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
def permute(self, n: int, k: int) -> List[int]:
# TODO: Implement optimized solution
pass

```

Python Solution:

```

class Solution(object):
def permute(self, n, k):
"""
:type n: int
:type k: int
:rtype: List[int]
"""

```

JavaScript Solution:

```

/**
 * Problem: Permutations IV
 * Difficulty: Hard
 * Tags: array, graph, math, sort
 */

```

```

* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

/**
 * @param {number} n
 * @param {number} k
 * @return {number[]}
 */
var permute = function(n, k) {

};

```

TypeScript Solution:

```

/**
 * Problem: Permutations IV
 * Difficulty: Hard
 * Tags: array, graph, math, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function permute(n: number, k: number): number[] {

};

```

C# Solution:

```

/*
 * Problem: Permutations IV
 * Difficulty: Hard
 * Tags: array, graph, math, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

```

```

public class Solution {
    public int[] Permute(int n, long k) {

    }
}

```

C Solution:

```

/*
 * Problem: Permutations IV
 * Difficulty: Hard
 * Tags: array, graph, math, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* permute(int n, long long k, int* returnSize) {

}

```

Go Solution:

```

// Problem: Permutations IV
// Difficulty: Hard
// Tags: array, graph, math, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func permute(n int, k int64) []int {

}

```

Kotlin Solution:

```

class Solution {
    fun permute(n: Int, k: Long): IntArray {

    }

}

```

Swift Solution:

```

class Solution {
    func permute(_ n: Int, _ k: Int) -> [Int] {

    }

}

```

Rust Solution:

```

// Problem: Permutations IV
// Difficulty: Hard
// Tags: array, graph, math, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn permute(n: i32, k: i64) -> Vec<i32> {

    }

}

```

Ruby Solution:

```

# @param {Integer} n
# @param {Integer} k
# @return {Integer[]}
def permute(n, k)

end

```

PHP Solution:

```

class Solution {

    /**
     * @param Integer $n
     * @param Integer $k
     * @return Integer[]
     */
    function permute($n, $k) {

    }

}

```

Dart Solution:

```

class Solution {
  List<int> permute(int n, int k) {

  }

}

```

Scala Solution:

```

object Solution {
  def permute(n: Int, k: Long): Array[Int] = {

  }

}

```

Elixir Solution:

```

defmodule Solution do
  @spec permute(n :: integer, k :: integer) :: [integer]
  def permute(n, k) do

  end
end

```

Erlang Solution:

```

-spec permute(N :: integer(), K :: integer()) -> [integer()].
permute(N, K) ->

.

```

Racket Solution:

```
(define/contract (permute n k)
  (-> exact-integer? exact-integer? (listof exact-integer?))
  )
```