

# Problem 3255: Find the Power of K-Size Subarrays II

## Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given an array of integers

nums

of length

n

and a

positive

integer

k

.

The

power

of an array is defined as:

Its

maximum

element if

all

of its elements are

consecutive

and

sorted

in

ascending

order.

-1 otherwise.

You need to find the

power

of all

subarrays

of

nums

of size

k

.

Return an integer array

results

of size

$n - k + 1$

, where

results[i]

is the

power

of

nums[i..(i + k - 1)]

.

Example 1:

Input:

nums = [1,2,3,4,3,2,5], k = 3

Output:

[3,4,-1,-1,-1]

Explanation:

There are 5 subarrays of

nums

of size 3:

[1, 2, 3]

with the maximum element 3.

[2, 3, 4]

with the maximum element 4.

[3, 4, 3]

whose elements are

not

consecutive.

[4, 3, 2]

whose elements are

not

sorted.

[3, 2, 5]

whose elements are

not

consecutive.

Example 2:

Input:

nums = [2,2,2,2,2], k = 4

Output:

[-1,-1]

Example 3:

Input:

nums = [3,2,3,2,3,2], k = 2

Output:

[-1,3,-1,3,-1]

Constraints:

$1 \leq n == \text{nums.length} \leq 10$

5

$1 \leq \text{nums}[i] \leq 10$

6

$1 \leq k \leq n$

## Code Snippets

**C++:**

```
class Solution {
public:
    vector<int> resultsArray(vector<int>& nums, int k) {

    }
};
```

### Java:

```
class Solution {  
    public int[] resultsArray(int[] nums, int k) {  
  
    }  
}
```

### Python3:

```
class Solution:  
    def resultsArray(self, nums: List[int], k: int) -> List[int]:
```

### Python:

```
class Solution(object):  
    def resultsArray(self, nums, k):  
        """  
        :type nums: List[int]  
        :type k: int  
        :rtype: List[int]  
        """
```

### JavaScript:

```
/**  
 * @param {number[]} nums  
 * @param {number} k  
 * @return {number[]}  
 */  
var resultsArray = function(nums, k) {  
  
};
```

### TypeScript:

```
function resultsArray(nums: number[], k: number): number[] {  
  
};
```

### C#:

```

public class Solution {
    public int[] ResultsArray(int[] nums, int k) {

    }
}

```

### C:

```

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* resultsArray(int* nums, int numsSize, int k, int* returnSize) {

}

```

### Go:

```

func resultsArray(nums []int, k int) []int {

}

```

### Kotlin:

```

class Solution {
    fun resultsArray(nums: IntArray, k: Int): IntArray {

    }
}

```

### Swift:

```

class Solution {
    func resultsArray(_ nums: [Int], _ k: Int) -> [Int] {

    }
}

```

### Rust:

```

impl Solution {
    pub fn results_array(nums: Vec<i32>, k: i32) -> Vec<i32> {

    }
}

```

```
}
```

### Ruby:

```
# @param {Integer[]} nums
# @param {Integer} k
# @return {Integer[]}
def results_array(nums, k)

end
```

### PHP:

```
class Solution {

    /**
     * @param Integer[] $nums
     * @param Integer $k
     * @return Integer[]
     */
    function resultsArray($nums, $k) {

    }

}
```

### Dart:

```
class Solution {
  List<int> resultsArray(List<int> nums, int k) {

  }

}
```

### Scala:

```
object Solution {
  def resultsArray(nums: Array[Int], k: Int): Array[Int] = {

  }

}
```

### Elixir:



```

defmodule Solution do
  @spec results_array(nums :: [integer], k :: integer) :: [integer]
  def results_array(nums, k) do

  end

end

```

## Erlang:

```

-spec results_array(Nums :: [integer()], K :: integer()) -> [integer()].
results_array(Nums, K) ->
.

```

## Racket:

```

(define/contract (results-array nums k)
  (-> (listof exact-integer?) exact-integer? (listof exact-integer?))
  )

```

# Solutions

## C++ Solution:

```

/*
 * Problem: Find the Power of K-Size Subarrays II
 * Difficulty: Medium
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    vector<int> resultsArray(vector<int>& nums, int k) {

    }

};

```

## Java Solution:

```

/**
 * Problem: Find the Power of K-Size Subarrays II
 * Difficulty: Medium
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public int[] resultsArray(int[] nums, int k) {

}
}

```

### Python3 Solution:

```

"""
Problem: Find the Power of K-Size Subarrays II
Difficulty: Medium
Tags: array, sort

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
def resultsArray(self, nums: List[int], k: int) -> List[int]:
# TODO: Implement optimized solution
pass

```

### Python Solution:

```

class Solution(object):
def resultsArray(self, nums, k):
"""
:type nums: List[int]
:type k: int
:rtype: List[int]
"""

```

## JavaScript Solution:

```
/**
 * Problem: Find the Power of K-Size Subarrays II
 * Difficulty: Medium
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number[]} nums
 * @param {number} k
 * @return {number[]}
 */
var resultsArray = function(nums, k) {

};
```

## TypeScript Solution:

```
/**
 * Problem: Find the Power of K-Size Subarrays II
 * Difficulty: Medium
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function resultsArray(nums: number[], k: number): number[] {

};
```

## C# Solution:

```
/*
 * Problem: Find the Power of K-Size Subarrays II
 * Difficulty: Medium
```

```

* Tags: array, sort
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

public class Solution {
public int[] ResultsArray(int[] nums, int k) {

}
}

```

### C Solution:

```

/*
* Problem: Find the Power of K-Size Subarrays II
* Difficulty: Medium
* Tags: array, sort
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

/**
* Note: The returned array must be malloced, assume caller calls free().
*/
int* resultsArray(int* nums, int numsSize, int k, int* returnSize) {

}

```

### Go Solution:

```

// Problem: Find the Power of K-Size Subarrays II
// Difficulty: Medium
// Tags: array, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

```

```
func resultsArray(nums []int, k int) []int {

}
```

### Kotlin Solution:

```
class Solution {
    fun resultsArray(nums: IntArray, k: Int): IntArray {

    }
}
```

### Swift Solution:

```
class Solution {
    func resultsArray(_ nums: [Int], _ k: Int) -> [Int] {

    }
}
```

### Rust Solution:

```
// Problem: Find the Power of K-Size Subarrays II
// Difficulty: Medium
// Tags: array, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn results_array(nums: Vec<i32>, k: i32) -> Vec<i32> {

    }
}
```

### Ruby Solution:

```
# @param {Integer[]} nums
# @param {Integer} k
```

```
# @return {Integer[]}  
def results_array(nums, k)  
  
end
```

### PHP Solution:

```
class Solution {  
  
    /**  
     * @param Integer[] $nums  
     * @param Integer $k  
     * @return Integer[]  
     */  
    function resultsArray($nums, $k) {  
  
    }  
}
```

### Dart Solution:

```
class Solution {  
    List<int> resultsArray(List<int> nums, int k) {  
  
    }  
}
```

### Scala Solution:

```
object Solution {  
    def resultsArray(nums: Array[Int], k: Int): Array[Int] = {  
  
    }  
}
```

### Elixir Solution:

```
defmodule Solution do  
    @spec results_array(nums :: [integer], k :: integer) :: [integer]  
    def results_array(nums, k) do
```

```
end  
end
```

### Erlang Solution:

```
-spec results_array(Nums :: [integer()], K :: integer()) -> [integer()].  
results_array(Nums, K) ->  
.
```

### Racket Solution:

```
(define/contract (results-array nums k)  
  (-> (listof exact-integer?) exact-integer? (listof exact-integer?))  
  )
```