

Problem 3365: Rearrange K Substrings to Form Target String

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given two strings

s

and

t

, both of which are anagrams of each other, and an integer

k

.

Your task is to determine whether it is possible to split the string

s

into

k

equal-sized substrings, rearrange the substrings, and concatenate them in

any order

to create a new string that matches the given string

t

.

Return

true

if this is possible, otherwise, return

false

.

An

anagram

is a word or phrase formed by rearranging the letters of a different word or phrase, using all the original letters exactly once.

A

substring

is a contiguous

non-empty

sequence of characters within a string.

Example 1:

Input:

s = "abcd", t = "cdab", k = 2

Output:

true

Explanation:

Split

s

into 2 substrings of length 2:

["ab", "cd"]

.

Rearranging these substrings as

["cd", "ab"]

, and then concatenating them results in

"cdab"

, which matches

t

.

Example 2:

Input:

s = "aabbcc", t = "bbaacc", k = 3

Output:

true

Explanation:

Split

s

into 3 substrings of length 2:

["aa", "bb", "cc"]

.

Rearranging these substrings as

["bb", "aa", "cc"]

, and then concatenating them results in

"bbaacc"

, which matches

t

.

Example 3:

Input:

s = "aabbcc", t = "bbaacc", k = 2

Output:

false

Explanation:

Split

s

into 2 substrings of length 3:

["aab", "bcc"]

.

These substrings cannot be rearranged to form

t = "bbaacc"

, so the output is

false

.

Constraints:

$1 \leq s.length == t.length \leq 2 * 10$

5

$1 \leq k \leq s.length$

s.length

is divisible by

k

.

s

and

t

consist only of lowercase English letters.

The input is generated such that

s

and

t

are anagrams of each other.

Code Snippets

C++:

```
class Solution {  
public:  
    bool isPossibleToRearrange(string s, string t, int k) {  
  
    }  
};
```

Java:

```
class Solution {  
    public boolean isPossibleToRearrange(String s, String t, int k) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def isPossibleToRearrange(self, s: str, t: str, k: int) -> bool:
```

Python:

```
class Solution(object):
    def isPossibleToRearrange(self, s, t, k):
        """
        :type s: str
        :type t: str
        :type k: int
        :rtype: bool
        """
```

JavaScript:

```
/**
 * @param {string} s
 * @param {string} t
 * @param {number} k
 * @return {boolean}
 */
var isPossibleToRearrange = function(s, t, k) {

};
```

TypeScript:

```
function isPossibleToRearrange(s: string, t: string, k: number): boolean {

};
```

C#:

```
public class Solution {
    public bool IsPossibleToRearrange(string s, string t, int k) {

    }
}
```

C:

```
bool isPossibleToRearrange(char* s, char* t, int k) {

}
```

Go:

```
func isPossibleToRearrange(s string, t string, k int) bool {  
  
}
```

Kotlin:

```
class Solution {  
    fun isPossibleToRearrange(s: String, t: String, k: Int): Boolean {  
  
    }  
}
```

Swift:

```
class Solution {  
    func isPossibleToRearrange(_ s: String, _ t: String, _ k: Int) -> Bool {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn is_possible_to_rearrange(s: String, t: String, k: i32) -> bool {  
  
    }  
}
```

Ruby:

```
# @param {String} s  
# @param {String} t  
# @param {Integer} k  
# @return {Boolean}  
def is_possible_to_rearrange(s, t, k)  
  
end
```

PHP:


```

class Solution {

    /**
     * @param String $s
     * @param String $t
     * @param Integer $k
     * @return Boolean
     */
    function isPossibleToRearrange($s, $t, $k) {

    }

}

```

Dart:

```

class Solution {
    bool isPossibleToRearrange(String s, String t, int k) {

    }

}

```

Scala:

```

object Solution {
    def isPossibleToRearrange(s: String, t: String, k: Int): Boolean = {

    }

}

```

Elixir:

```

defmodule Solution do
    @spec is_possible_to_rearrange(s :: String.t, t :: String.t, k :: integer) ::
    boolean
    def is_possible_to_rearrange(s, t, k) do

    end

end

```

Erlang:

```

-spec is_possible_to_rearrange(S :: unicode:unicode_binary(), T ::
unicode:unicode_binary(), K :: integer()) -> boolean().

```

```
is_possible_to_rearrange(S, T, K) ->
.
```

Racket:

```
(define/contract (is-possible-to-rearrange s t k)
  (-> string? string? exact-integer? boolean?)
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Rearrange K Substrings to Form Target String
 * Difficulty: Medium
 * Tags: string, tree, hash, sort
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

class Solution {
public:
    bool isPossibleToRearrange(string s, string t, int k) {

    }
};
```

Java Solution:

```
/**
 * Problem: Rearrange K Substrings to Form Target String
 * Difficulty: Medium
 * Tags: string, tree, hash, sort
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */
```

```

*/

class Solution {
public boolean isPossibleToRearrange(String s, String t, int k) {

}

}

```

Python3 Solution:

```

"""
Problem: Rearrange K Substrings to Form Target String
Difficulty: Medium
Tags: string, tree, hash, sort

Approach: String manipulation with hash map or two pointers
Time Complexity: O(n) or O(n log n)
Space Complexity: O(h) for recursion stack where h is height
"""

class Solution:
def isPossibleToRearrange(self, s: str, t: str, k: int) -> bool:
# TODO: Implement optimized solution
pass

```

Python Solution:

```

class Solution(object):
def isPossibleToRearrange(self, s, t, k):
"""
:type s: str
:type t: str
:type k: int
:rtype: bool
"""

```

JavaScript Solution:

```

/**
* Problem: Rearrange K Substrings to Form Target String
* Difficulty: Medium

```

```

* Tags: string, tree, hash, sort
*
* Approach: String manipulation with hash map or two pointers
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(h) for recursion stack where h is height
*/

/**
* @param {string} s
* @param {string} t
* @param {number} k
* @return {boolean}
*/
var isPossibleToRearrange = function(s, t, k) {

};

```

TypeScript Solution:

```

/**
* Problem: Rearrange K Substrings to Form Target String
* Difficulty: Medium
* Tags: string, tree, hash, sort
*
* Approach: String manipulation with hash map or two pointers
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(h) for recursion stack where h is height
*/

function isPossibleToRearrange(s: string, t: string, k: number): boolean {

};

```

C# Solution:

```

/*
* Problem: Rearrange K Substrings to Form Target String
* Difficulty: Medium
* Tags: string, tree, hash, sort
*
* Approach: String manipulation with hash map or two pointers

```

```

* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(h) for recursion stack where h is height
*/

public class Solution {
public bool IsPossibleToRearrange(string s, string t, int k) {

}
}

```

C Solution:

```

/*
* Problem: Rearrange K Substrings to Form Target String
* Difficulty: Medium
* Tags: string, tree, hash, sort
*
* Approach: String manipulation with hash map or two pointers
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(h) for recursion stack where h is height
*/

bool isPossibleToRearrange(char* s, char* t, int k) {

}

```

Go Solution:

```

// Problem: Rearrange K Substrings to Form Target String
// Difficulty: Medium
// Tags: string, tree, hash, sort
//
// Approach: String manipulation with hash map or two pointers
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

func isPossibleToRearrange(s string, t string, k int) bool {

}

```

Kotlin Solution:

```

class Solution {
    fun isPossibleToRearrange(s: String, t: String, k: Int): Boolean {

    }
}

```

Swift Solution:

```

class Solution {
    func isPossibleToRearrange(_ s: String, _ t: String, _ k: Int) -> Bool {

    }
}

```

Rust Solution:

```

// Problem: Rearrange K Substrings to Form Target String
// Difficulty: Medium
// Tags: string, tree, hash, sort
//
// Approach: String manipulation with hash map or two pointers
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

impl Solution {
    pub fn is_possible_to_rearrange(s: String, t: String, k: i32) -> bool {

    }
}

```

Ruby Solution:

```

# @param {String} s
# @param {String} t
# @param {Integer} k
# @return {Boolean}
def is_possible_to_rearrange(s, t, k)

end

```

PHP Solution:

```

class Solution {

    /**
     * @param String $s
     * @param String $t
     * @param Integer $k
     * @return Boolean
     */
    function isPossibleToRearrange($s, $t, $k) {

    }

}

```

Dart Solution:

```

class Solution {
  bool isPossibleToRearrange(String s, String t, int k) {

  }

}

```

Scala Solution:

```

object Solution {
  def isPossibleToRearrange(s: String, t: String, k: Int): Boolean = {

  }

}

```

Elixir Solution:

```

defmodule Solution do
  @spec is_possible_to_rearrange(s :: String.t, t :: String.t, k :: integer) ::
    boolean
  def is_possible_to_rearrange(s, t, k) do

  end

end

```

Erlang Solution:

```
-spec is_possible_to_rearrange(S :: unicode:unicode_binary(), T ::  
unicode:unicode_binary(), K :: integer()) -> boolean().  
is_possible_to_rearrange(S, T, K) ->  
.
```

Racket Solution:

```
(define/contract (is-possible-to-rearrange s t k)  
  (-> string? string? exact-integer? boolean?)  
)
```