

Problem 413: Arithmetic Slices

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

An integer array is called arithmetic if it consists of

at least three elements

and if the difference between any two consecutive elements is the same.

For example,

[1,3,5,7,9]

,

[7,7,7,7]

, and

[3,-1,-5,-9]

are arithmetic sequences.

Given an integer array

nums

, return

the number of arithmetic

subarrays

of

nums

.

A

subarray

is a contiguous subsequence of the array.

Example 1:

Input:

nums = [1,2,3,4]

Output:

3

Explanation:

We have 3 arithmetic slices in nums: [1, 2, 3], [2, 3, 4] and [1,2,3,4] itself.

Example 2:

Input:

nums = [1]

Output:

0

Constraints:

$1 \leq \text{nums.length} \leq 5000$

$-1000 \leq \text{nums}[i] \leq 1000$

Code Snippets

C++:

```
class Solution {
public:
    int numberOfArithmeticSlices(vector<int>& nums) {

    }
};
```

Java:

```
class Solution {
    public int numberOfArithmeticSlices(int[] nums) {

    }
}
```

Python3:

```
class Solution:
    def numberOfArithmeticSlices(self, nums: List[int]) -> int:
```

Python:

```
class Solution(object):
    def numberOfArithmeticSlices(self, nums):
        """
        :type nums: List[int]
        :rtype: int
        """
```

JavaScript:

```

/**
 * @param {number[]} nums
 * @return {number}
 */
var numberOfArithmeticSlices = function(nums) {

};

```

TypeScript:

```

function numberOfArithmeticSlices(nums: number[]): number {

};

```

C#:

```

public class Solution {
    public int NumberOfArithmeticSlices(int[] nums) {

    }
}

```

C:

```

int numberOfArithmeticSlices(int* nums, int numsSize) {

}

```

Go:

```

func numberOfArithmeticSlices(nums []int) int {

}

```

Kotlin:

```

class Solution {
    fun numberOfArithmeticSlices(nums: IntArray): Int {

    }
}

```

Swift:

```

class Solution {
  func numberOfArithmeticSlices(_ nums: [Int]) -> Int {

  }
}

```

Rust:

```

impl Solution {
  pub fn number_of_arithmetic_slices(nums: Vec<i32>) -> i32 {

  }
}

```

Ruby:

```

# @param {Integer[]} nums
# @return {Integer}
def number_of_arithmetic_slices(nums)

end

```

PHP:

```

class Solution {

  /**
   * @param Integer[] $nums
   * @return Integer
   */
  function numberOfArithmeticSlices($nums) {

  }
}

```

Dart:

```

class Solution {
  int numberOfArithmeticSlices(List<int> nums) {

  }
}

```

Scala:

```
object Solution {  
  def numberOfArithmeticSlices(nums: Array[Int]): Int = {  
  
  }  
}
```

Elixir:

```
defmodule Solution do  
  @spec number_of_arithmetic_slices(nums :: [integer]) :: integer  
  def number_of_arithmetic_slices(nums) do  
  
  end  
end
```

Erlang:

```
-spec number_of_arithmetic_slices(Nums :: [integer()]) -> integer().  
number_of_arithmetic_slices(Nums) ->  
.
```

Racket:

```
(define/contract (number-of-arithmetic-slices nums)  
  (-> (listof exact-integer?) exact-integer?)  
)
```

Solutions

C++ Solution:

```
/*  
 * Problem: Arithmetic Slices  
 * Difficulty: Medium  
 * Tags: array, dp  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) or O(n * m) for DP table  
 */
```

```

class Solution {
public:
    int numberOfArithmeticSlices(vector<int>& nums) {

    }

};

```

Java Solution:

```

/**
 * Problem: Arithmetic Slices
 * Difficulty: Medium
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
    public int numberOfArithmeticSlices(int[] nums) {

    }

}

```

Python3 Solution:

```

"""
Problem: Arithmetic Slices
Difficulty: Medium
Tags: array, dp

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) or O(n * m) for DP table
"""

class Solution:
    def numberOfArithmeticSlices(self, nums: List[int]) -> int:
        # TODO: Implement optimized solution

```

```
pass
```

Python Solution:

```
class Solution(object):
    def numberOfArithmeticSlices(self, nums):
        """
        :type nums: List[int]
        :rtype: int
        """
```

JavaScript Solution:

```
/**
 * Problem: Arithmetic Slices
 * Difficulty: Medium
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
 * @param {number[]} nums
 * @return {number}
 */
var numberOfArithmeticSlices = function(nums) {

};
```

TypeScript Solution:

```
/**
 * Problem: Arithmetic Slices
 * Difficulty: Medium
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
```



```

*/

function numberOfArithmeticSlices(nums: number[]): number {

};

```

C# Solution:

```

/*
 * Problem: Arithmetic Slices
 * Difficulty: Medium
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

public class Solution {
    public int NumberOfArithmeticSlices(int[] nums) {

    }
}

```

C Solution:

```

/*
 * Problem: Arithmetic Slices
 * Difficulty: Medium
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

int numberOfArithmeticSlices(int* nums, int numsSize) {

}

```

Go Solution:

```

// Problem: Arithmetic Slices
// Difficulty: Medium
// Tags: array, dp
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

func numberOfArithmeticSlices(nums []int) int {

}

```

Kotlin Solution:

```

class Solution {
    fun numberOfArithmeticSlices(nums: IntArray): Int {

    }
}

```

Swift Solution:

```

class Solution {
    func numberOfArithmeticSlices(_ nums: [Int]) -> Int {

    }
}

```

Rust Solution:

```

// Problem: Arithmetic Slices
// Difficulty: Medium
// Tags: array, dp
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

impl Solution {
    pub fn number_of_arithmetic_slices(nums: Vec<i32>) -> i32 {

    }
}

```

```
}
```

Ruby Solution:

```
# @param {Integer[]} nums
# @return {Integer}
def number_of_arithmetic_slices(nums)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $nums
     * @return Integer
     */
    function numberOfArithmeticSlices($nums) {

    }

}
```

Dart Solution:

```
class Solution {
  int numberOfArithmeticSlices(List<int> nums) {

  }

}
```

Scala Solution:

```
object Solution {
  def numberOfArithmeticSlices(nums: Array[Int]): Int = {

  }

}
```

Elixir Solution:

```
defmodule Solution do
  @spec number_of_arithmetic_slices(nums :: [integer]) :: integer
  def number_of_arithmetic_slices(nums) do

  end
end
```

Erlang Solution:

```
-spec number_of_arithmetic_slices(Nums :: [integer()]) -> integer().
number_of_arithmetic_slices(Nums) ->
.
```

Racket Solution:

```
(define/contract (number-of-arithmetic-slices nums)
  (-> (listof exact-integer?) exact-integer?)
)
```