

Problem 2144: Minimum Cost of Buying Candies With Discount

Problem Information

Difficulty: Easy

Acceptance Rate: 62.56%

Paid Only: No

Tags: Array, Greedy, Sorting

Problem Description

A shop is selling candies at a discount. For **every two** candies sold, the shop gives a **third** candy for **free**.

The customer can choose **any** candy to take away for free as long as the cost of the chosen candy is less than or equal to the **minimum** cost of the two candies bought.

* For example, if there are 4 candies with costs 1, 2, 3, and 4, and the customer buys candies with costs 2 and 3, they can take the candy with cost 1 for free, but not the candy with cost 4.

Given a 0-indexed integer array `cost`, where `cost[i]` denotes the cost of the `i`th candy, return the minimum cost of buying all the candies.

Example 1:

Input: `cost = [1,2,3]` **Output:** 5 **Explanation:** We buy the candies with costs 2 and 3, and take the candy with cost 1 for free. The total cost of buying all candies is $2 + 3 = 5$. This is the **only** way we can buy the candies. Note that we cannot buy candies with costs 1 and 3, and then take the candy with cost 2 for free. The cost of the free candy has to be less than or equal to the minimum cost of the purchased candies.

Example 2:

Input: `cost = [6,5,7,9,2,2]` **Output:** 23 **Explanation:** The way in which we can get the minimum cost is described below: - Buy candies with costs 9 and 7 - Take the candy with cost

6 for free - We buy candies with costs 5 and 2 - Take the last remaining candy with cost 2 for free Hence, the minimum cost to buy all candies is $9 + 7 + 5 + 2 = 23$.

Example 3:

Input: cost = [5,5] **Output:** 10 **Explanation:** Since there are only 2 candies, we buy both of them. There is not a third candy we can take for free. Hence, the minimum cost to buy all candies is $5 + 5 = 10$.

Constraints:

$1 \leq \text{cost.length} \leq 100$ $1 \leq \text{cost}[i] \leq 100$

Code Snippets

C++:

```
class Solution {
public:
    int minimumCost(vector<int>& cost) {

    }
};
```

Java:

```
class Solution {
    public int minimumCost(int[] cost) {

    }
}
```

Python3:

```
class Solution:
    def minimumCost(self, cost: List[int]) -> int:
```