

Problem 2052: Minimum Cost to Separate Sentence Into Rows

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given a string

sentence

containing words separated by spaces, and an integer

k

. Your task is to separate

sentence

into

rows

where the number of characters in each row is

at most

k

. You may assume that

sentence

does not begin or end with a space, and the words in

sentence

are separated by a single space.

You can split

sentence

into rows by inserting line breaks between words in

sentence

. A word

cannot

be split between two rows. Each word must be used exactly once, and the word order cannot be rearranged. Adjacent words in a row should be separated by a single space, and rows should not begin or end with spaces.

The

cost

of a row with length

n

is

$(k - n)$

2

, and the

total cost

is the sum of the

costs

for all rows

except

the last one.

For example if

sentence = "i love leetcode"

and

k = 12

:

Separating

sentence

into

"i"

,

"love"

, and

"leetcode"

has a cost of

$(12 - 1)$

2

$+ (12 - 4)$

2

$= 185$

.

Separating

sentence

into

"i love"

, and

"leetcode"

has a cost of

$(12 - 6)$

2

$= 36$

.

Separating

sentence

into

"i"

, and

"love leetcode"

is not possible because the length of

"love leetcode"

is greater than

k

.

Return

the

minimum

possible total cost of separating

sentence

into rows.

Example 1:

Input:

sentence = "i love leetcode", k = 12

Output:

Explanation:

Separating sentence into "i", "love", and "leetcode" has a cost of $(12 - 1)$

2

+ $(12 - 4)$

2

= 185. Separating sentence into "i love", and "leetcode" has a cost of $(12 - 6)$

2

= 36. Separating sentence into "i", "love leetcode" is not possible because "love leetcode" has length 13. 36 is the minimum possible total cost so return it.

Example 2:

Input:

sentence = "apples and bananas taste great", k = 7

Output:

21

Explanation

Separating sentence into "apples", "and", "bananas", "taste", and "great" has a cost of $(7 - 6)$

2

+ $(7 - 3)$

2

+ $(7 - 7)$

2

+ (7 - 5)

2

= 21. 21 is the minimum possible total cost so return it.

Example 3:

Input:

sentence = "a", k = 5

Output:

0

Explanation:

The cost of the last row is not included in the total cost, and since there is only one row, return 0.

Constraints:

$1 \leq \text{sentence.length} \leq 5000$

$1 \leq k \leq 5000$

The length of each word in

sentence

is at most

k

.

sentence

consists of only lowercase English letters and spaces.

sentence

does not begin or end with a space.

Words in

sentence

are separated by a single space.

Code Snippets

C++:

```
class Solution {  
public:  
    int minimumCost(string sentence, int k) {  
  
    }  
};
```

Java:

```
class Solution {  
    public int minimumCost(String sentence, int k) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def minimumCost(self, sentence: str, k: int) -> int:
```

Python:


```

class Solution(object):
def minimumCost(self, sentence, k):
    """
    :type sentence: str
    :type k: int
    :rtype: int
    """

```

JavaScript:

```

/**
 * @param {string} sentence
 * @param {number} k
 * @return {number}
 */
var minimumCost = function(sentence, k) {

};

```

TypeScript:

```

function minimumCost(sentence: string, k: number): number {

};

```

C#:

```

public class Solution {
    public int MinimumCost(string sentence, int k) {

    }
}

```

C:

```

int minimumCost(char* sentence, int k) {

}

```

Go:

```

func minimumCost(sentence string, k int) int {

```

```
}
```

Kotlin:

```
class Solution {  
    fun minimumCost(sentence: String, k: Int): Int {  
  
    }  
}
```

Swift:

```
class Solution {  
    func minimumCost(_ sentence: String, _ k: Int) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn minimum_cost(sentence: String, k: i32) -> i32 {  
  
    }  
}
```

Ruby:

```
# @param {String} sentence  
# @param {Integer} k  
# @return {Integer}  
def minimum_cost(sentence, k)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param String $sentence  
     * @param Integer $k
```

```

* @return Integer
*/
function minimumCost($sentence, $k) {

}

}

```

Dart:

```

class Solution {
  int minimumCost(String sentence, int k) {

  }

}

```

Scala:

```

object Solution {
  def minimumCost(sentence: String, k: Int): Int = {

  }

}

```

Elixir:

```

defmodule Solution do
  @spec minimum_cost(sentence :: String.t, k :: integer) :: integer
  def minimum_cost(sentence, k) do

  end

end

```

Erlang:

```

-spec minimum_cost(Sentence :: unicode:unicode_binary(), K :: integer()) ->
integer().
minimum_cost(Sentence, K) ->
.

```

Racket:

```
(define/contract (minimum-cost sentence k)
  (-> string? exact-integer? exact-integer?)
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Minimum Cost to Separate Sentence Into Rows
 * Difficulty: Medium
 * Tags: array, string, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
public:
    int minimumCost(string sentence, int k) {

    }
};
```

Java Solution:

```
/**
 * Problem: Minimum Cost to Separate Sentence Into Rows
 * Difficulty: Medium
 * Tags: array, string, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
    public int minimumCost(String sentence, int k) {

    }
}
```

```
}
```

Python3 Solution:

```
"""
Problem: Minimum Cost to Separate Sentence Into Rows
Difficulty: Medium
Tags: array, string, dp

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) or O(n * m) for DP table
"""

class Solution:
    def minimumCost(self, sentence: str, k: int) -> int:
        # TODO: Implement optimized solution
        pass
```

Python Solution:

```
class Solution(object):
    def minimumCost(self, sentence, k):
        """
        :type sentence: str
        :type k: int
        :rtype: int
        """
```

JavaScript Solution:

```
/**
 * Problem: Minimum Cost to Separate Sentence Into Rows
 * Difficulty: Medium
 * Tags: array, string, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */
```

```

/**
 * @param {string} sentence
 * @param {number} k
 * @return {number}
 */
var minimumCost = function(sentence, k) {

};

```

TypeScript Solution:

```

/**
 * Problem: Minimum Cost to Separate Sentence Into Rows
 * Difficulty: Medium
 * Tags: array, string, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

function minimumCost(sentence: string, k: number): number {

};

```

C# Solution:

```

/*
 * Problem: Minimum Cost to Separate Sentence Into Rows
 * Difficulty: Medium
 * Tags: array, string, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

public class Solution {
    public int MinimumCost(string sentence, int k) {

    }
}

```

```
}
```

C Solution:

```
/*
 * Problem: Minimum Cost to Separate Sentence Into Rows
 * Difficulty: Medium
 * Tags: array, string, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

int minimumCost(char* sentence, int k) {

}
```

Go Solution:

```
// Problem: Minimum Cost to Separate Sentence Into Rows
// Difficulty: Medium
// Tags: array, string, dp
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

func minimumCost(sentence string, k int) int {

}
```

Kotlin Solution:

```
class Solution {
    fun minimumCost(sentence: String, k: Int): Int {

    }
}
```

Swift Solution:

```

class Solution {
    func minimumCost(_ sentence: String, _ k: Int) -> Int {

    }
}

```

Rust Solution:

```

// Problem: Minimum Cost to Separate Sentence Into Rows
// Difficulty: Medium
// Tags: array, string, dp
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

impl Solution {
    pub fn minimum_cost(sentence: String, k: i32) -> i32 {

    }
}

```

Ruby Solution:

```

# @param {String} sentence
# @param {Integer} k
# @return {Integer}
def minimum_cost(sentence, k)

end

```

PHP Solution:

```

class Solution {

    /**
     * @param String $sentence
     * @param Integer $k
     * @return Integer
     */
    function minimumCost($sentence, $k) {

```



```
}  
}
```

Dart Solution:

```
class Solution {  
  int minimumCost(String sentence, int k) {  
  
  }  
}
```

Scala Solution:

```
object Solution {  
  def minimumCost(sentence: String, k: Int): Int = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec minimum_cost(sentence :: String.t, k :: integer) :: integer  
  def minimum_cost(sentence, k) do  
  
  end  
end
```

Erlang Solution:

```
-spec minimum_cost(Sentence :: unicode:unicode_binary(), K :: integer()) ->  
integer().  
minimum_cost(Sentence, K) ->  
.
```

Racket Solution:

```
(define/contract (minimum-cost sentence k)  
  (-> string? exact-integer? exact-integer?)  
)
```

