

# Problem 1942: The Number of the Smallest Unoccupied Chair

## Problem Information

Difficulty: Medium

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

There is a party where

$n$

friends numbered from

0

to

$n - 1$

are attending. There is an

infinite

number of chairs in this party that are numbered from

0

to

infinity

. When a friend arrives at the party, they sit on the unoccupied chair with the

smallest number

.

For example, if chairs

0

,

1

, and

5

are occupied when a friend comes, they will sit on chair number

2

.

When a friend leaves the party, their chair becomes unoccupied at the moment they leave. If another friend arrives at that same moment, they can sit in that chair.

You are given a

0-indexed

2D integer array

times

where

$\text{times}[i] = [\text{arrival}$

$i$

, leaving

i

]

, indicating the arrival and leaving times of the

i

th

friend respectively, and an integer

targetFriend

. All arrival times are

distinct

.

Return

the

chair number

that the friend numbered

targetFriend

will sit on

.

Example 1:

Input:

times = [[1,4],[2,3],[4,6]], targetFriend = 1

Output:

1

Explanation:

- Friend 0 arrives at time 1 and sits on chair 0. - Friend 1 arrives at time 2 and sits on chair 1. - Friend 1 leaves at time 3 and chair 1 becomes empty. - Friend 0 leaves at time 4 and chair 0 becomes empty. - Friend 2 arrives at time 4 and sits on chair 0. Since friend 1 sat on chair 1, we return 1.

Example 2:

Input:

times = [[3,10],[1,5],[2,6]], targetFriend = 0

Output:

2

Explanation:

- Friend 1 arrives at time 1 and sits on chair 0. - Friend 2 arrives at time 2 and sits on chair 1. - Friend 0 arrives at time 3 and sits on chair 2. - Friend 1 leaves at time 5 and chair 0 becomes empty. - Friend 2 leaves at time 6 and chair 1 becomes empty. - Friend 0 leaves at time 10 and chair 2 becomes empty. Since friend 0 sat on chair 2, we return 2.

Constraints:

n == times.length

2 <= n <= 10

4

times[i].length == 2

1 <= arrival

i

< leaving

i

<= 10

5

0 <= targetFriend <= n - 1

Each

arrival

i

time is

distinct

.

## Code Snippets

**C++:**

```
class Solution {  
public:  
    int smallestChair(vector<vector<int>>& times, int targetFriend) {  
  
    }  
};
```

### Java:

```
class Solution {  
    public int smallestChair(int[][] times, int targetFriend) {  
  
    }  
}
```

### Python3:

```
class Solution:  
    def smallestChair(self, times: List[List[int]], targetFriend: int) -> int:
```

### Python:

```
class Solution(object):  
    def smallestChair(self, times, targetFriend):  
        """  
        :type times: List[List[int]]  
        :type targetFriend: int  
        :rtype: int  
        """
```

### JavaScript:

```
/**  
 * @param {number[][]} times  
 * @param {number} targetFriend  
 * @return {number}  
 */  
var smallestChair = function(times, targetFriend) {  
  
};
```

### TypeScript:

```
function smallestChair(times: number[][], targetFriend: number): number {  
  
};
```

### C#:

```

public class Solution {
    public int SmallestChair(int[][] times, int targetFriend) {

    }
}

```

### C:

```

int smallestChair(int** times, int timesSize, int* timesColSize, int
targetFriend) {

}

```

### Go:

```

func smallestChair(times [][]int, targetFriend int) int {

}

```

### Kotlin:

```

class Solution {
    fun smallestChair(times: Array<IntArray>, targetFriend: Int): Int {

    }
}

```

### Swift:

```

class Solution {
    func smallestChair(_ times: [[Int]], _ targetFriend: Int) -> Int {

    }
}

```

### Rust:

```

impl Solution {
    pub fn smallest_chair(times: Vec<Vec<i32>>, target_friend: i32) -> i32 {

    }
}

```

## Ruby:

```
# @param {Integer[][]} times
# @param {Integer} target_friend
# @return {Integer}
def smallest_chair(times, target_friend)

end
```

## PHP:

```
class Solution {

    /**
     * @param Integer[][] $times
     * @param Integer $targetFriend
     * @return Integer
     */
    function smallestChair($times, $targetFriend) {

    }

}
```

## Dart:

```
class Solution {
  int smallestChair(List<List<int>> times, int targetFriend) {

  }
}
```

## Scala:

```
object Solution {
  def smallestChair(times: Array[Array[Int]], targetFriend: Int): Int = {

  }
}
```

## Elixir:

```
defmodule Solution do
  @spec smallest_chair(times :: [[integer]], target_friend :: integer) ::
```



```

integer
def smallest_chair(times, target_friend) do

end
end

```

### Erlang:

```

-spec smallest_chair(Times :: [[integer()]], TargetFriend :: integer()) ->
integer().
smallest_chair(Times, TargetFriend) ->
.

```

### Racket:

```

(define/contract (smallest-chair times targetFriend)
  (-> (listof (listof exact-integer?)) exact-integer? exact-integer?)
  )

```

## Solutions

### C++ Solution:

```

/*
 * Problem: The Number of the Smallest Unoccupied Chair
 * Difficulty: Medium
 * Tags: array, hash, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
public:
    int smallestChair(vector<vector<int>>& times, int targetFriend) {

    }
};

```

### Java Solution:

```

/**
 * Problem: The Number of the Smallest Unoccupied Chair
 * Difficulty: Medium
 * Tags: array, hash, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
public int smallestChair(int[][] times, int targetFriend) {

}
}

```

### Python3 Solution:

```

"""
Problem: The Number of the Smallest Unoccupied Chair
Difficulty: Medium
Tags: array, hash, queue, heap

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) for hash map
"""

class Solution:
def smallestChair(self, times: List[List[int]], targetFriend: int) -> int:
# TODO: Implement optimized solution
pass

```

### Python Solution:

```

class Solution(object):
def smallestChair(self, times, targetFriend):
"""
:type times: List[List[int]]
:type targetFriend: int
:rtype: int
"""

```

## JavaScript Solution:

```
/**
 * Problem: The Number of the Smallest Unoccupied Chair
 * Difficulty: Medium
 * Tags: array, hash, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

/**
 * @param {number[][]} times
 * @param {number} targetFriend
 * @return {number}
 */
var smallestChair = function(times, targetFriend) {

};
```

## TypeScript Solution:

```
/**
 * Problem: The Number of the Smallest Unoccupied Chair
 * Difficulty: Medium
 * Tags: array, hash, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

function smallestChair(times: number[][], targetFriend: number): number {

};
```

## C# Solution:

```
/*
 * Problem: The Number of the Smallest Unoccupied Chair
 * Difficulty: Medium
```

```

* Tags: array, hash, queue, heap
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

public class Solution {
public int SmallestChair(int[][] times, int targetFriend) {

}
}

```

### C Solution:

```

/*
* Problem: The Number of the Smallest Unoccupied Chair
* Difficulty: Medium
* Tags: array, hash, queue, heap
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

int smallestChair(int** times, int timesSize, int* timesColSize, int
targetFriend) {

}

```

### Go Solution:

```

// Problem: The Number of the Smallest Unoccupied Chair
// Difficulty: Medium
// Tags: array, hash, queue, heap
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

func smallestChair(times [][]int, targetFriend int) int {

```

```
}
```

### Kotlin Solution:

```
class Solution {  
    fun smallestChair(times: Array<IntArray>, targetFriend: Int): Int {  
  
    }  
}
```

### Swift Solution:

```
class Solution {  
    func smallestChair(_ times: [[Int]], _ targetFriend: Int) -> Int {  
  
    }  
}
```

### Rust Solution:

```
// Problem: The Number of the Smallest Unoccupied Chair  
// Difficulty: Medium  
// Tags: array, hash, queue, heap  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(n) for hash map  
  
impl Solution {  
    pub fn smallest_chair(times: Vec<Vec<i32>>, target_friend: i32) -> i32 {  
  
    }  
}
```

### Ruby Solution:

```
# @param {Integer[][]} times  
# @param {Integer} target_friend  
# @return {Integer}  
def smallest_chair(times, target_friend)
```

```
end
```

### PHP Solution:

```
class Solution {  
  
    /**  
     * @param Integer[][] $times  
     * @param Integer $targetFriend  
     * @return Integer  
     */  
    function smallestChair($times, $targetFriend) {  
  
    }  
}
```

### Dart Solution:

```
class Solution {  
    int smallestChair(List<List<int>> times, int targetFriend) {  
  
    }  
}
```

### Scala Solution:

```
object Solution {  
    def smallestChair(times: Array[Array[Int]], targetFriend: Int): Int = {  
  
    }  
}
```

### Elixir Solution:

```
defmodule Solution do  
    @spec smallest_chair(times :: [[integer]], target_friend :: integer) ::  
        integer  
    def smallest_chair(times, target_friend) do  
  
    end
```

```
end
```

### Erlang Solution:

```
-spec smallest_chair(Times :: [[integer()]], TargetFriend :: integer()) ->
integer().
smallest_chair(Times, TargetFriend) ->
.
```

### Racket Solution:

```
(define/contract (smallest-chair times targetFriend)
  (-> (listof (listof exact-integer?)) exact-integer? exact-integer?)
  )
```