

# Problem 2013: Detect Squares

## Problem Information

**Difficulty:** Medium

**Acceptance Rate:** 0.00%

**Paid Only:** No

## Problem Description

You are given a stream of points on the X-Y plane. Design an algorithm that:

Adds

new points from the stream into a data structure.

Duplicate

points are allowed and should be treated as different points.

Given a query point,

counts

the number of ways to choose three points from the data structure such that the three points and the query point form an

axis-aligned square

with

positive area

.

An

axis-aligned square

is a square whose edges are all the same length and are either parallel or perpendicular to the x-axis and y-axis.

Implement the

DetectSquares

class:

DetectSquares()

Initializes the object with an empty data structure.

void add(int[] point)

Adds a new point

point = [x, y]

to the data structure.

int count(int[] point)

Counts the number of ways to form


axis-aligned squares

with point

point = [x, y]

as described above.

Example 1:



Input

["DetectSquares", "add", "add", "add", "count", "count", "add", "count"] [[], [[3, 10]], [[11, 2]], [[3, 2]], [[11, 10]], [[14, 8]], [[11, 2]], [[11, 10]]]

Output

[null, null, null, null, 1, 0, null, 2]

Explanation

DetectSquares detectSquares = new DetectSquares(); detectSquares.add([3, 10]); detectSquares.add([11, 2]); detectSquares.add([3, 2]); detectSquares.count([11, 10]); // return 1. You can choose: // - The first, second, and third points detectSquares.count([14, 8]); // return 0. The query point cannot form a square with any points in the data structure. detectSquares.add([11, 2]); // Adding duplicate points is allowed. detectSquares.count([11, 10]); // return 2. You can choose: // - The first, second, and third points // - The first, third, and fourth points

Constraints:

point.length == 2

0 <= x, y <= 1000

At most

3000

calls

in total

will be made to

add

and

count

.

## Code Snippets

### C++:

```
class DetectSquares {
public:
    DetectSquares() {

    }

    void add(vector<int> point) {

    }

    int count(vector<int> point) {

    }
};

/**
 * Your DetectSquares object will be instantiated and called as such:
 * DetectSquares* obj = new DetectSquares();
 * obj->add(point);
 * int param_2 = obj->count(point);
 */
```

```
*/
```

## Java:

```
class DetectSquares {

    public DetectSquares() {

    }

    public void add(int[] point) {

    }

    public int count(int[] point) {

    }

}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * DetectSquares obj = new DetectSquares();
 * obj.add(point);
 * int param_2 = obj.count(point);
 */
```

## Python3:

```
class DetectSquares:

    def __init__(self):

    def add(self, point: List[int]) -> None:

    def count(self, point: List[int]) -> int:

    # Your DetectSquares object will be instantiated and called as such:
    # obj = DetectSquares()
```

```
# obj.add(point)
# param_2 = obj.count(point)
```

## Python:

```
class DetectSquares(object):

    def __init__(self):

    def add(self, point):
        """
        :type point: List[int]
        :rtype: None
        """

    def count(self, point):
        """
        :type point: List[int]
        :rtype: int
        """

# Your DetectSquares object will be instantiated and called as such:
# obj = DetectSquares()
# obj.add(point)
# param_2 = obj.count(point)
```

## JavaScript:

```
var DetectSquares = function() {

};

/**
 * @param {number[]} point
 * @return {void}
 */
DetectSquares.prototype.add = function(point) {
```

```

};

/**
 * @param {number[]} point
 * @return {number}
 */
DetectSquares.prototype.count = function(point) {

};

/**
 * Your DetectSquares object will be instantiated and called as such:
 * var obj = new DetectSquares()
 * obj.add(point)
 * var param_2 = obj.count(point)
 */

```

## TypeScript:

```

class DetectSquares {
  constructor() {

  }

  add(point: number[]): void {

  }

  count(point: number[]): number {

  }
}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * var obj = new DetectSquares()
 * obj.add(point)
 * var param_2 = obj.count(point)
 */

```

## C#:

```
public class DetectSquares {

    public DetectSquares() {

    }

    public void Add(int[] point) {

    }

    public int Count(int[] point) {

    }

}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * DetectSquares obj = new DetectSquares();
 * obj.Add(point);
 * int param_2 = obj.Count(point);
 */
```

## C:

```
typedef struct {

} DetectSquares;

DetectSquares* detectSquaresCreate() {

}

void detectSquaresAdd(DetectSquares* obj, int* point, int pointSize) {

}

int detectSquaresCount(DetectSquares* obj, int* point, int pointSize) {
```



```

}

void detectSquaresFree(DetectSquares* obj) {

}

/**
 * Your DetectSquares struct will be instantiated and called as such:
 * DetectSquares* obj = detectSquaresCreate();
 * detectSquaresAdd(obj, point, pointSize);

 * int param_2 = detectSquaresCount(obj, point, pointSize);

 * detectSquaresFree(obj);
 */

```

## Go:

```

type DetectSquares struct {

}

func Constructor() DetectSquares {

}

func (this *DetectSquares) Add(point []int) {

}

func (this *DetectSquares) Count(point []int) int {

}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * obj := Constructor();

```

```
* obj.Add(point);
* param_2 := obj.Count(point);
*/
```

## Kotlin:

```
class DetectSquares() {

    fun add(point: IntArray) {

    }

    fun count(point: IntArray): Int {

    }

}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * var obj = DetectSquares()
 * obj.add(point)
 * var param_2 = obj.count(point)
 */
```

## Swift:

```
class DetectSquares {

    init() {

    }

    func add(_ point: [Int]) {

    }

    func count(_ point: [Int]) -> Int {

    }

}
```

```

/**
 * Your DetectSquares object will be instantiated and called as such:
 * let obj = DetectSquares()
 * obj.add(point)
 * let ret_2: Int = obj.count(point)
 */

```

## Rust:

```

struct DetectSquares {

}

/**
 * `&self` means the method takes an immutable reference.
 * If you need a mutable reference, change it to `&mut self` instead.
 */
impl DetectSquares {

    fn new() -> Self {

    }

    fn add(&self, point: Vec<i32>) {

    }

    fn count(&self, point: Vec<i32>) -> i32 {

    }
}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * let obj = DetectSquares::new();
 * obj.add(point);
 * let ret_2: i32 = obj.count(point);
 */

```

## Ruby:

```
class DetectSquares
  def initialize()

  end

  =begin
  :type point: Integer[]
  :rtype: Void
  =end
  def add(point)

  end

  =begin
  :type point: Integer[]
  :rtype: Integer
  =end
  def count(point)

  end

end

# Your DetectSquares object will be instantiated and called as such:
# obj = DetectSquares.new()
# obj.add(point)
# param_2 = obj.count(point)
```

## PHP:

```
class DetectSquares {
    /**
     *
     */
    function __construct() {

    }

    /**
```

```

* @param Integer[] $point
* @return NULL
*/
function add($point) {

}

/**
* @param Integer[] $point
* @return Integer
*/
function count($point) {

}
}

/**
* Your DetectSquares object will be instantiated and called as such:
* $obj = DetectSquares();
* $obj->add($point);
* $ret_2 = $obj->count($point);
*/

```

## Dart:

```

class DetectSquares {

  DetectSquares() {

  }

  void add(List<int> point) {

  }

  int count(List<int> point) {

  }
}

/**
* Your DetectSquares object will be instantiated and called as such:

```

```
* DetectSquares obj = DetectSquares();
* obj.add(point);
* int param2 = obj.count(point);
*/
```

## Scala:

```
class DetectSquares() {

  def add(point: Array[Int]): Unit = {

  }

  def count(point: Array[Int]): Int = {

  }

}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * val obj = new DetectSquares()
 * obj.add(point)
 * val param_2 = obj.count(point)
 */
```

## Elixir:

```
defmodule DetectSquares do
  @spec init_() :: any
  def init_() do

  end

  @spec add(point :: [integer]) :: any
  def add(point) do

  end

  @spec count(point :: [integer]) :: integer
  def count(point) do
```

```

end
end

# Your functions will be called as such:
# DetectSquares.init_()
# DetectSquares.add(point)
# param_2 = DetectSquares.count(point)

# DetectSquares.init_ will be called before every test case, in which you can
do some necessary initializations.

```

## Erlang:

```

-spec detect_squares_init_() -> any().
detect_squares_init_() ->
.

-spec detect_squares_add(Point :: [integer()]) -> any().
detect_squares_add(Point) ->
.

-spec detect_squares_count(Point :: [integer()]) -> integer().
detect_squares_count(Point) ->
.

%% Your functions will be called as such:
%% detect_squares_init_(),
%% detect_squares_add(Point),
%% Param_2 = detect_squares_count(Point),

%% detect_squares_init_ will be called before every test case, in which you
can do some necessary initializations.

```

## Racket:

```

(define detect-squares%
  (class object%
    (super-new)

    (init-field)

```

```

; add : (listof exact-integer?) -> void?
(define/public (add point)
)
; count : (listof exact-integer?) -> exact-integer?
(define/public (count point)
)))

;; Your detect-squares% object will be instantiated and called as such:
;; (define obj (new detect-squares%))
;; (send obj add point)
;; (define param_2 (send obj count point))

```

## Solutions

### C++ Solution:

```

/*
 * Problem: Detect Squares
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class DetectSquares {
public:
    DetectSquares() {

    }

    void add(vector<int> point) {

    }

    int count(vector<int> point) {

    }
};

```



```

/**
 * Your DetectSquares object will be instantiated and called as such:
 * DetectSquares* obj = new DetectSquares();
 * obj->add(point);
 * int param_2 = obj->count(point);
 */

```

## Java Solution:

```

/**
 * Problem: Detect Squares
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class DetectSquares {

    public DetectSquares() {

    }

    public void add(int[] point) {

    }

    public int count(int[] point) {

    }

}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * DetectSquares obj = new DetectSquares();
 * obj.add(point);
 * int param_2 = obj.count(point);
 */

```

## Python3 Solution:

```
"""
Problem: Detect Squares
Difficulty: Medium
Tags: array, hash

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) for hash map
"""

class DetectSquares:

    def __init__(self):

    def add(self, point: List[int]) -> None:
        # TODO: Implement optimized solution
        pass
```

## Python Solution:

```
class DetectSquares(object):

    def __init__(self):

    def add(self, point):
        """
        :type point: List[int]
        :rtype: None
        """

    def count(self, point):
        """
        :type point: List[int]
        :rtype: int
        """
```

```
# Your DetectSquares object will be instantiated and called as such:
# obj = DetectSquares()
# obj.add(point)
# param_2 = obj.count(point)
```

## JavaScript Solution:

```
/**
 * Problem: Detect Squares
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

var DetectSquares = function() {

};

/**
 * @param {number[]} point
 * @return {void}
 */
DetectSquares.prototype.add = function(point) {

};

/**
 * @param {number[]} point
 * @return {number}
 */
DetectSquares.prototype.count = function(point) {

};

/**
 * Your DetectSquares object will be instantiated and called as such:
```

```
* var obj = new DetectSquares()
* obj.add(point)
* var param_2 = obj.count(point)
*/
```

### TypeScript Solution:

```
/**
 * Problem: Detect Squares
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class DetectSquares {
  constructor() {}

  add(point: number[]): void {}

  count(point: number[]): number {}
}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * var obj = new DetectSquares()
 * obj.add(point)
 * var param_2 = obj.count(point)
 */
```

### C# Solution:

```

/*
 * Problem: Detect Squares
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

public class DetectSquares {

    public DetectSquares() {

    }

    public void Add(int[] point) {

    }

    public int Count(int[] point) {

    }

}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * DetectSquares obj = new DetectSquares();
 * obj.Add(point);
 * int param_2 = obj.Count(point);
 */

```

## C Solution:

```

/*
 * Problem: Detect Squares
 * Difficulty: Medium
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map

```

```

*/

typedef struct {

} DetectSquares;

DetectSquares* detectSquaresCreate() {

}

void detectSquaresAdd(DetectSquares* obj, int* point, int pointSize) {

}

int detectSquaresCount(DetectSquares* obj, int* point, int pointSize) {

}

void detectSquaresFree(DetectSquares* obj) {

}

/**
 * Your DetectSquares struct will be instantiated and called as such:
 * DetectSquares* obj = detectSquaresCreate();
 * detectSquaresAdd(obj, point, pointSize);
 *
 * int param_2 = detectSquaresCount(obj, point, pointSize);
 *
 * detectSquaresFree(obj);
 */

```

### Go Solution:

```

// Problem: Detect Squares
// Difficulty: Medium
// Tags: array, hash

```

```

//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

type DetectSquares struct {

}

func Constructor() DetectSquares {

}

func (this *DetectSquares) Add(point []int) {

}

func (this *DetectSquares) Count(point []int) int {

}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * obj := Constructor();
 * obj.Add(point);
 * param_2 := obj.Count(point);
 */

```

### Kotlin Solution:

```

class DetectSquares() {

    fun add(point: IntArray) {

    }

    fun count(point: IntArray): Int {

```

```

}

}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * var obj = DetectSquares()
 * obj.add(point)
 * var param_2 = obj.count(point)
 */

```

### Swift Solution:

```

class DetectSquares {

    init() {

    }

    func add(_ point: [Int]) {

    }

    func count(_ point: [Int]) -> Int {

    }

}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * let obj = DetectSquares()
 * obj.add(point)
 * let ret_2: Int = obj.count(point)
 */

```

### Rust Solution:

```

// Problem: Detect Squares
// Difficulty: Medium

```



```

// Tags: array, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

struct DetectSquares {

}

/**
 * `&self` means the method takes an immutable reference.
 * If you need a mutable reference, change it to `&mut self` instead.
 */
impl DetectSquares {

    fn new() -> Self {

    }

    fn add(&self, point: Vec<i32>) {

    }

    fn count(&self, point: Vec<i32>) -> i32 {

    }
}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * let obj = DetectSquares::new();
 * obj.add(point);
 * let ret_2: i32 = obj.count(point);
 */

```

### Ruby Solution:

```

class DetectSquares
  def initialize()

```

```
end
```

```
=begin
```

```
:type point: Integer[]
```

```
:rtype: Void
```

```
=end
```

```
def add(point)
```

```
end
```

```
=begin
```

```
:type point: Integer[]
```

```
:rtype: Integer
```

```
=end
```

```
def count(point)
```

```
end
```

```
end
```

```
# Your DetectSquares object will be instantiated and called as such:
```

```
# obj = DetectSquares.new()
```

```
# obj.add(point)
```

```
# param_2 = obj.count(point)
```

## PHP Solution:

```
class DetectSquares {  
    /**  
     */  
    function __construct() {  
  
    }  
  
    /**  
     * @param Integer[] $point  
     * @return NULL  
    */  
}
```

```

*/
function add($point) {

}

/**
 * @param Integer[] $point
 * @return Integer
 */
function count($point) {

}
}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * $obj = DetectSquares();
 * $obj->add($point);
 * $ret_2 = $obj->count($point);
 */

```

### Dart Solution:

```

class DetectSquares {

  DetectSquares() {

  }

  void add(List<int> point) {

  }

  int count(List<int> point) {

  }
}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * DetectSquares obj = DetectSquares();

```

```
* obj.add(point);
* int param2 = obj.count(point);
*/
```

### Scala Solution:

```
class DetectSquares() {

  def add(point: Array[Int]): Unit = {

  }

  def count(point: Array[Int]): Int = {

  }

}

/**
 * Your DetectSquares object will be instantiated and called as such:
 * val obj = new DetectSquares()
 * obj.add(point)
 * val param_2 = obj.count(point)
 */
```

### Elixir Solution:

```
defmodule DetectSquares do
  @spec init_() :: any
  def init_() do

  end

  @spec add(point :: [integer]) :: any
  def add(point) do

  end

  @spec count(point :: [integer]) :: integer
  def count(point) do
```

```

end
end

# Your functions will be called as such:
# DetectSquares.init_()
# DetectSquares.add(point)
# param_2 = DetectSquares.count(point)

# DetectSquares.init_ will be called before every test case, in which you can
do some necessary initializations.

```

### Erlang Solution:

```

-spec detect_squares_init_() -> any().
detect_squares_init_() ->
.

-spec detect_squares_add(Point :: [integer()]) -> any().
detect_squares_add(Point) ->
.

-spec detect_squares_count(Point :: [integer()]) -> integer().
detect_squares_count(Point) ->
.

%% Your functions will be called as such:
%% detect_squares_init_(),
%% detect_squares_add(Point),
%% Param_2 = detect_squares_count(Point),

%% detect_squares_init_ will be called before every test case, in which you
can do some necessary initializations.

```

### Racket Solution:

```

(define detect-squares%
  (class object%
    (super-new)

    (init-field)

```

```
; add : (listof exact-integer?) -> void?  
(define/public (add point)  
  )  
; count : (listof exact-integer?) -> exact-integer?  
(define/public (count point)  
  ))
```

```
;; Your detect-squares% object will be instantiated and called as such:  
;; (define obj (new detect-squares%))  
;; (send obj add point)  
;; (define param_2 (send obj count point))
```