

Problem 3221: Maximum Array Hopping Score II

Problem Information

Difficulty: Medium

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given an array

nums

, you have to get the

maximum

score starting from index 0 and

hopping

until you reach the last element of the array.

In each

hop

, you can jump from index

i

to an index

$j > i$

, and you get a

score

of

$(j - i) * \text{nums}[j]$

.

Return the

maximum score

you can get.

Example 1:

Input:

$\text{nums} = [1, 5, 8]$

Output:

16

Explanation:

There are two possible ways to reach the last element:

$0 \rightarrow 1 \rightarrow 2$

with a score of

$(1 - 0) * 5 + (2 - 1) * 8 = 13$

.

$0 \rightarrow 2$

with a score of

$$(2 - 0) * 8 = 16$$

.

Example 2:

Input:

nums = [4,5,2,8,9,1,3]

Output:

42

Explanation:

We can do the hopping

0 -> 4 -> 6

with a score of

$$(4 - 0) * 9 + (6 - 4) * 3 = 42$$

.

Constraints:

$2 \leq \text{nums.length} \leq 10$

5

$1 \leq \text{nums}[i] \leq 10$

5

Code Snippets

C++:

```
class Solution {
public:
    long long maxScore(vector<int>& nums) {

    }
};
```

Java:

```
class Solution {
    public long maxScore(int[] nums) {

    }
}
```

Python3:

```
class Solution:
    def maxScore(self, nums: List[int]) -> int:
```

Python:

```
class Solution(object):
    def maxScore(self, nums):
        """
        :type nums: List[int]
        :rtype: int
        """
```

JavaScript:

```
/**
 * @param {number[]} nums
 * @return {number}
 */
var maxScore = function(nums) {

};
```

TypeScript:

```
function maxScore(nums: number[]): number {  
  
};
```

C#:

```
public class Solution {  
    public long MaxScore(int[] nums) {  
  
    }  
}
```

C:

```
long long maxScore(int* nums, int numsSize) {  
  
}
```

Go:

```
func maxScore(nums []int) int64 {  
  
}
```

Kotlin:

```
class Solution {  
    fun maxScore(nums: IntArray): Long {  
  
    }  
}
```

Swift:

```
class Solution {  
    func maxScore(_ nums: [Int]) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn max_score(nums: Vec<i32>) -> i64 {  
  
    }  
}
```

Ruby:

```
# @param {Integer[]} nums  
# @return {Integer}  
def max_score(nums)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param Integer[] $nums  
     * @return Integer  
     */  
    function maxScore($nums) {  
  
    }  
}
```

Dart:

```
class Solution {  
    int maxScore(List<int> nums) {  
  
    }  
}
```

Scala:

```
object Solution {  
    def maxScore(nums: Array[Int]): Long = {  
  
    }  
}
```

```
}
```

Elixir:

```
defmodule Solution do
  @spec max_score(nums :: [integer]) :: integer
  def max_score(nums) do

  end
end
```

Erlang:

```
-spec max_score(Nums :: [integer()]) -> integer().
max_score(Nums) ->
.
```

Racket:

```
(define/contract (max-score nums)
  (-> (listof exact-integer?) exact-integer?)
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Maximum Array Hopping Score II
 * Difficulty: Medium
 * Tags: array, greedy, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    long long maxScore(vector<int>& nums) {
```

```
}  
};
```

Java Solution:

```
/**  
 * Problem: Maximum Array Hopping Score II  
 * Difficulty: Medium  
 * Tags: array, greedy, stack  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(1) to O(n) depending on approach  
 */  
  
class Solution {  
    public long maxScore(int[] nums) {  
  
    }  
}
```

Python3 Solution:

```
"""  
Problem: Maximum Array Hopping Score II  
Difficulty: Medium  
Tags: array, greedy, stack  
  
Approach: Use two pointers or sliding window technique  
Time Complexity: O(n) or O(n log n)  
Space Complexity: O(1) to O(n) depending on approach  
"""  
  
class Solution:  
    def maxScore(self, nums: List[int]) -> int:  
        # TODO: Implement optimized solution  
        pass
```

Python Solution:


```

class Solution(object):
    def maxScore(self, nums):
        """
        :type nums: List[int]
        :rtype: int
        """

```

JavaScript Solution:

```

/**
 * Problem: Maximum Array Hopping Score II
 * Difficulty: Medium
 * Tags: array, greedy, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number[]} nums
 * @return {number}
 */
var maxScore = function(nums) {

};

```

TypeScript Solution:

```

/**
 * Problem: Maximum Array Hopping Score II
 * Difficulty: Medium
 * Tags: array, greedy, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function maxScore(nums: number[]): number {

};

```

C# Solution:

```
/*
 * Problem: Maximum Array Hopping Score II
 * Difficulty: Medium
 * Tags: array, greedy, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public long MaxScore(int[] nums) {

    }
}
```

C Solution:

```
/*
 * Problem: Maximum Array Hopping Score II
 * Difficulty: Medium
 * Tags: array, greedy, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

long long maxScore(int* nums, int numsSize) {

}
```

Go Solution:

```
// Problem: Maximum Array Hopping Score II
// Difficulty: Medium
// Tags: array, greedy, stack
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
```

```
// Space Complexity: O(1) to O(n) depending on approach

func maxScore(nums []int) int64 {

}
```

Kotlin Solution:

```
class Solution {
    fun maxScore(nums: IntArray): Long {

    }
}
```

Swift Solution:

```
class Solution {
    func maxScore(_ nums: [Int]) -> Int {

    }
}
```

Rust Solution:

```
// Problem: Maximum Array Hopping Score II
// Difficulty: Medium
// Tags: array, greedy, stack
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn max_score(nums: Vec<i32>) -> i64 {

    }
}
```

Ruby Solution:

```
# @param {Integer[]} nums
# @return {Integer}
def max_score(nums)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $nums
     * @return Integer
     */
    function maxScore($nums) {

    }

}
```

Dart Solution:

```
class Solution {
  int maxScore(List<int> nums) {

  }

}
```

Scala Solution:

```
object Solution {
  def maxScore(nums: Array[Int]): Long = {

  }

}
```

Elixir Solution:

```
defmodule Solution do
  @spec max_score(nums :: [integer]) :: integer
  def max_score(nums) do

  end
end
```

```
end
```

Erlang Solution:

```
-spec max_score(Nums :: [integer()]) -> integer().  
max_score(Nums) ->  
.
```

Racket Solution:

```
(define/contract (max-score nums)  
  (-> (listof exact-integer?) exact-integer?)  
  )
```