

# Problem 2177: Find Three Consecutive Integers That Sum to a Given Number

## Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

Given an integer

`num`

, return

three consecutive integers (as a sorted array)

that

sum

to

`num`

. If

`num`

cannot be expressed as the sum of three consecutive integers, return

an

empty

array.

Example 1:

Input:

num = 33

Output:

[10,11,12]

Explanation:

33 can be expressed as  $10 + 11 + 12 = 33$ . 10, 11, 12 are 3 consecutive integers, so we return [10, 11, 12].

Example 2:

Input:

num = 4

Output:

[]

Explanation:

There is no way to express 4 as the sum of 3 consecutive integers.

Constraints:

$0 \leq \text{num} \leq 10$

15

## Code Snippets

### C++:

```
class Solution {
public:
    vector<long long> sumOfThree(long long num) {

    }
};
```

### Java:

```
class Solution {
    public long[] sumOfThree(long num) {

    }
}
```

### Python3:

```
class Solution:
    def sumOfThree(self, num: int) -> List[int]:
```

### Python:

```
class Solution(object):
    def sumOfThree(self, num):
        """
        :type num: int
        :rtype: List[int]
        """
```

### JavaScript:

```
/**
 * @param {number} num
 * @return {number[]}
 */
var sumOfThree = function(num) {

};
```

### TypeScript:

```
function sumOfThree(num: number): number[] {  
  
};
```

### C#:

```
public class Solution {  
    public long[] SumOfThree(long num) {  
  
    }  
}
```

### C:

```
/**  
 * Note: The returned array must be malloced, assume caller calls free().  
 */  
long long* sumOfThree(long long num, int* returnSize) {  
  
}
```

### Go:

```
func sumOfThree(num int64) []int64 {  
  
}
```

### Kotlin:

```
class Solution {  
    fun sumOfThree(num: Long): LongArray {  
  
    }  
}
```

### Swift:

```
class Solution {  
    func sumOfThree(_ num: Int) -> [Int] {  
  
    }  
}
```

```
}
```

### Rust:

```
impl Solution {  
    pub fn sum_of_three(num: i64) -> Vec<i64> {  
  
    }  
}
```

### Ruby:

```
# @param {Integer} num  
# @return {Integer[]}  
def sum_of_three(num)  
  
end
```

### PHP:

```
class Solution {  
  
    /**  
     * @param Integer $num  
     * @return Integer[]  
     */  
    function sumOfThree($num) {  
  
    }  
}
```

### Dart:

```
class Solution {  
    List<int> sumOfThree(int num) {  
  
    }  
}
```

### Scala:

```

object Solution {
  def sumOfThree(num: Long): Array[Long] = {

  }
}

```

### Elixir:

```

defmodule Solution do
  @spec sum_of_three(num :: integer) :: [integer]
  def sum_of_three(num) do

  end
end

```

### Erlang:

```

-spec sum_of_three(Num :: integer()) -> [integer()].
sum_of_three(Num) ->
.

```

### Racket:

```

(define/contract (sum-of-three num)
  (-> exact-integer? (listof exact-integer?))
)

```

## Solutions

### C++ Solution:

```

/*
 * Problem: Find Three Consecutive Integers That Sum to a Given Number
 * Difficulty: Medium
 * Tags: array, math, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

```

```

class Solution {
public:
    vector<long long> sumOfThree(long long num) {

    }
};

```

### Java Solution:

```

/**
 * Problem: Find Three Consecutive Integers That Sum to a Given Number
 * Difficulty: Medium
 * Tags: array, math, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public long[] sumOfThree(long num) {

    }
}

```

### Python3 Solution:

```

"""
Problem: Find Three Consecutive Integers That Sum to a Given Number
Difficulty: Medium
Tags: array, math, sort

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def sumOfThree(self, num: int) -> List[int]:
        # TODO: Implement optimized solution
        pass

```

## Python Solution:

```
class Solution(object):
    def sumOfThree(self, num):
        """
        :type num: int
        :rtype: List[int]
        """
```

## JavaScript Solution:

```
/**
 * Problem: Find Three Consecutive Integers That Sum to a Given Number
 * Difficulty: Medium
 * Tags: array, math, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number} num
 * @return {number[]}
 */
var sumOfThree = function(num) {

};
```

## TypeScript Solution:

```
/**
 * Problem: Find Three Consecutive Integers That Sum to a Given Number
 * Difficulty: Medium
 * Tags: array, math, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function sumOfThree(num: number): number[] {
```



```
};
```

### C# Solution:

```
/*
 * Problem: Find Three Consecutive Integers That Sum to a Given Number
 * Difficulty: Medium
 * Tags: array, math, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public long[] SumOfThree(long num) {

    }
}
```

### C Solution:

```
/*
 * Problem: Find Three Consecutive Integers That Sum to a Given Number
 * Difficulty: Medium
 * Tags: array, math, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
long long* sumOfThree(long long num, int* returnSize) {

}
```

### Go Solution:

```
// Problem: Find Three Consecutive Integers That Sum to a Given Number
// Difficulty: Medium
// Tags: array, math, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func sumOfThree(num int64) []int64 {

}
```

### Kotlin Solution:

```
class Solution {
    fun sumOfThree(num: Long): LongArray {

    }
}
```

### Swift Solution:

```
class Solution {
    func sumOfThree(_ num: Int) -> [Int] {

    }
}
```

### Rust Solution:

```
// Problem: Find Three Consecutive Integers That Sum to a Given Number
// Difficulty: Medium
// Tags: array, math, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn sum_of_three(num: i64) -> Vec<i64> {

    }
}
```

```
}
```

### Ruby Solution:

```
# @param {Integer} num
# @return {Integer[]}
def sum_of_three(num)

end
```

### PHP Solution:

```
class Solution {

    /**
     * @param Integer $num
     * @return Integer[]
     */
    function sumOfThree($num) {

    }

}
```

### Dart Solution:

```
class Solution {
  List<int> sumOfThree(int num) {

  }

}
```

### Scala Solution:

```
object Solution {
  def sumOfThree(num: Long): Array[Long] = {

  }

}
```

### Elixir Solution:

```
defmodule Solution do
  @spec sum_of_three(num :: integer) :: [integer]
  def sum_of_three(num) do

  end
end
```

### Erlang Solution:

```
-spec sum_of_three(Num :: integer()) -> [integer()].
sum_of_three(Num) ->
.
```

### Racket Solution:

```
(define/contract (sum-of-three num)
  (-> exact-integer? (listof exact-integer?))
)
```