

Problem 3636: Threshold Majority Queries

Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given an integer array

`nums`

of length

`n`

and an array

`queries`

, where

`queries[i] = [l`

`i`

, `r`

`i`

, threshold

`i`

]

.

Return an array of integers

ans

where

ans[i]

is equal to the element in the subarray

nums[l

i

...r

i

]

that appears

at least

threshold

i

times, selecting the element with the

highest

frequency (choosing the

smallest

in case of a tie), or -1 if no such element

exists

.

Example 1:

Input:

nums = [1,1,2,2,1,1], queries = [[0,5,4],[0,3,3],[2,3,2]]

Output:

[1,-1,2]

Explanation:

Query

Sub-array

Threshold

Frequency table

Answer

[0, 5, 4]

[1, 1, 2, 2, 1, 1]

4

$1 \rightarrow 4, 2 \rightarrow 2$

1

[0, 3, 3]

[1, 1, 2, 2]

3

$1 \rightarrow 2, 2 \rightarrow 2$

-1

[2, 3, 2]

[2, 2]

2

$2 \rightarrow 2$

2

Example 2:

Input:

nums = [3,2,3,2,3,2,3], queries = [[0,6,4],[1,5,2],[2,4,1],[3,3,1]]

Output:

[3,2,3,2]

Explanation:

Query

Sub-array

Threshold

Frequency table

Answer

[0, 6, 4]

[3, 2, 3, 2, 3, 2, 3]

4

$3 \rightarrow 4, 2 \rightarrow 3$

3

[1, 5, 2]

[2, 3, 2, 3, 2]

2

$2 \rightarrow 3, 3 \rightarrow 2$

2

[2, 4, 1]

[3, 2, 3]

1

$3 \rightarrow 2, 2 \rightarrow 1$

3

[3, 3, 1]

[2]

1

$2 \rightarrow 1$

2

Constraints:

$1 \leq \text{nums.length} == n \leq 10$

4

$1 \leq \text{nums}[i] \leq 10$

9

$1 \leq \text{queries.length} \leq 5 * 10$

4

`queries[i] = [l`

`i`

`, r`

`i`

`, threshold`

`i`

`]`

$0 \leq l$

`i`

$\leq r$

`i`

< n

1 <= threshold

i

<= r

i

- i

i

+ 1

Code Snippets

C++:

```
class Solution {
public:
    vector<int> subarrayMajority(vector<int>& nums, vector<vector<int>>& queries)
    {

    }

};
```

Java:

```
class Solution {
    public int[] subarrayMajority(int[] nums, int[][] queries) {

    }

}
```

Python3:

```

class Solution:
    def subarrayMajority(self, nums: List[int], queries: List[List[int]]) ->
    List[int]:

```

Python:

```

class Solution(object):
    def subarrayMajority(self, nums, queries):
        """
        :type nums: List[int]
        :type queries: List[List[int]]
        :rtype: List[int]
        """

```

JavaScript:

```

/**
 * @param {number[]} nums
 * @param {number[][]} queries
 * @return {number[]}
 */
var subarrayMajority = function(nums, queries) {

};

```

TypeScript:

```

function subarrayMajority(nums: number[], queries: number[][]): number[] {

};

```

C#:

```

public class Solution {
    public int[] SubarrayMajority(int[] nums, int[][] queries) {

    }
}

```

C:

```

/**
 * Note: The returned array must be malloced, assume caller calls free().

```



```

*/
int* subarrayMajority(int* nums, int numsSize, int** queries, int
queriesSize, int* queriesColSize, int* returnSize) {

}

```

Go:

```

func subarrayMajority(nums []int, queries [][]int) []int {

}

```

Kotlin:

```

class Solution {
    fun subarrayMajority(nums: IntArray, queries: Array<IntArray>): IntArray {

    }
}

```

Swift:

```

class Solution {
    func subarrayMajority(_ nums: [Int], _ queries: [[Int]]) -> [Int] {

    }
}

```

Rust:

```

impl Solution {
    pub fn subarray_majority(nums: Vec<i32>, queries: Vec<Vec<i32>> >) -> Vec<i32>
    {

    }
}

```

Ruby:

```

# @param {Integer[]} nums
# @param {Integer[][]} queries
# @return {Integer[]}

```

```
def subarray_majority(nums, queries)

end
```

PHP:

```
class Solution {

    /**
     * @param Integer[] $nums
     * @param Integer[][] $queries
     * @return Integer[]
     */
    function subarrayMajority($nums, $queries) {

    }

}
```

Dart:

```
class Solution {
  List<int> subarrayMajority(List<int> nums, List<List<int>> queries) {

  }
}
```

Scala:

```
object Solution {
  def subarrayMajority(nums: Array[Int], queries: Array[Array[Int]]):
    Array[Int] = {

  }
}
```

Elixir:

```
defmodule Solution do
  @spec subarray_majority(nums :: [integer], queries :: [[integer]]) ::
    [integer]
  def subarray_majority(nums, queries) do
```

```
end  
end
```

Erlang:

```
-spec subarray_majority(Nums :: [integer()], Queries :: [[integer()]]) ->  
[integer()].  
subarray_majority(Nums, Queries) ->  
.
```

Racket:

```
(define/contract (subarray-majority nums queries)  
  (-> (listof exact-integer?) (listof (listof exact-integer?)) (listof  
    exact-integer?))  
  )
```

Solutions

C++ Solution:

```
/*  
 * Problem: Threshold Majority Queries  
 * Difficulty: Hard  
 * Tags: array, hash, search  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(n) for hash map  
 */  
  
class Solution {  
public:  
    vector<int> subarrayMajority(vector<int>& nums, vector<vector<int>>& queries)  
    {  
  
    }  
};
```

Java Solution:

```

/**
 * Problem: Threshold Majority Queries
 * Difficulty: Hard
 * Tags: array, hash, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
public int[] subarrayMajority(int[] nums, int[][] queries) {

}

}

```

Python3 Solution:

```

"""
Problem: Threshold Majority Queries
Difficulty: Hard
Tags: array, hash, search

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) for hash map
"""

class Solution:
def subarrayMajority(self, nums: List[int], queries: List[List[int]]) ->
List[int]:
# TODO: Implement optimized solution
pass

```

Python Solution:

```

class Solution(object):
def subarrayMajority(self, nums, queries):
"""
:type nums: List[int]
:type queries: List[List[int]]
:rtype: List[int]

```

```
"""
```

JavaScript Solution:

```
/**
 * Problem: Threshold Majority Queries
 * Difficulty: Hard
 * Tags: array, hash, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

/**
 * @param {number[]} nums
 * @param {number[][]} queries
 * @return {number[]}
 */
var subarrayMajority = function(nums, queries) {

};
```

TypeScript Solution:

```
/**
 * Problem: Threshold Majority Queries
 * Difficulty: Hard
 * Tags: array, hash, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

function subarrayMajority(nums: number[], queries: number[][]): number[] {

};
```

C# Solution:

```

/*
 * Problem: Threshold Majority Queries
 * Difficulty: Hard
 * Tags: array, hash, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

public class Solution {
    public int[] SubarrayMajority(int[] nums, int[][] queries) {

    }
}

```

C Solution:

```

/*
 * Problem: Threshold Majority Queries
 * Difficulty: Hard
 * Tags: array, hash, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* subarrayMajority(int* nums, int numsSize, int** queries, int
queriesSize, int* queriesColSize, int* returnSize) {

}

```

Go Solution:

```

// Problem: Threshold Majority Queries
// Difficulty: Hard
// Tags: array, hash, search
//

```

```

// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

func subarrayMajority(nums []int, queries [][]int) []int {

}

```

Kotlin Solution:

```

class Solution {
    fun subarrayMajority(nums: IntArray, queries: Array<IntArray>): IntArray {

    }
}

```

Swift Solution:

```

class Solution {
    func subarrayMajority(_ nums: [Int], _ queries: [[Int]]) -> [Int] {

    }
}

```

Rust Solution:

```

// Problem: Threshold Majority Queries
// Difficulty: Hard
// Tags: array, hash, search
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

impl Solution {
    pub fn subarray_majority(nums: Vec<i32>, queries: Vec<Vec<i32>>) -> Vec<i32>
    {

    }
}

```

Ruby Solution:

```
# @param {Integer[]} nums
# @param {Integer[][]} queries
# @return {Integer[]}
def subarray_majority(nums, queries)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $nums
     * @param Integer[][] $queries
     * @return Integer[]
     */
    function subarrayMajority($nums, $queries) {

    }

}
```

Dart Solution:

```
class Solution {
  List<int> subarrayMajority(List<int> nums, List<List<int>> queries) {

  }
}
```

Scala Solution:

```
object Solution {
  def subarrayMajority(nums: Array[Int], queries: Array[Array[Int]]):
    Array[Int] = {

    }
}
```

Elixir Solution:


```

defmodule Solution do
  @spec subarray_majority(nums :: [integer], queries :: [[integer]]) ::
    [integer]
  def subarray_majority(nums, queries) do

  end
end

```

Erlang Solution:

```

-spec subarray_majority(Nums :: [integer()], Queries :: [[integer()]]) ->
  [integer()].
subarray_majority(Nums, Queries) ->
.

```

Racket Solution:

```

(define/contract (subarray-majority nums queries)
  (-> (listof exact-integer?) (listof (listof exact-integer?)) (listof
exact-integer?))
)

```