Problem 2492: Minimum Score of a Path Between Two Cities

Problem Information

Difficulty: Medium
Acceptance Rate: 58.23%
Paid Only: No
Tags: Depth-First Search, Breadth-First Search, Union Find, Graph

Problem Description

You are given a positive integer `n` representing `n` cities numbered from `1` to `n`. You are also given a **2D** array `roads` where `roads[i] = [ai, bi, distancei]` indicates that there is a **bidirectional** road between cities `ai` and `bi` with a distance equal to `distancei`. The cities graph is not necessarily connected.

The **score** of a path between two cities is defined as the **minimum** distance of a road in this path.

Return _the**minimum** possible score of a path between cities _`1` _and_`n`.

Note :

* A path is a sequence of roads between two cities. * It is allowed for a path to contain the same road **multiple** times, and you can visit cities `1` and `n` multiple times along the path. * The test cases are generated such that there is **at least** one path between `1` and `n`.

Example 1:

Input: n = 4, roads = [[1,2,9],[2,3,6],[2,4,5],[1,4,7]] **Output:** 5 **Explanation:** The path from city 1 to 4 with the minimum score is: 1 -> 2 -> 4. The score of this path is min(9,5) = 5. It can be shown that no other path has less score.

Example 2:



Input: n = 4, roads = [[1,2,2],[1,3,4],[3,4,7]] **Output:** 2 **Explanation:** The path from city 1 to 4 with the minimum score is: 1 -> 2 -> 1 -> 3 -> 4. The score of this path is min(2,2,4,7) = 2.

Constraints:

* `2 <= n <= 105` * `1 <= roads.length <= 105` * `roads[i].length == 3` * `1 <= ai, bi <= n` * `ai != bi` * `1 <= distancei <= 104` * There are no repeated edges. * There is at least one path between `1` and `n`.

Code Snippets

C++:

```
class Solution {
public:
int minScore(int n, vector<vector<int>>& roads) {

}
};
```

Java:

```
class Solution {
public int minScore(int n, int[][] roads) {

}
}
```

Python3:

```
class Solution:
def minScore(self, n: int, roads: List[List[int]]) -> int:
```