

# Problem 2953: Count Complete Substrings

## Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given a string

word

and an integer

k

.

A substring

s

of

word

is

complete

if:

Each character in

s

occurs

exactly

k

times.

The difference between two adjacent characters is

at most

2

. That is, for any two adjacent characters

c1

and

c2

in

s

, the absolute difference in their positions in the alphabet is

at most

2

.

Return

the number of

complete

substrings of

word

.

A

substring

is a

non-empty

contiguous sequence of characters in a string.

Example 1:

Input:

word = "igigee", k = 2

Output:

3

Explanation:

The complete substrings where each character appears exactly twice and the difference between adjacent characters is at most 2 are:

igig

ee, igig

ee

,

igigee

.

Example 2:

Input:

word = "aaabbbccc", k = 3

Output:

6

Explanation:

The complete substrings where each character appears exactly three times and the difference between adjacent characters is at most 2 are:

aaa

bbbccc, aaa

bbb

ccc, aaabbb

ccc

,

aaabbb

ccc, aaa

bbbccc

,

aaabbbccc

.

Constraints:

$1 \leq \text{word.length} \leq 10$

5

word

consists only of lowercase English letters.

$1 \leq k \leq \text{word.length}$

## Code Snippets

**C++:**

```
class Solution {
public:
    int countCompleteSubstrings(string word, int k) {

    }
};
```

**Java:**

```
class Solution {
    public int countCompleteSubstrings(String word, int k) {

    }
}
```

**Python3:**

```

class Solution:
    def countCompleteSubstrings(self, word: str, k: int) -> int:

```

## Python:

```

class Solution(object):
    def countCompleteSubstrings(self, word, k):
        """
        :type word: str
        :type k: int
        :rtype: int
        """

```

## JavaScript:

```

/**
 * @param {string} word
 * @param {number} k
 * @return {number}
 */
var countCompleteSubstrings = function(word, k) {

};

```

## TypeScript:

```

function countCompleteSubstrings(word: string, k: number): number {

};

```

## C#:

```

public class Solution {
    public int CountCompleteSubstrings(string word, int k) {

    }
}

```

## C:

```

int countCompleteSubstrings(char* word, int k) {

}

```

**Go:**

```
func countCompleteSubstrings(word string, k int) int {  
  
}
```

**Kotlin:**

```
class Solution {  
    fun countCompleteSubstrings(word: String, k: Int): Int {  
  
    }  
}
```

**Swift:**

```
class Solution {  
    func countCompleteSubstrings(_ word: String, _ k: Int) -> Int {  
  
    }  
}
```

**Rust:**

```
impl Solution {  
    pub fn count_complete_substrings(word: String, k: i32) -> i32 {  
  
    }  
}
```

**Ruby:**

```
# @param {String} word  
# @param {Integer} k  
# @return {Integer}  
def count_complete_substrings(word, k)  
  
end
```

**PHP:**

```
class Solution {
```

```

/**
 * @param String $word
 * @param Integer $k
 * @return Integer
 */
function countCompleteSubstrings($word, $k) {

}
}

```

### Dart:

```

class Solution {
  int countCompleteSubstrings(String word, int k) {

  }
}

```

### Scala:

```

object Solution {
  def countCompleteSubstrings(word: String, k: Int): Int = {

  }
}

```

### Elixir:

```

defmodule Solution do
  @spec count_complete_substrings(word :: String.t, k :: integer) :: integer
  def count_complete_substrings(word, k) do

  end
end

```

### Erlang:

```

-spec count_complete_substrings(Word :: unicode:unicode_binary(), K ::
integer()) -> integer().
count_complete_substrings(Word, K) ->
.

```



## Racket:

```
(define/contract (count-complete-substrings word k)
  (-> string? exact-integer? exact-integer?)
)
```

## Solutions

### C++ Solution:

```
/*
 * Problem: Count Complete Substrings
 * Difficulty: Hard
 * Tags: array, string, tree, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

class Solution {
public:
    int countCompleteSubstrings(string word, int k) {

    }
};
```

### Java Solution:

```
/**
 * Problem: Count Complete Substrings
 * Difficulty: Hard
 * Tags: array, string, tree, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

class Solution {
    public int countCompleteSubstrings(String word, int k) {
```

```
}  
}
```

### Python3 Solution:

```
"""  
Problem: Count Complete Substrings  
Difficulty: Hard  
Tags: array, string, tree, hash  
  
Approach: Use two pointers or sliding window technique  
Time Complexity: O(n) or O(n log n)  
Space Complexity: O(h) for recursion stack where h is height  
"""  
  
class Solution:  
    def countCompleteSubstrings(self, word: str, k: int) -> int:  
        # TODO: Implement optimized solution  
        pass
```

### Python Solution:

```
class Solution(object):  
    def countCompleteSubstrings(self, word, k):  
        """  
        :type word: str  
        :type k: int  
        :rtype: int  
        """
```

### JavaScript Solution:

```
/**  
 * Problem: Count Complete Substrings  
 * Difficulty: Hard  
 * Tags: array, string, tree, hash  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(h) for recursion stack where h is height  
 */
```

```

*/

/**
 * @param {string} word
 * @param {number} k
 * @return {number}
 */
var countCompleteSubstrings = function(word, k) {

};

```

### TypeScript Solution:

```

/**
 * Problem: Count Complete Substrings
 * Difficulty: Hard
 * Tags: array, string, tree, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

function countCompleteSubstrings(word: string, k: number): number {

};

```

### C# Solution:

```

/*
 * Problem: Count Complete Substrings
 * Difficulty: Hard
 * Tags: array, string, tree, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

public class Solution {
    public int CountCompleteSubstrings(string word, int k) {

```

```
}  
}
```

### C Solution:

```
/*  
 * Problem: Count Complete Substrings  
 * Difficulty: Hard  
 * Tags: array, string, tree, hash  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(h) for recursion stack where h is height  
 */  
  
int countCompleteSubstrings(char* word, int k) {  
  
}
```

### Go Solution:

```
// Problem: Count Complete Substrings  
// Difficulty: Hard  
// Tags: array, string, tree, hash  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(h) for recursion stack where h is height  
  
func countCompleteSubstrings(word string, k int) int {  
  
}
```

### Kotlin Solution:

```
class Solution {  
    fun countCompleteSubstrings(word: String, k: Int): Int {  
  
    }  
}
```

### Swift Solution:

```
class Solution {  
    func countCompleteSubstrings(_ word: String, _ k: Int) -> Int {  
  
    }  
}
```

### Rust Solution:

```
// Problem: Count Complete Substrings  
// Difficulty: Hard  
// Tags: array, string, tree, hash  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(h) for recursion stack where h is height  
  
impl Solution {  
    pub fn count_complete_substrings(word: String, k: i32) -> i32 {  
  
    }  
}
```

### Ruby Solution:

```
# @param {String} word  
# @param {Integer} k  
# @return {Integer}  
def count_complete_substrings(word, k)  
  
end
```

### PHP Solution:

```
class Solution {  
  
    /**  
     * @param String $word  
     * @param Integer $k  
     * @return Integer  
     */  
}
```

```
function countCompleteSubstrings($word, $k) {

}

}
```

### Dart Solution:

```
class Solution {
  int countCompleteSubstrings(String word, int k) {

  }
}
```

### Scala Solution:

```
object Solution {
  def countCompleteSubstrings(word: String, k: Int): Int = {

  }
}
```

### Elixir Solution:

```
defmodule Solution do
  @spec count_complete_substrings(word :: String.t, k :: integer) :: integer
  def count_complete_substrings(word, k) do

  end
end
```

### Erlang Solution:

```
-spec count_complete_substrings(Word :: unicode:unicode_binary(), K ::
integer()) -> integer().
count_complete_substrings(Word, K) ->
.
```

### Racket Solution:

```
(define/contract (count-complete-substrings word k)
  (-> string? exact-integer? exact-integer?))
```

