

Problem 2732: Find a Good Subset of the Matrix

Problem Information

Difficulty: Hard

Acceptance Rate: 46.54%

Paid Only: No

Tags: Array, Hash Table, Bit Manipulation, Matrix

Problem Description

You are given a **0-indexed** $m \times n$ binary matrix `grid`.

Let us call a **non-empty** subset of rows **good** if the sum of each column of the subset is at most half of the length of the subset.

More formally, if the length of the chosen subset of rows is k , then the sum of each column should be at most $\lfloor k / 2 \rfloor$.

Return `an integer array` that contains row indices of a good subset sorted in **ascending** order.

If there are multiple good subsets, you can return any of them. If there are no good subsets, return an empty array.

A **subset** of rows of the matrix `grid` is any matrix that can be obtained by deleting some (possibly none or all) rows from `grid`.

Example 1:

Input: `grid = [[0,1,1,0],[0,0,0,1],[1,1,1,1]]` **Output:** `[0,1]` **Explanation:** We can choose the 0th and 1st rows to create a good subset of rows. The length of the chosen subset is 2. - The sum of the 0th column is $0 + 0 = 0$, which is at most half of the length of the subset. - The sum of the 1st column is $1 + 0 = 1$, which is at most half of the length of the subset. - The sum of the 2nd column is $1 + 0 = 1$, which is at most half of the length of the subset. - The sum of the 3rd column is $0 + 1 = 1$, which is at most half of the length of the subset.

****Example 2:****

****Input:**** grid = [[0]] ****Output:**** [0] ****Explanation:**** We can choose the 0th row to create a good subset of rows. The length of the chosen subset is 1. - The sum of the 0th column is 0, which is at most half of the length of the subset.

****Example 3:****

****Input:**** grid = [[1,1,1],[1,1,1]] ****Output:**** [] ****Explanation:**** It is impossible to choose any subset of rows to create a good subset.

****Constraints:****

* `m == grid.length` * `n == grid[i].length` * `1 <= m <= 104` * `1 <= n <= 5` * `grid[i][j]` is either `0` or `1`.

Code Snippets

C++:

```
class Solution {
public:
    vector<int> goodSubsetofBinaryMatrix(vector<vector<int>>& grid) {

    }
};
```

Java:

```
class Solution {
    public List<Integer> goodSubsetofBinaryMatrix(int[][] grid) {

    }
}
```

Python3:

```
class Solution:
    def goodSubsetofBinaryMatrix(self, grid: List[List[int]]) -> List[int]:
```