

Problem 1074: Number of Submatrices That Sum to Target

Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given a

matrix

and a

target

, return the number of non-empty submatrices that sum to

target

.

A submatrix

$x1, y1, x2, y2$

is the set of all cells

$matrix[x][y]$

with

$x1 \leq x \leq x2$

and

$$y_1 \leq y \leq y_2$$

.

Two submatrices

$$(x_1, y_1, x_2, y_2)$$

and

$$(x'_1, y'_1, x'_2, y'_2)$$

are different if they have some coordinate that is different: for example, if

$$x_1 \neq x'_1$$

.

Example 1:

0	1	0
1	1	1
0	1	0

Input:

matrix = [[0,1,0],[1,1,1],[0,1,0]], target = 0

Output:

4

Explanation:

The four 1x1 submatrices that only contain 0.

Example 2:

Input:

matrix = [[1,-1],[-1,1]], target = 0

Output:

5

Explanation:

The two 1x2 submatrices, plus the two 2x1 submatrices, plus the 2x2 submatrix.

Example 3:

Input:

matrix = [[904]], target = 0

Output:

0

Constraints:

1 <= matrix.length <= 100

1 <= matrix[0].length <= 100

$-1000 \leq \text{matrix}[i][j] \leq 1000$

$-10^8 \leq \text{target} \leq 10^8$

Code Snippets

C++:

```
class Solution {
public:
    int numSubmatrixSumTarget(vector<vector<int>>& matrix, int target) {

    }
};
```

Java:

```
class Solution {
    public int numSubmatrixSumTarget(int[][] matrix, int target) {

    }
}
```

Python3:

```
class Solution:
    def numSubmatrixSumTarget(self, matrix: List[List[int]], target: int) -> int:
```

Python:

```
class Solution(object):
    def numSubmatrixSumTarget(self, matrix, target):
        """
        :type matrix: List[List[int]]
        :type target: int
        :rtype: int
        """
```

JavaScript:

```

/**
 * @param {number[][]} matrix
 * @param {number} target
 * @return {number}
 */
var numSubmatrixSumTarget = function(matrix, target) {

};

```

TypeScript:

```

function numSubmatrixSumTarget(matrix: number[][], target: number): number {

};

```

C#:

```

public class Solution {
    public int NumSubmatrixSumTarget(int[][] matrix, int target) {

    }
}

```

C:

```

int numSubmatrixSumTarget(int** matrix, int matrixSize, int* matrixColSize,
int target) {

}

```

Go:

```

func numSubmatrixSumTarget(matrix [][]int, target int) int {

}

```

Kotlin:

```

class Solution {
    fun numSubmatrixSumTarget(matrix: Array<IntArray>, target: Int): Int {

    }
}

```

Swift:

```
class Solution {  
    func numSubmatrixSumTarget(_ matrix: [[Int]], _ target: Int) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn num_submatrix_sum_target(matrix: Vec<Vec<i32>>, target: i32) -> i32 {  
  
    }  
}
```

Ruby:

```
# @param {Integer[][]} matrix  
# @param {Integer} target  
# @return {Integer}  
def num_submatrix_sum_target(matrix, target)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param Integer[][] $matrix  
     * @param Integer $target  
     * @return Integer  
     */  
    function numSubmatrixSumTarget($matrix, $target) {  
  
    }  
}
```

Dart:

```
class Solution {  
    int numSubmatrixSumTarget(List<List<int>> matrix, int target) {
```

```
}  
}
```

Scala:

```
object Solution {  
  def numSubmatrixSumTarget(matrix: Array[Array[Int]], target: Int): Int = {  
  
  }  
}
```

Elixir:

```
defmodule Solution do  
  @spec num_submatrix_sum_target(matrix :: [[integer]], target :: integer) ::  
    integer  
  def num_submatrix_sum_target(matrix, target) do  
  
  end  
end
```

Erlang:

```
-spec num_submatrix_sum_target(Matrix :: [[integer()]], Target :: integer())  
-> integer().  
num_submatrix_sum_target(Matrix, Target) ->  
.
```

Racket:

```
(define/contract (num-submatrix-sum-target matrix target)  
  (-> (listof (listof exact-integer?)) exact-integer? exact-integer?)  
  )
```

Solutions

C++ Solution:

```

/*
 * Problem: Number of Submatrices That Sum to Target
 * Difficulty: Hard
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
public:
    int numSubmatrixSumTarget(vector<vector<int>>& matrix, int target) {

    }
};

```

Java Solution:

```

/**
 * Problem: Number of Submatrices That Sum to Target
 * Difficulty: Hard
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
    public int numSubmatrixSumTarget(int[][] matrix, int target) {

    }
}

```

Python3 Solution:

```

"""
Problem: Number of Submatrices That Sum to Target
Difficulty: Hard
Tags: array, hash

```

```

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) for hash map
"""

class Solution:
    def numSubmatrixSumTarget(self, matrix: List[List[int]], target: int) -> int:
        # TODO: Implement optimized solution
        pass

```

Python Solution:

```

class Solution(object):
    def numSubmatrixSumTarget(self, matrix, target):
        """
        :type matrix: List[List[int]]
        :type target: int
        :rtype: int
        """

```

JavaScript Solution:

```

/**
 * Problem: Number of Submatrices That Sum to Target
 * Difficulty: Hard
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

/**
 * @param {number[][]} matrix
 * @param {number} target
 * @return {number}
 */
var numSubmatrixSumTarget = function(matrix, target) {

};

```

TypeScript Solution:

```
/**
 * Problem: Number of Submatrices That Sum to Target
 * Difficulty: Hard
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

function numSubmatrixSumTarget(matrix: number[][], target: number): number {

};
```

C# Solution:

```
/*
 * Problem: Number of Submatrices That Sum to Target
 * Difficulty: Hard
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

public class Solution {
    public int NumSubmatrixSumTarget(int[][] matrix, int target) {

    }
}
```

C Solution:

```
/*
 * Problem: Number of Submatrices That Sum to Target
 * Difficulty: Hard
 * Tags: array, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
```

```

* Space Complexity: O(n) for hash map
*/

int numSubmatrixSumTarget(int** matrix, int matrixSize, int* matrixColSize,
int target) {

}

```

Go Solution:

```

// Problem: Number of Submatrices That Sum to Target
// Difficulty: Hard
// Tags: array, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

func numSubmatrixSumTarget(matrix [][]int, target int) int {

}

```

Kotlin Solution:

```

class Solution {
    fun numSubmatrixSumTarget(matrix: Array<IntArray>, target: Int): Int {

    }
}

```

Swift Solution:

```

class Solution {
    func numSubmatrixSumTarget(_ matrix: [[Int]], _ target: Int) -> Int {

    }
}

```

Rust Solution:

```

// Problem: Number of Submatrices That Sum to Target
// Difficulty: Hard
// Tags: array, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

impl Solution {
    pub fn num_submatrix_sum_target(matrix: Vec<Vec<i32>>, target: i32) -> i32 {

    }
}

```

Ruby Solution:

```

# @param {Integer[][]} matrix
# @param {Integer} target
# @return {Integer}
def num_submatrix_sum_target(matrix, target)

end

```

PHP Solution:

```

class Solution {

    /**
     * @param Integer[][] $matrix
     * @param Integer $target
     * @return Integer
     */
    function numSubmatrixSumTarget($matrix, $target) {

    }

}

```

Dart Solution:

```

class Solution {
    int numSubmatrixSumTarget(List<List<int>> matrix, int target) {

```

```
}  
}
```

Scala Solution:

```
object Solution {  
  def numSubmatrixSumTarget(matrix: Array[Array[Int]], target: Int): Int = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec num_submatrix_sum_target(matrix :: [[integer]], target :: integer) ::  
    integer  
  def num_submatrix_sum_target(matrix, target) do  
  
  end  
end
```

Erlang Solution:

```
-spec num_submatrix_sum_target(Matrix :: [[integer()]], Target :: integer())  
-> integer().  
num_submatrix_sum_target(Matrix, Target) ->  
.
```

Racket Solution:

```
(define/contract (num-submatrix-sum-target matrix target)  
  (-> (listof (listof exact-integer?)) exact-integer? exact-integer?)  
  )
```