

Problem 629: K Inverse Pairs Array

Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

For an integer array

`nums`

, an

inverse pair

is a pair of integers

$[i, j]$

where

$0 \leq i < j < \text{nums.length}$

and

$\text{nums}[i] > \text{nums}[j]$

.

Given two integers n and k , return the number of different arrays consisting of numbers from

to

n

such that there are exactly

k

inverse pairs

. Since the answer can be huge, return it

modulo

10

9

+ 7

.

Example 1:

Input:

$n = 3, k = 0$

Output:

1

Explanation:

Only the array [1,2,3] which consists of numbers from 1 to 3 has exactly 0 inverse pairs.

Example 2:

Input:

$n = 3, k = 1$

Output:

2

Explanation:

The array [1,3,2] and [2,1,3] have exactly 1 inverse pair.

Constraints:

$1 \leq n \leq 1000$

$0 \leq k \leq 1000$

Code Snippets

C++:

```
class Solution {
public:
    int kInversePairs(int n, int k) {

    }
};
```

Java:

```
class Solution {
    public int kInversePairs(int n, int k) {

    }
}
```

Python3:

```
class Solution:
    def kInversePairs(self, n: int, k: int) -> int:
```

Python:

```
class Solution(object):
    def kInversePairs(self, n, k):
        """
        :type n: int
        :type k: int
        :rtype: int
        """
```

JavaScript:

```
/**
 * @param {number} n
 * @param {number} k
 * @return {number}
 */
var kInversePairs = function(n, k) {

};
```

TypeScript:

```
function kInversePairs(n: number, k: number): number {

};
```

C#:

```
public class Solution {
    public int KInversePairs(int n, int k) {

    }
}
```

C:

```
int kInversePairs(int n, int k) {

}
```

Go:

```
func kInversePairs(n int, k int) int {  
  
}
```

Kotlin:

```
class Solution {  
    fun kInversePairs(n: Int, k: Int): Int {  
  
    }  
}
```

Swift:

```
class Solution {  
    func kInversePairs(_ n: Int, _ k: Int) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn k_inverse_pairs(n: i32, k: i32) -> i32 {  
  
    }  
}
```

Ruby:

```
# @param {Integer} n  
# @param {Integer} k  
# @return {Integer}  
def k_inverse_pairs(n, k)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param Integer $n
```

```

* @param Integer $k
* @return Integer
*/
function kInversePairs($n, $k) {

}

}

```

Dart:

```

class Solution {
  int kInversePairs(int n, int k) {

  }
}

```

Scala:

```

object Solution {
  def kInversePairs(n: Int, k: Int): Int = {

  }
}

```

Elixir:

```

defmodule Solution do
  @spec k_inverse_pairs(n :: integer, k :: integer) :: integer
  def k_inverse_pairs(n, k) do

  end
end

```

Erlang:

```

-spec k_inverse_pairs(N :: integer(), K :: integer()) -> integer().
k_inverse_pairs(N, K) ->
.

```

Racket:

```
(define/contract (k-inverse-pairs n k)
  (-> exact-integer? exact-integer? exact-integer?)
)
```

Solutions

C++ Solution:

```
/*
 * Problem: K Inverse Pairs Array
 * Difficulty: Hard
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
public:
    int kInversePairs(int n, int k) {

    }
};
```

Java Solution:

```
/**
 * Problem: K Inverse Pairs Array
 * Difficulty: Hard
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
    public int kInversePairs(int n, int k) {

    }
}
```

```
}
```

Python3 Solution:

```
"""
Problem: K Inverse Pairs Array
Difficulty: Hard
Tags: array, dp

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) or O(n * m) for DP table
"""

class Solution:
    def kInversePairs(self, n: int, k: int) -> int:
        # TODO: Implement optimized solution
        pass
```

Python Solution:

```
class Solution(object):
    def kInversePairs(self, n, k):
        """
        :type n: int
        :type k: int
        :rtype: int
        """
```

JavaScript Solution:

```
/**
 * Problem: K Inverse Pairs Array
 * Difficulty: Hard
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */
```



```

/**
 * @param {number} n
 * @param {number} k
 * @return {number}
 */
var kInversePairs = function(n, k) {

};

```

TypeScript Solution:

```

/**
 * Problem: K Inverse Pairs Array
 * Difficulty: Hard
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

function kInversePairs(n: number, k: number): number {

};

```

C# Solution:

```

/*
 * Problem: K Inverse Pairs Array
 * Difficulty: Hard
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

public class Solution {
    public int KInversePairs(int n, int k) {

    }
}

```

```
}
```

C Solution:

```
/*
 * Problem: K Inverse Pairs Array
 * Difficulty: Hard
 * Tags: array, dp
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

int kInversePairs(int n, int k) {

}
```

Go Solution:

```
// Problem: K Inverse Pairs Array
// Difficulty: Hard
// Tags: array, dp
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

func kInversePairs(n int, k int) int {

}
```

Kotlin Solution:

```
class Solution {
    fun kInversePairs(n: Int, k: Int): Int {

    }
}
```

Swift Solution:

```

class Solution {
    func kInversePairs(_ n: Int, _ k: Int) -> Int {

    }
}

```

Rust Solution:

```

// Problem: K Inverse Pairs Array
// Difficulty: Hard
// Tags: array, dp
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

impl Solution {
    pub fn k_inverse_pairs(n: i32, k: i32) -> i32 {

    }
}

```

Ruby Solution:

```

# @param {Integer} n
# @param {Integer} k
# @return {Integer}
def k_inverse_pairs(n, k)

end

```

PHP Solution:

```

class Solution {

    /**
     * @param Integer $n
     * @param Integer $k
     * @return Integer
     */
    function kInversePairs($n, $k) {

```

```
}  
}
```

Dart Solution:

```
class Solution {  
  int kInversePairs(int n, int k) {  
  
  }  
}
```

Scala Solution:

```
object Solution {  
  def kInversePairs(n: Int, k: Int): Int = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec k_inverse_pairs(n :: integer, k :: integer) :: integer  
  def k_inverse_pairs(n, k) do  
  
  end  
end
```

Erlang Solution:

```
-spec k_inverse_pairs(N :: integer(), K :: integer()) -> integer().  
k_inverse_pairs(N, K) ->  
.
```

Racket Solution:

```
(define/contract (k-inverse-pairs n k)  
  (-> exact-integer? exact-integer? exact-integer?)  
)
```