

Problem 3502: Minimum Cost to Reach Every Position

Problem Information

Difficulty: [Easy](#)

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given an integer array

$cost$

of size

n

. You are currently at position

n

(at the end of the line) in a line of

$n + 1$

people (numbered from 0 to

n

).

You wish to move forward in the line, but each person in front of you charges a specific amount to

swap

places. The cost to swap with person

i

is given by

$\text{cost}[i]$

.

You are allowed to swap places with people as follows:

If they are in front of you, you

must

pay them

$\text{cost}[i]$

to swap with them.

If they are behind you, they can swap with you for free.

Return an array

answer

of size

n

, where

$\text{answer}[i]$

is the

minimum

total cost to reach each position

i

in the line

.

Example 1:

Input:

cost = [5,3,4,1,3,2]

Output:

[5,3,3,1,1,1]

Explanation:

We can get to each position in the following way:

i = 0

. We can swap with person 0 for a cost of 5.

i =

1

. We can swap with person 1 for a cost of 3.

i = 2

. We can swap with person 1 for a cost of 3, then swap with person 2 for free.

$i = 3$

. We can swap with person 3 for a cost of 1.

$i = 4$

. We can swap with person 3 for a cost of 1, then swap with person 4 for free.

$i = 5$

. We can swap with person 3 for a cost of 1, then swap with person 5 for free.

Example 2:

Input:

$\text{cost} = [1, 2, 4, 6, 7]$

Output:

$[1, 1, 1, 1, 1]$

Explanation:

We can swap with person 0 for a cost of

1, then we will be able to reach any position

i

for free.

Constraints:

$1 \leq n == \text{cost.length} \leq 100$

$1 \leq \text{cost}[i] \leq 100$

Code Snippets

C++:

```
class Solution {  
public:  
    vector<int> minCosts(vector<int>& cost) {  
  
    }  
};
```

Java:

```
class Solution {  
    public int[] minCosts(int[] cost) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def minCosts(self, cost: List[int]) -> List[int]:
```

Python:

```
class Solution(object):  
    def minCosts(self, cost):  
        """  
        :type cost: List[int]  
        :rtype: List[int]  
        """
```

JavaScript:

```
/**  
 * @param {number[]} cost  
 * @return {number[]}  
 */  
var minCosts = function(cost) {  
  
};
```

TypeScript:

```
function minCosts(cost: number[]): number[] {  
  
};
```

C#:

```
public class Solution {  
    public int[] MinCosts(int[] cost) {  
  
    }  
}
```

C:

```
/**  
 * Note: The returned array must be malloced, assume caller calls free().  
 */  
int* minCosts(int* cost, int costSize, int* returnSize) {  
  
}
```

Go:

```
func minCosts(cost []int) []int {  
  
}
```

Kotlin:

```
class Solution {  
    fun minCosts(cost: IntArray): IntArray {  
  
    }  
}
```

Swift:

```
class Solution {  
    func minCosts(_ cost: [Int]) -> [Int] {  
  
    }  
}
```

```
}
```

Rust:

```
impl Solution {  
    pub fn min_costs(cost: Vec<i32>) -> Vec<i32> {  
  
    }  
}
```

Ruby:

```
# @param {Integer[]} cost  
# @return {Integer[]}  
def min_costs(cost)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param Integer[] $cost  
     * @return Integer[]  
     */  
    function minCosts($cost) {  
  
    }  
}
```

Dart:

```
class Solution {  
    List<int> minCosts(List<int> cost) {  
  
    }  
}
```

Scala:

```

object Solution {
  def minCosts(cost: Array[Int]): Array[Int] = {

  }
}

```

Elixir:

```

defmodule Solution do
  @spec min_costs(cost :: [integer]) :: [integer]
  def min_costs(cost) do

  end
end

```

Erlang:

```

-spec min_costs(Cost :: [integer()]) -> [integer()].
min_costs(Cost) ->
.

```

Racket:

```

(define/contract (min-costs cost)
  (-> (listof exact-integer?) (listof exact-integer?))
  )

```

Solutions

C++ Solution:

```

/*
 * Problem: Minimum Cost to Reach Every Position
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

```



```

class Solution {
public:
    vector<int> minCosts(vector<int>& cost) {

    }

};

```

Java Solution:

```

/**
 * Problem: Minimum Cost to Reach Every Position
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public int[] minCosts(int[] cost) {

    }

}

```

Python3 Solution:

```

"""
Problem: Minimum Cost to Reach Every Position
Difficulty: Easy
Tags: array

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def minCosts(self, cost: List[int]) -> List[int]:
        # TODO: Implement optimized solution
        pass

```

Python Solution:

```
class Solution(object):
    def minCosts(self, cost):
        """
        :type cost: List[int]
        :rtype: List[int]
        """
```

JavaScript Solution:

```
/**
 * Problem: Minimum Cost to Reach Every Position
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number[]} cost
 * @return {number[]}
 */
var minCosts = function(cost) {

};
```

TypeScript Solution:

```
/**
 * Problem: Minimum Cost to Reach Every Position
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function minCosts(cost: number[]): number[] {
```

```
};
```

C# Solution:

```
/*
 * Problem: Minimum Cost to Reach Every Position
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public int[] MinCosts(int[] cost) {

    }
}
```

C Solution:

```
/*
 * Problem: Minimum Cost to Reach Every Position
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* minCosts(int* cost, int costSize, int* returnSize) {

}
```

Go Solution:

```

// Problem: Minimum Cost to Reach Every Position
// Difficulty: Easy
// Tags: array
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func minCosts(cost []int) []int {

}

```

Kotlin Solution:

```

class Solution {
    fun minCosts(cost: IntArray): IntArray {

    }
}

```

Swift Solution:

```

class Solution {
    func minCosts(_ cost: [Int]) -> [Int] {

    }
}

```

Rust Solution:

```

// Problem: Minimum Cost to Reach Every Position
// Difficulty: Easy
// Tags: array
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn min_costs(cost: Vec<i32>) -> Vec<i32> {

    }
}

```

```
}
```

Ruby Solution:

```
# @param {Integer[]} cost
# @return {Integer[]}
def min_costs(cost)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $cost
     * @return Integer[]
     */
    function minCosts($cost) {

    }

}
```

Dart Solution:

```
class Solution {
  List<int> minCosts(List<int> cost) {

  }

}
```

Scala Solution:

```
object Solution {
  def minCosts(cost: Array[Int]): Array[Int] = {

  }

}
```

Elixir Solution:

```
defmodule Solution do
  @spec min_costs(cost :: [integer]) :: [integer]
  def min_costs(cost) do

  end
end
```

Erlang Solution:

```
-spec min_costs(Cost :: [integer()]) -> [integer()].
min_costs(Cost) ->
.
```

Racket Solution:

```
(define/contract (min-costs cost)
  (-> (listof exact-integer?) (listof exact-integer?))
)
```