

Problem 637: Average of Levels in Binary Tree

Problem Information

Difficulty: Easy

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given the

root

of a binary tree, return

the average value of the nodes on each level in the form of an array


. Answers within

10

-5

of the actual answer will be accepted.

Example 1:




Input:

root = [3,9,20,null,null,15,7]

Output:

[3.00000,14.50000,11.00000] Explanation: The average value of nodes on level 0 is 3, on level 1 is 14.5, and on level 2 is 11. Hence return [3, 14.5, 11].

Example 2:



Input:

root = [3,9,20,15,7]

Output:

[3.00000,14.50000,11.00000]

Constraints:

The number of nodes in the tree is in the range

[1, 10

4

]

.

-2

31

<= Node.val <= 2

31

- 1

Code Snippets

C++:

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     TreeNode *left;
 *     TreeNode *right;
 *     TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *     TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *     TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
 *     right(right) {}
 * };
 */
class Solution {
public:
    vector<double> averageOfLevels(TreeNode* root) {

    }
};
```

Java:

```
/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     int val;
 *     TreeNode left;
 *     TreeNode right;
 *     TreeNode() {}

```

```

* TreeNode(int val) { this.val = val; }
* TreeNode(int val, TreeNode left, TreeNode right) {
* this.val = val;
* this.left = left;
* this.right = right;
* }
* }
*/
class Solution {
public List<Double> averageOfLevels(TreeNode root) {

}

}

```

Python3:

```

# Definition for a binary tree node.
# class TreeNode:
# def __init__(self, val=0, left=None, right=None):
# self.val = val
# self.left = left
# self.right = right
class Solution:
def averageOfLevels(self, root: Optional[TreeNode]) -> List[float]:

```

Python:

```

# Definition for a binary tree node.
# class TreeNode(object):
# def __init__(self, val=0, left=None, right=None):
# self.val = val
# self.left = left
# self.right = right
class Solution(object):
def averageOfLevels(self, root):
"""
:type root: Optional[TreeNode]
:rtype: List[float]
"""

```

JavaScript:

```

/**
 * Definition for a binary tree node.
 * function TreeNode(val, left, right) {
 *   this.val = (val===undefined ? 0 : val)
 *   this.left = (left===undefined ? null : left)
 *   this.right = (right===undefined ? null : right)
 * }
 */
/**
 * @param {TreeNode} root
 * @return {number[]}
 */
var averageOfLevels = function(root) {

};

```

TypeScript:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   val: number
 *   left: TreeNode | null
 *   right: TreeNode | null
 *   constructor(val?: number, left?: TreeNode | null, right?: TreeNode | null)
 *   {
 *     this.val = (val===undefined ? 0 : val)
 *     this.left = (left===undefined ? null : left)
 *     this.right = (right===undefined ? null : right)
 *   }
 * }
 */

function averageOfLevels(root: TreeNode | null): number[] {

};

```

C#:

```

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *   public int val;

```

```

* public TreeNode left;
* public TreeNode right;
* public TreeNode(int val=0, TreeNode left=null, TreeNode right=null) {
* this.val = val;
* this.left = left;
* this.right = right;
* }
* }
*/

public class Solution {
public IList<double> AverageOfLevels(TreeNode root) {

}

}

```

C:

```

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 * int val;
 * struct TreeNode *left;
 * struct TreeNode *right;
 * };
 */
/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
double* averageOfLevels(struct TreeNode* root, int* returnSize) {

}

```

Go:

```

/**
 * Definition for a binary tree node.
 * type TreeNode struct {
 * Val int
 * Left *TreeNode
 * Right *TreeNode
 * }
 */

```

```
func averageOfLevels(root *TreeNode) []float64 {

}
```

Kotlin:

```
/**
 * Example:
 * var ti = TreeNode(5)
 * var v = ti.`val`
 * Definition for a binary tree node.
 * class TreeNode(var `val`: Int) {
 *     var left: TreeNode? = null
 *     var right: TreeNode? = null
 * }
 */
class Solution {
    fun averageOfLevels(root: TreeNode?): DoubleArray {

    }
}
```

Swift:

```
/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     public var val: Int
 *     public var left: TreeNode?
 *     public var right: TreeNode?
 *     public init() { self.val = 0; self.left = nil; self.right = nil; }
 *     public init(_ val: Int) { self.val = val; self.left = nil; self.right = nil; }
 *     public init(_ val: Int, _ left: TreeNode?, _ right: TreeNode?) {
 *         self.val = val
 *         self.left = left
 *         self.right = right
 *     }
 * }
 */
class Solution {
    func averageOfLevels(_ root: TreeNode?) -> [Double] {
```



```
}  
}
```

Rust:

```
// Definition for a binary tree node.  
// #[derive(Debug, PartialEq, Eq)]  
// pub struct TreeNode {  
//   pub val: i32,  
//   pub left: Option<Rc<RefCell<TreeNode>>>,  
//   pub right: Option<Rc<RefCell<TreeNode>>>,  
// }  
//  
// impl TreeNode {  
//   #[inline]  
//   pub fn new(val: i32) -> Self {  
//     TreeNode {  
//       val,  
//       left: None,  
//       right: None  
//     }  
//   }  
// }  
// }  
  
use std::rc::Rc;  
use std::cell::RefCell;  
impl Solution {  
  pub fn average_of_levels(root: Option<Rc<RefCell<TreeNode>>>) -> Vec<f64> {  
  
  }  
}
```

Ruby:

```
# Definition for a binary tree node.  
# class TreeNode  
#   attr_accessor :val, :left, :right  
#   def initialize(val = 0, left = nil, right = nil)  
#     @val = val  
#     @left = left  
#     @right = right  
#   end  
end
```

```

# end
# @param {TreeNode} root
# @return {Float[]}
def average_of_levels(root)

end

```

PHP:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 * public $val = null;
 * public $left = null;
 * public $right = null;
 * function __construct($val = 0, $left = null, $right = null) {
 * $this->val = $val;
 * $this->left = $left;
 * $this->right = $right;
 * }
 * }
 */
class Solution {

/**
 * @param TreeNode $root
 * @return Float[]
 */
function averageOfLevels($root) {

}

}

```

Dart:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 * int val;
 * TreeNode? left;
 * TreeNode? right;
 * TreeNode([this.val = 0, this.left, this.right]);

```

```

* }
*/
class Solution {
    List<double> averageOfLevels(TreeNode? root) {

    }
}

```

Scala:

```

/**
 * Definition for a binary tree node.
 * class TreeNode(_value: Int = 0, _left: TreeNode = null, _right: TreeNode =
 * null) {
 *   var value: Int = _value
 *   var left: TreeNode = _left
 *   var right: TreeNode = _right
 * }
 */
object Solution {
    def averageOfLevels(root: TreeNode): Array[Double] = {

    }
}

```

Elixir:

```

# Definition for a binary tree node.
#
# defmodule TreeNode do
#   @type t :: %__MODULE__{
#     val: integer,
#     left: TreeNode.t() | nil,
#     right: TreeNode.t() | nil
#   }
#   defstruct val: 0, left: nil, right: nil
# end

defmodule Solution do
  @spec average_of_levels(root :: TreeNode.t | nil) :: [float]
  def average_of_levels(root) do

```

```
end
end
```

Erlang:

```
%% Definition for a binary tree node.
%%
%% -record(tree_node, {val = 0 :: integer(),
%% left = null :: 'null' | #tree_node{},
%% right = null :: 'null' | #tree_node{}}).

-spec average_of_levels(Root :: #tree_node{} | null) -> [float()].
average_of_levels(Root) ->
.
```

Racket:

```
; Definition for a binary tree node.
#|

; val : integer?
; left : (or/c tree-node? #f)
; right : (or/c tree-node? #f)
(struct tree-node
  (val left right) #:mutable #:transparent)

; constructor
(define (make-tree-node [val 0])
  (tree-node val #f #f))

|#

(define/contract (average-of-levels root)
  (-> (or/c tree-node? #f) (listof flonum?))
  )
```

Solutions

C++ Solution:

```

/*
 * Problem: Average of Levels in Binary Tree
 * Difficulty: Easy
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     TreeNode *left;
 *     TreeNode *right;
 *     TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *     TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *     TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
 *     right(right) {}
 * };
 */
class Solution {
public:
    vector<double> averageOfLevels(TreeNode* root) {

    }
};

```

Java Solution:

```

/**
 * Problem: Average of Levels in Binary Tree
 * Difficulty: Easy
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**

```

```

* Definition for a binary tree node.
* public class TreeNode {
*   int val;
*   TreeNode left;
*   TreeNode right;
*   TreeNode() {}
*   TreeNode(int val) { this.val = val; }
*   TreeNode(int val, TreeNode left, TreeNode right) {
*     this.val = val;
*     this.left = left;
*     this.right = right;
*   }
* }
*/
class Solution {
public List<Double> averageOfLevels(TreeNode root) {

}

}

```

Python3 Solution:

```

"""
Problem: Average of Levels in Binary Tree
Difficulty: Easy
Tags: array, tree, search

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(h) for recursion stack where h is height
"""

# Definition for a binary tree node.
# class TreeNode:
#     def __init__(self, val=0, left=None, right=None):
#         self.val = val
#         self.left = left
#         self.right = right
class Solution:
    def averageOfLevels(self, root: Optional[TreeNode]) -> List[float]:
        # TODO: Implement optimized solution

```

```
pass
```

Python Solution:

```
# Definition for a binary tree node.
# class TreeNode(object):
#     def __init__(self, val=0, left=None, right=None):
#         self.val = val
#         self.left = left
#         self.right = right
class Solution(object):
    def averageOfLevels(self, root):
        """
        :type root: Optional[TreeNode]
        :rtype: List[float]
        """
```

JavaScript Solution:

```
/**
 * Problem: Average of Levels in Binary Tree
 * Difficulty: Easy
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * function TreeNode(val, left, right) {
 *     this.val = (val===undefined ? 0 : val)
 *     this.left = (left===undefined ? null : left)
 *     this.right = (right===undefined ? null : right)
 * }
 */
/**
 * @param {TreeNode} root
 * @return {number[]}
 */
```

```

var averageOfLevels = function(root) {

};

```

TypeScript Solution:

```

/**
 * Problem: Average of Levels in Binary Tree
 * Difficulty: Easy
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   val: number
 *   left: TreeNode | null
 *   right: TreeNode | null
 *   constructor(val?: number, left?: TreeNode | null, right?: TreeNode | null)
 *   {
 *     this.val = (val===undefined ? 0 : val)
 *     this.left = (left===undefined ? null : left)
 *     this.right = (right===undefined ? null : right)
 *   }
 * }
 */

function averageOfLevels(root: TreeNode | null): number[] {

};

```

C# Solution:

```

/*
 * Problem: Average of Levels in Binary Tree
 * Difficulty: Easy
 * Tags: array, tree, search

```



```

*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(h) for recursion stack where h is height
*/

/**
* Definition for a binary tree node.
* public class TreeNode {
* public int val;
* public TreeNode left;
* public TreeNode right;
* public TreeNode(int val=0, TreeNode left=null, TreeNode right=null) {
* this.val = val;
* this.left = left;
* this.right = right;
* }
* }
*/
public class Solution {
public IList<double> AverageOfLevels(TreeNode root) {

}
}

```

C Solution:

```

/*
* Problem: Average of Levels in Binary Tree
* Difficulty: Easy
* Tags: array, tree, search
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(h) for recursion stack where h is height
*/

/**
* Definition for a binary tree node.
* struct TreeNode {
* int val;

```

```

* struct TreeNode *left;
* struct TreeNode *right;
* };
*/
/**
* Note: The returned array must be malloced, assume caller calls free().
*/
double* averageOfLevels(struct TreeNode* root, int* returnSize) {

}

```

Go Solution:

```

// Problem: Average of Levels in Binary Tree
// Difficulty: Easy
// Tags: array, tree, search
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

/**
* Definition for a binary tree node.
* type TreeNode struct {
*     Val int
*     Left *TreeNode
*     Right *TreeNode
* }
*/
func averageOfLevels(root *TreeNode) []float64 {

}

```

Kotlin Solution:

```

/**
* Example:
* var ti = TreeNode(5)
* var v = ti.`val`
* Definition for a binary tree node.
* class TreeNode(var `val`: Int) {

```

```

* var left: TreeNode? = null
* var right: TreeNode? = null
* }
*/
class Solution {
fun averageOfLevels(root: TreeNode?): DoubleArray {

}
}

```

Swift Solution:

```

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 * public var val: Int
 * public var left: TreeNode?
 * public var right: TreeNode?
 * public init() { self.val = 0; self.left = nil; self.right = nil; }
 * public init(_ val: Int) { self.val = val; self.left = nil; self.right =
nil; }
 * public init(_ val: Int, _ left: TreeNode?, _ right: TreeNode?) {
 * self.val = val
 * self.left = left
 * self.right = right
 * }
 * }
 */
class Solution {
func averageOfLevels(_ root: TreeNode?) -> [Double] {

}
}

```

Rust Solution:

```

// Problem: Average of Levels in Binary Tree
// Difficulty: Easy
// Tags: array, tree, search
//
// Approach: Use two pointers or sliding window technique

```

```

// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

// Definition for a binary tree node.
// #[derive(Debug, PartialEq, Eq)]
// pub struct TreeNode {
//     pub val: i32,
//     pub left: Option<Rc<RefCell<TreeNode>>>,
//     pub right: Option<Rc<RefCell<TreeNode>>>,
// }
//
// impl TreeNode {
//     #[inline]
//     pub fn new(val: i32) -> Self {
//         TreeNode {
//             val,
//             left: None,
//             right: None
//         }
//     }
// }

use std::rc::Rc;
use std::cell::RefCell;

impl Solution {
    pub fn average_of_levels(root: Option<Rc<RefCell<TreeNode>>>) -> Vec<f64> {

    }
}

```

Ruby Solution:

```

# Definition for a binary tree node.
# class TreeNode
#   attr_accessor :val, :left, :right
#   def initialize(val = 0, left = nil, right = nil)
#     @val = val
#     @left = left
#     @right = right
#   end
# end

# @param {TreeNode} root

```

```
# @return {Float[]}
def average_of_levels(root)

end
```

PHP Solution:

```
/**
 * Definition for a binary tree node.
 * class TreeNode {
 * public $val = null;
 * public $left = null;
 * public $right = null;
 * function __construct($val = 0, $left = null, $right = null) {
 * $this->val = $val;
 * $this->left = $left;
 * $this->right = $right;
 * }
 * }
 */
class Solution {

/**
 * @param TreeNode $root
 * @return Float[]
 */
function averageOfLevels($root) {

}

}
```

Dart Solution:

```
/**
 * Definition for a binary tree node.
 * class TreeNode {
 * int val;
 * TreeNode? left;
 * TreeNode? right;
 * TreeNode([this.val = 0, this.left, this.right]);
 * }
 */
```

```

*/
class Solution {
List<double> averageOfLevels(TreeNode? root) {

}

}

```

Scala Solution:

```

/**
 * Definition for a binary tree node.
 * class TreeNode(_value: Int = 0, _left: TreeNode = null, _right: TreeNode =
null) {
 *   var value: Int = _value
 *   var left: TreeNode = _left
 *   var right: TreeNode = _right
 * }
 */
object Solution {
def averageOfLevels(root: TreeNode): Array[Double] = {

}

}

```

Elixir Solution:

```

# Definition for a binary tree node.
#
# defmodule TreeNode do
#   @type t :: %__MODULE__{
#     val: integer,
#     left: TreeNode.t() | nil,
#     right: TreeNode.t() | nil
#   }
#   defstruct val: 0, left: nil, right: nil
# end

defmodule Solution do
  @spec average_of_levels(root :: TreeNode.t | nil) :: [float]
  def average_of_levels(root) do

```

```
end
end
```

Erlang Solution:

```
%% Definition for a binary tree node.
%%
%% -record(tree_node, {val = 0 :: integer(),
%% left = null :: 'null' | #tree_node{},
%% right = null :: 'null' | #tree_node{}}).

-spec average_of_levels(Root :: #tree_node{} | null) -> [float()].
average_of_levels(Root) ->
.

```

Racket Solution:

```
; Definition for a binary tree node.
#|

; val : integer?
; left : (or/c tree-node? #f)
; right : (or/c tree-node? #f)
(struct tree-node
  (val left right) #:mutable #:transparent)

; constructor
(define (make-tree-node [val 0])
  (tree-node val #f #f))

|#

(define/contract (average-of-levels root)
  (-> (or/c tree-node? #f) (listof flonum?))
  )

```