

Problem 1396: Design Underground System

Problem Information

Difficulty: Medium

Acceptance Rate: 74.22%

Paid Only: No

Tags: Hash Table, String, Design

Problem Description

An underground railway system is keeping track of customer travel times between different stations. They are using this data to calculate the average time it takes to travel from one station to another.

Implement the `UndergroundSystem` class:

```
* `void checkIn(int id, string stationName, int t)` * A customer with a card ID equal to `id`,
checks in at the station `stationName` at time `t`. * A customer can only be checked into one
place at a time. * `void checkOut(int id, string stationName, int t)` * A customer with a card ID
equal to `id`, checks out from the station `stationName` at time `t`. * `double
getAverageTime(string startStation, string endStation)` * Returns the average time it takes to
travel from `startStation` to `endStation`. * The average time is computed from all the previous
traveling times from `startStation` to `endStation` that happened **directly**, meaning a
check in at `startStation` followed by a check out from `endStation`. * The time it takes to
travel from `startStation` to `endStation` **may be different** from the time it takes to travel
from `endStation` to `startStation`. * There will be at least one customer that has traveled from
`startStation` to `endStation` before `getAverageTime` is called.
```

You may assume all calls to the `checkIn` and `checkOut` methods are consistent. If a customer checks in at time `t1` then checks out at time `t2`, then `t1 < t2`. All events happen in chronological order.

****Example 1:****

```
**Input** ["UndergroundSystem","checkIn","checkIn","checkIn","checkOut","checkOut","check
Out","getAverageTime","getAverageTime","checkIn","getAverageTime","checkOut","getAvera
geTime"] [[],[45,"Leyton",3],[32,"Paradise",8],[27,"Leyton",10],[45,"Waterloo",15],[27,"Waterlo
```

```

o",20],[32,"Cambridge",22],[["Paradise","Cambridge"],["Leyton","Waterloo"],[10,"Leyton",24],[
Leyton","Waterloo"],[10,"Waterloo",38],[["Leyton","Waterloo"]] **Output**
[null,null,null,null,null,null,14.00000,11.00000,null,11.00000,null,12.00000]
**Explanation** UndergroundSystem undergroundSystem = new UndergroundSystem();
undergroundSystem.checkIn(45, "Leyton", 3); undergroundSystem.checkIn(32, "Paradise",
8); undergroundSystem.checkIn(27, "Leyton", 10); undergroundSystem.checkOut(45,
"Waterloo", 15); // Customer 45 "Leyton" -> "Waterloo" in 15-3 = 12
undergroundSystem.checkOut(27, "Waterloo", 20); // Customer 27 "Leyton" -> "Waterloo" in
20-10 = 10 undergroundSystem.checkOut(32, "Cambridge", 22); // Customer 32 "Paradise" ->
"Cambridge" in 22-8 = 14 undergroundSystem.getAverageTime("Paradise", "Cambridge"); //
return 14.00000. One trip "Paradise" -> "Cambridge", (14) / 1 = 14
undergroundSystem.getAverageTime("Leyton", "Waterloo"); // return 11.00000. Two trips
"Leyton" -> "Waterloo", (10 + 12) / 2 = 11 undergroundSystem.checkIn(10, "Leyton", 24);
undergroundSystem.getAverageTime("Leyton", "Waterloo"); // return 11.00000
undergroundSystem.checkOut(10, "Waterloo", 38); // Customer 10 "Leyton" -> "Waterloo" in
38-24 = 14 undergroundSystem.getAverageTime("Leyton", "Waterloo"); // return 12.00000.
Three trips "Leyton" -> "Waterloo", (10 + 12 + 14) / 3 = 12

```

Example 2:

```

**Input** ["UndergroundSystem","checkIn","checkOut","getAverageTime","checkIn","checkOu
t","getAverageTime","checkIn","checkOut","getAverageTime"] [[],[10,"Leyton",3],[10,"Paradise",
8],[["Leyton","Paradise"],[5,"Leyton",10],[5,"Paradise",16],[["Leyton","Paradise"],[2,"Leyton",21
],[2,"Paradise",30],[["Leyton","Paradise"]]] **Output**
[null,null,null,5.00000,null,null,5.50000,null,null,6.66667] **Explanation** UndergroundSystem
undergroundSystem = new UndergroundSystem(); undergroundSystem.checkIn(10, "Leyton",
3); undergroundSystem.checkOut(10, "Paradise", 8); // Customer 10 "Leyton" -> "Paradise" in
8-3 = 5 undergroundSystem.getAverageTime("Leyton", "Paradise"); // return 5.00000, (5) / 1 =
5 undergroundSystem.checkIn(5, "Leyton", 10); undergroundSystem.checkOut(5, "Paradise",
16); // Customer 5 "Leyton" -> "Paradise" in 16-10 = 6
undergroundSystem.getAverageTime("Leyton", "Paradise"); // return 5.50000, (5 + 6) / 2 = 5.5
undergroundSystem.checkIn(2, "Leyton", 21); undergroundSystem.checkOut(2, "Paradise",
30); // Customer 2 "Leyton" -> "Paradise" in 30-21 = 9
undergroundSystem.getAverageTime("Leyton", "Paradise"); // return 6.66667, (5 + 6 + 9) / 3 =
6.66667

```

Constraints:

* `1` <= id, t <= 106 * `1` <= stationName.length, startStation.length, endStation.length <= 10 *
All strings consist of uppercase and lowercase English letters and digits. * There will be at
most `2 * 104` calls **in total** to `checkIn`, `checkOut`, and `getAverageTime`. * Answers
within `10-5` of the actual value will be accepted.

Code Snippets

C++:

```
class UndergroundSystem {
public:
    UndergroundSystem() {

    }

    void checkIn(int id, string stationName, int t) {

    }

    void checkOut(int id, string stationName, int t) {

    }

    double getAverageTime(string startStation, string endStation) {

    }
};

/**
 * Your UndergroundSystem object will be instantiated and called as such:
 * UndergroundSystem* obj = new UndergroundSystem();
 * obj->checkIn(id,stationName,t);
 * obj->checkOut(id,stationName,t);
 * double param_3 = obj->getAverageTime(startStation,endStation);
 */
```

Java:

```
class UndergroundSystem {

    public UndergroundSystem() {

    }

    public void checkIn(int id, String stationName, int t) {
```

```

}

public void checkOut(int id, String stationName, int t) {

}

public double getAverageTime(String startStation, String endStation) {

}
}

/**
 * Your UndergroundSystem object will be instantiated and called as such:
 * UndergroundSystem obj = new UndergroundSystem();
 * obj.checkIn(id,stationName,t);
 * obj.checkOut(id,stationName,t);
 * double param_3 = obj.getAverageTime(startStation,endStation);
 */

```

Python3:

```

class UndergroundSystem:

    def __init__(self):

    def checkIn(self, id: int, stationName: str, t: int) -> None:

    def checkOut(self, id: int, stationName: str, t: int) -> None:

    def getAverageTime(self, startStation: str, endStation: str) -> float:

    # Your UndergroundSystem object will be instantiated and called as such:
    # obj = UndergroundSystem()
    # obj.checkIn(id,stationName,t)
    # obj.checkOut(id,stationName,t)
    # param_3 = obj.getAverageTime(startStation,endStation)

```

