

Problem 2331: Evaluate Boolean Binary Tree

Problem Information

Difficulty: Easy

Acceptance Rate: 82.41%

Paid Only: No

Tags: Tree, Depth-First Search, Binary Tree

Problem Description

You are given the `root` of a **full binary tree** with the following properties:

- Leaf nodes** have either the value `0` or `1`, where `0` represents `False` and `1` represents `True`.
- Non-leaf nodes** have either the value `2` or `3`, where `2` represents the boolean `OR` and `3` represents the boolean `AND`.

The **evaluation** of a node is as follows:

- If the node is a leaf node, the evaluation is the **value** of the node, i.e. `True` or `False`.
- Otherwise, **evaluate** the node's two children and **apply** the boolean operation of its value with the children's evaluations.

Return `the boolean result of evaluating the root node.`

A **full binary tree** is a binary tree where each node has either `0` or `2` children.

A **leaf node** is a node that has zero children.

Example 1:



Input: `root = [2,1,3,null,null,0,1]` **Output:** `true` **Explanation:** The above diagram illustrates the evaluation process. The AND node evaluates to `False AND True = False`. The OR node evaluates to `True OR False = True`. The root node evaluates to `True`, so we return `true`.

****Example 2:****

****Input:**** root = [0] ****Output:**** false ****Explanation:**** The root node is a leaf node and it evaluates to false, so we return false.

****Constraints:****

* The number of nodes in the tree is in the range `[1, 1000]`. * `0 <= Node.val <= 3` * Every node has either `0` or `2` children. * Leaf nodes have a value of `0` or `1`. * Non-leaf nodes have a value of `2` or `3`.

Code Snippets

C++:

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     TreeNode *left;
 *     TreeNode *right;
 *     TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *     TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *     TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
 *     right(right) {}
 * };
 */
class Solution {
public:
    bool evaluateTree(TreeNode* root) {

    }
};
```

Java:

```
/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     int val;
```

```

* TreeNode left;
* TreeNode right;
* TreeNode() {}
* TreeNode(int val) { this.val = val; }
* TreeNode(int val, TreeNode left, TreeNode right) {
* this.val = val;
* this.left = left;
* this.right = right;
* }
* }
*/
class Solution {
public boolean evaluateTree(TreeNode root) {

}
}

```

Python3:

```

# Definition for a binary tree node.
# class TreeNode:
# def __init__(self, val=0, left=None, right=None):
# self.val = val
# self.left = left
# self.right = right
class Solution:
def evaluateTree(self, root: Optional[TreeNode]) -> bool:

```