

# Problem 3449: Maximize the Minimum Game Score

## Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given an array

points

of size

$n$

and an integer

$m$

. There is another array

gameScore

of size

$n$

, where

gameScore[i]

represents the score achieved at the

i

th

game. Initially,

`gameScore[i] == 0`

for all

i

.

You start at index -1, which is outside the array (before the first position at index 0). You can make

at most

m

moves. In each move, you can either:

Increase the index by 1 and add

`points[i]`

to

`gameScore[i]`

.

Decrease the index by 1 and add

`points[i]`

to

gameScore[i]

.

Note

that the index must always remain within the bounds of the array after the first move.

Return the

maximum possible minimum

value in

gameScore

after

at most

m

moves.

Example 1:

Input:

points = [2,4], m = 3

Output:

4

Explanation:

Initially, index

$i = -1$

and

$\text{gameScore} = [0, 0]$

.

Move

Index

$\text{gameScore}$

Increase

$i$

0

$[2, 0]$

Increase

$i$

1

$[2, 4]$

Decrease

$i$

0

$[4, 4]$

The minimum value in

gameScore

is 4, and this is the maximum possible minimum among all configurations. Hence, 4 is the output.

Example 2:

Input:

points = [1,2,3], m = 5

Output:

2

Explanation:

Initially, index

i = -1

and

gameScore = [0, 0, 0]

.

Move

Index

gameScore

Increase

i

0

[1, 0, 0]

Increase

i

1

[1, 2, 0]

Decrease

i

0

[2, 2, 0]

Increase

i

1

[2, 4, 0]

Increase

i

2

[2, 4, 3]

The minimum value in

gameScore

is 2, and this is the maximum possible minimum among all configurations. Hence, 2 is the output.

Constraints:

$2 \leq n \leq \text{points.length} \leq 5 * 10$

4

$1 \leq \text{points}[i] \leq 10$

6

$1 \leq m \leq 10$

9

## Code Snippets

**C++:**

```
class Solution {
public:
    long long maxScore(vector<int>& points, int m) {

    }
};
```

**Java:**

```
class Solution {
    public long maxScore(int[] points, int m) {

    }
}
```

**Python3:**

```
class Solution:
    def maxScore(self, points: List[int], m: int) -> int:
```

### Python:

```
class Solution(object):  
    def maxScore(self, points, m):  
        """  
        :type points: List[int]  
        :type m: int  
        :rtype: int  
        """
```

### JavaScript:

```
/**  
 * @param {number[]} points  
 * @param {number} m  
 * @return {number}  
 */  
var maxScore = function(points, m) {  
  
};
```

### TypeScript:

```
function maxScore(points: number[], m: number): number {  
  
};
```

### C#:

```
public class Solution {  
    public long MaxScore(int[] points, int m) {  
  
    }  
}
```

### C:

```
long long maxScore(int* points, int pointsSize, int m) {  
  
}
```

### Go:



```
func maxScore(points []int, m int) int64 {  
  
}
```

### Kotlin:

```
class Solution {  
    fun maxScore(points: IntArray, m: Int): Long {  
  
    }  
}
```

### Swift:

```
class Solution {  
    func maxScore(_ points: [Int], _ m: Int) -> Int {  
  
    }  
}
```

### Rust:

```
impl Solution {  
    pub fn max_score(points: Vec<i32>, m: i32) -> i64 {  
  
    }  
}
```

### Ruby:

```
# @param {Integer[]} points  
# @param {Integer} m  
# @return {Integer}  
def max_score(points, m)  
  
end
```

### PHP:

```
class Solution {  
  
    /**  
     * @param Integer[] $points
```

```

* @param Integer $m
* @return Integer
*/
function maxScore($points, $m) {

}

}

```

### Dart:

```

class Solution {
  int maxScore(List<int> points, int m) {

  }
}

```

### Scala:

```

object Solution {
  def maxScore(points: Array[Int], m: Int): Long = {

  }
}

```

### Elixir:

```

defmodule Solution do
  @spec max_score(points :: [integer], m :: integer) :: integer
  def max_score(points, m) do

  end
end

```

### Erlang:

```

-spec max_score(Points :: [integer()], M :: integer()) -> integer().
max_score(Points, M) ->
.

```

### Racket:

```
(define/contract (max-score points m)
  (-> (listof exact-integer?) exact-integer? exact-integer?)
)
```

## Solutions

### C++ Solution:

```
/*
 * Problem: Maximize the Minimum Game Score
 * Difficulty: Hard
 * Tags: array, greedy, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    long long maxScore(vector<int>& points, int m) {

    }
};
```

### Java Solution:

```
/**
 * Problem: Maximize the Minimum Game Score
 * Difficulty: Hard
 * Tags: array, greedy, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public long maxScore(int[] points, int m) {

    }
}
```

```
}
```

### Python3 Solution:

```
"""
Problem: Maximize the Minimum Game Score
Difficulty: Hard
Tags: array, greedy, search

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def maxScore(self, points: List[int], m: int) -> int:
        # TODO: Implement optimized solution
        pass
```

### Python Solution:

```
class Solution(object):
    def maxScore(self, points, m):
        """
        :type points: List[int]
        :type m: int
        :rtype: int
        """
```

### JavaScript Solution:

```
/**
 * Problem: Maximize the Minimum Game Score
 * Difficulty: Hard
 * Tags: array, greedy, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */
```

```

/**
 * @param {number[]} points
 * @param {number} m
 * @return {number}
 */
var maxScore = function(points, m) {

};

```

### TypeScript Solution:

```

/**
 * Problem: Maximize the Minimum Game Score
 * Difficulty: Hard
 * Tags: array, greedy, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function maxScore(points: number[], m: number): number {

};

```

### C# Solution:

```

/*
 * Problem: Maximize the Minimum Game Score
 * Difficulty: Hard
 * Tags: array, greedy, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public long MaxScore(int[] points, int m) {

    }
}

```

```
}
```

### C Solution:

```
/*
 * Problem: Maximize the Minimum Game Score
 * Difficulty: Hard
 * Tags: array, greedy, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

long long maxScore(int* points, int pointsSize, int m) {

}
```

### Go Solution:

```
// Problem: Maximize the Minimum Game Score
// Difficulty: Hard
// Tags: array, greedy, search
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func maxScore(points []int, m int) int64 {

}
```

### Kotlin Solution:

```
class Solution {
    fun maxScore(points: IntArray, m: Int): Long {

    }
}
```

### Swift Solution:

```

class Solution {
func maxScore(_ points: [Int], _ m: Int) -> Int {

}

}

```

### Rust Solution:

```

// Problem: Maximize the Minimum Game Score
// Difficulty: Hard
// Tags: array, greedy, search
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
pub fn max_score(points: Vec<i32>, m: i32) -> i64 {

}

}

```

### Ruby Solution:

```

# @param {Integer[]} points
# @param {Integer} m
# @return {Integer}
def max_score(points, m)

end

```

### PHP Solution:

```

class Solution {

/**
 * @param Integer[] $points
 * @param Integer $m
 * @return Integer
 */
function maxScore($points, $m) {

```

```
}  
}
```

### Dart Solution:

```
class Solution {  
  int maxScore(List<int> points, int m) {  
  
  }  
}
```

### Scala Solution:

```
object Solution {  
  def maxScore(points: Array[Int], m: Int): Long = {  
  
  }  
}
```

### Elixir Solution:

```
defmodule Solution do  
  @spec max_score(points :: [integer], m :: integer) :: integer  
  def max_score(points, m) do  
  
  end  
end
```

### Erlang Solution:

```
-spec max_score(Points :: [integer()], M :: integer()) -> integer().  
max_score(Points, M) ->  
.
```

### Racket Solution:

```
(define/contract (max-score points m)  
  (-> (listof exact-integer?) exact-integer? exact-integer?)  
  )
```