

# Problem 234: Palindrome Linked List

## Problem Information

Difficulty: **Easy**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

Given the

head

of a singly linked list, return

true

if it is a

palindrome


or

false

otherwise

.

Example 1:




Input:

head = [1,2,2,1]

Output:

true

Example 2:



Input:

head = [1,2]

Output:

false

Constraints:

The number of nodes in the list is in the range

[1, 10

5

]

.

$0 \leq \text{Node.val} \leq 9$

Follow up:

Could you do it in

$O(n)$

time and

$O(1)$

space?

## Code Snippets

### C++:

```
/**
 * Definition for singly-linked list.
 * struct ListNode {
 *   int val;
 *   ListNode *next;
 *   ListNode() : val(0), next(nullptr) {}
 *   ListNode(int x) : val(x), next(nullptr) {}
 *   ListNode(int x, ListNode *next) : val(x), next(next) {}
 * };
 */
class Solution {
public:
    bool isPalindrome(ListNode* head) {

    }
};
```

### Java:

```
/**
 * Definition for singly-linked list.
 * public class ListNode {
 *   int val;
 *   ListNode next;
 *   ListNode() {}
 *   ListNode(int val) { this.val = val; }
 * }
```

```

* ListNode(int val, ListNode next) { this.val = val; this.next = next; }
* }
*/

class Solution {
public boolean isPalindrome(ListNode head) {

}
}

```

### Python3:

```

# Definition for singly-linked list.
# class ListNode:
# def __init__(self, val=0, next=None):
# self.val = val
# self.next = next
class Solution:
def isPalindrome(self, head: Optional[ListNode]) -> bool:

```

### Python:

```

# Definition for singly-linked list.
# class ListNode(object):
# def __init__(self, val=0, next=None):
# self.val = val
# self.next = next
class Solution(object):
def isPalindrome(self, head):
    """
    :type head: Optional[ListNode]
    :rtype: bool
    """

```

### JavaScript:

```

/**
* Definition for singly-linked list.
* function ListNode(val, next) {
* this.val = (val===undefined ? 0 : val)
* this.next = (next===undefined ? null : next)
* }
*/

```

```

/**
 * @param {ListNode} head
 * @return {boolean}
 */
var isPalindrome = function(head) {

};

```

## TypeScript:

```

/**
 * Definition for singly-linked list.
 * class ListNode {
 *   val: number
 *   next: ListNode | null
 *   constructor(val?: number, next?: ListNode | null) {
 *     this.val = (val===undefined ? 0 : val)
 *     this.next = (next===undefined ? null : next)
 *   }
 * }
 */

function isPalindrome(head: ListNode | null): boolean {

};

```

## C#:

```

/**
 * Definition for singly-linked list.
 * public class ListNode {
 *   public int val;
 *   public ListNode next;
 *   public ListNode(int val=0, ListNode next=null) {
 *     this.val = val;
 *     this.next = next;
 *   }
 * }
 */

public class Solution {
    public bool IsPalindrome(ListNode head) {

```

```
}  
}
```

**C:**

```
/**  
 * Definition for singly-linked list.  
 * struct ListNode {  
 *   int val;  
 *   struct ListNode *next;  
 * };  
 */  
bool isPalindrome(struct ListNode* head) {  
  
}
```

**Go:**

```
/**  
 * Definition for singly-linked list.  
 * type ListNode struct {  
 *   Val int  
 *   Next *ListNode  
 * }  
 */  
func isPalindrome(head *ListNode) bool {  
  
}
```

**Kotlin:**

```
/**  
 * Example:  
 * var li = ListNode(5)  
 * var v = li.`val`  
 * Definition for singly-linked list.  
 * class ListNode(var `val`: Int) {  
 *   var next: ListNode? = null  
 * }  
 */  
class Solution {  
    fun isPalindrome(head: ListNode?): Boolean {
```

```
}  
}
```

## Swift:

```
/**  
 * Definition for singly-linked list.  
 * public class ListNode {  
 * public var val: Int  
 * public var next: ListNode?  
 * public init() { self.val = 0; self.next = nil; }  
 * public init(_ val: Int) { self.val = val; self.next = nil; }  
 * public init(_ val: Int, _ next: ListNode?) { self.val = val; self.next =  
next; }  
 * }  
 */  
class Solution {  
func isPalindrome(_ head: ListNode?) -> Bool {  
  
}  
}
```

## Rust:

```
// Definition for singly-linked list.  
// #[derive(PartialEq, Eq, Clone, Debug)]  
// pub struct ListNode {  
// pub val: i32,  
// pub next: Option<Box<ListNode>>  
// }  
//  
// impl ListNode {  
// #[inline]  
// fn new(val: i32) -> Self {  
// ListNode {  
// next: None,  
// val  
// }  
// }  
// }  
impl Solution {
```

```

pub fn is_palindrome(head: Option<Box<ListNode>>) -> bool {

}

}

```

## Ruby:

```

# Definition for singly-linked list.
# class ListNode
#   attr_accessor :val, :next
#   def initialize(val = 0, _next = nil)
#     @val = val
#     @next = _next
#   end
# end
# @param {ListNode} head
# @return {Boolean}
def is_palindrome(head)

end

```

## PHP:

```

/**
 * Definition for a singly-linked list.
 * class ListNode {
 *   public $val = 0;
 *   public $next = null;
 *   function __construct($val = 0, $next = null) {
 *     $this->val = $val;
 *     $this->next = $next;
 *   }
 * }
 */
class Solution {

/**
 * @param ListNode $head
 * @return Boolean
 */
function isPalindrome($head) {

```



```
}  
}
```

### Dart:

```
/**  
 * Definition for singly-linked list.  
 * class ListNode {  
 *   int val;  
 *   ListNode? next;  
 *   ListNode([this.val = 0, this.next]);  
 * }  
 */  
class Solution {  
  bool isPalindrome(ListNode? head) {  
  
  }  
}
```

### Scala:

```
/**  
 * Definition for singly-linked list.  
 * class ListNode(_x: Int = 0, _next: ListNode = null) {  
 *   var next: ListNode = _next  
 *   var x: Int = _x  
 * }  
 */  
object Solution {  
  def isPalindrome(head: ListNode): Boolean = {  
  
  }  
}
```

### Elixir:

```
# Definition for singly-linked list.  
#  
# defmodule ListNode do  
#   @type t :: %__MODULE__{  
#     val: integer,  
#     next: ListNode.t() | nil  
#   }
```

```

# }
# defstruct val: 0, next: nil
# end

defmodule Solution do
  @spec is_palindrome(head :: ListNode.t | nil) :: boolean
  def is_palindrome(head) do

  end
end

```

## Erlang:

```

%% Definition for singly-linked list.
%%
%% -record(list_node, {val = 0 :: integer(),
%% next = null :: 'null' | #list_node{}}).

-spec is_palindrome(Head :: #list_node{} | null) -> boolean().
is_palindrome(Head) ->
.

```

## Racket:

```

; Definition for singly-linked list:
#|

; val : integer?
; next : (or/c list-node? #f)
(struct list-node
  (val next) #:mutable #:transparent)

; constructor
(define (make-list-node [val 0])
  (list-node val #f))

|#

(define/contract (is-palindrome head)
  (-> (or/c list-node? #f) boolean?)
)

```

## Solutions

### C++ Solution:

```
/*
 * Problem: Palindrome Linked List
 * Difficulty: Easy
 * Tags: array, string, linked_list, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Definition for singly-linked list.
 * struct ListNode {
 *   int val;
 *   ListNode *next;
 *   ListNode() : val(0), next(nullptr) {
 *     // TODO: Implement optimized solution
 *   }
 *   return 0;
 *   ListNode(int x) : val(x), next(nullptr) {
 *     // TODO: Implement optimized solution
 *   }
 *   return 0;
 *   ListNode(int x, ListNode *next) : val(x), next(next) {
 *     // TODO: Implement optimized solution
 *   }
 *   return 0;
 * };
 */

class Solution {
public:
    bool isPalindrome(ListNode* head) {

    }
};
```

### Java Solution:

```

/**
 * Problem: Palindrome Linked List
 * Difficulty: Easy
 * Tags: array, string, linked_list, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Definition for singly-linked list.
 * public class ListNode {
 *     int val;
 *     ListNode next;
 *     ListNode() {
 * // TODO: Implement optimized solution
 * return 0;
 * }
 *     ListNode(int val) { this.val = val; }
 *     ListNode(int val, ListNode next) { this.val = val; this.next = next; }
 * }
 */
class Solution {
public boolean isPalindrome(ListNode head) {

}

}

```

### Python3 Solution:

```

"""
Problem: Palindrome Linked List
Difficulty: Easy
Tags: array, string, linked_list, stack

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

# Definition for singly-linked list.

```

```

# class ListNode:
# def __init__(self, val=0, next=None):
# self.val = val
# self.next = next
class Solution:
def isPalindrome(self, head: Optional[ListNode]) -> bool:
# TODO: Implement optimized solution
pass

```

### Python Solution:

```

# Definition for singly-linked list.
# class ListNode(object):
# def __init__(self, val=0, next=None):
# self.val = val
# self.next = next
class Solution(object):
def isPalindrome(self, head):
    """
    :type head: Optional[ListNode]
    :rtype: bool
    """

```

### JavaScript Solution:

```

/**
 * Problem: Palindrome Linked List
 * Difficulty: Easy
 * Tags: array, string, linked_list, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Definition for singly-linked list.
 * function ListNode(val, next) {
 * this.val = (val===undefined ? 0 : val)
 * this.next = (next===undefined ? null : next)
 * }

```

```

*/
/**
 * @param {ListNode} head
 * @return {boolean}
 */
var isPalindrome = function(head) {

};

```

### TypeScript Solution:

```

/**
 * Problem: Palindrome Linked List
 * Difficulty: Easy
 * Tags: array, string, linked_list, stack
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Definition for singly-linked list.
 * class ListNode {
 *   val: number
 *   next: ListNode | null
 *   constructor(val?: number, next?: ListNode | null) {
 *     this.val = (val===undefined ? 0 : val)
 *     this.next = (next===undefined ? null : next)
 *   }
 * }
 */

function isPalindrome(head: ListNode | null): boolean {

};

```

### C# Solution:

```

/*
 * Problem: Palindrome Linked List

```

```

* Difficulty: Easy
* Tags: array, string, linked_list, stack
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

/**
* Definition for singly-linked list.
* public class ListNode {
* public int val;
* public ListNode next;
* public ListNode(int val=0, ListNode next=null) {
* this.val = val;
* this.next = next;
* }
* }
*/
public class Solution {
public bool IsPalindrome(ListNode head) {

}
}

```

## C Solution:

```

/*
* Problem: Palindrome Linked List
* Difficulty: Easy
* Tags: array, string, linked_list, stack
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

/**
* Definition for singly-linked list.
* struct ListNode {
* int val;

```

```

* struct ListNode *next;
* };
*/
bool isPalindrome(struct ListNode* head) {

}

```

### Go Solution:

```

// Problem: Palindrome Linked List
// Difficulty: Easy
// Tags: array, string, linked_list, stack
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

/**
 * Definition for singly-linked list.
 * type ListNode struct {
 *     Val int
 *     Next *ListNode
 * }
 */
func isPalindrome(head *ListNode) bool {

}

```

### Kotlin Solution:

```

/**
 * Example:
 * var li = ListNode(5)
 * var v = li.`val`
 * Definition for singly-linked list.
 * class ListNode(var `val`: Int) {
 *     var next: ListNode? = null
 * }
 */
class Solution {
fun isPalindrome(head: ListNode?): Boolean {

```



```
}  
}
```

### Swift Solution:

```
/**  
 * Definition for singly-linked list.  
 * public class ListNode {  
 * public var val: Int  
 * public var next: ListNode?  
 * public init() { self.val = 0; self.next = nil; }  
 * public init(_ val: Int) { self.val = val; self.next = nil; }  
 * public init(_ val: Int, _ next: ListNode?) { self.val = val; self.next =  
next; }  
 * }  
 */  
class Solution {  
func isPalindrome(_ head: ListNode?) -> Bool {  
  
}  
}
```

### Rust Solution:

```
// Problem: Palindrome Linked List  
// Difficulty: Easy  
// Tags: array, string, linked_list, stack  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(1) to O(n) depending on approach  
  
// Definition for singly-linked list.  
// #[derive(PartialEq, Eq, Clone, Debug)]  
// pub struct ListNode {  
// pub val: i32,  
// pub next: Option<Box<ListNode>>  
// }  
//  
// impl ListNode {
```

```

// #[inline]
// fn new(val: i32) -> Self {
// ListNode {
// next: None,
// val
// }
// }
// }

impl Solution {
pub fn is_palindrome(head: Option<Box<ListNode>>) -> bool {

}
}

```

### Ruby Solution:

```

# Definition for singly-linked list.
# class ListNode
# attr_accessor :val, :next
# def initialize(val = 0, _next = nil)
# @val = val
# @next = _next
# end
# end

# @param {ListNode} head
# @return {Boolean}
def is_palindrome(head)

end

```

### PHP Solution:

```

/**
 * Definition for a singly-linked list.
 * class ListNode {
 * public $val = 0;
 * public $next = null;
 * function __construct($val = 0, $next = null) {
 * $this->val = $val;
 * $this->next = $next;
 * }

```

```

* }
*/
class Solution {

/**
 * @param ListNode $head
 * @return Boolean
 */
function isPalindrome($head) {

}

}

```

### Dart Solution:

```

/**
 * Definition for singly-linked list.
 * class ListNode {
 *   int val;
 *   ListNode? next;
 *   ListNode([this.val = 0, this.next]);
 * }
 */
class Solution {
  bool isPalindrome(ListNode? head) {

  }

}

```

### Scala Solution:

```

/**
 * Definition for singly-linked list.
 * class ListNode(_x: Int = 0, _next: ListNode = null) {
 *   var next: ListNode = _next
 *   var x: Int = _x
 * }
 */
object Solution {
  def isPalindrome(head: ListNode): Boolean = {

```

```
}  
}
```

### Elixir Solution:

```
# Definition for singly-linked list.  
#  
# defmodule ListNode do  
# @type t :: %__MODULE__{  
#   val: integer,  
#   next: ListNode.t() | nil  
# }  
# defstruct val: 0, next: nil  
# end  
  
defmodule Solution do  
  @spec is_palindrome(head :: ListNode.t | nil) :: boolean  
  def is_palindrome(head) do  
  
  end  
end
```

### Erlang Solution:

```
%% Definition for singly-linked list.  
%%  
%% -record(list_node, {val = 0 :: integer(),  
%%   next = null :: 'null' | #list_node{}}).  
  
-spec is_palindrome(Head :: #list_node{} | null) -> boolean().  
is_palindrome(Head) ->  
.
```

### Racket Solution:

```
; Definition for singly-linked list:  
#|  
  
; val : integer?  
; next : (or/c list-node? #f)  
(struct list-node
```

```
(val next) #:mutable #:transparent)

; constructor
(define (make-list-node [val 0])
  (list-node val #f))

|#

(define/contract (is-palindrome head)
  (-> (or/c list-node? #f) boolean?)
)
```