

Problem 798: Smallest Rotation with Highest Score

Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given an array

`nums`

. You can rotate it by a non-negative integer

`k`

so that the array becomes

`[nums[k], nums[k + 1], ... nums[nums.length - 1], nums[0], nums[1], ..., nums[k-1]]`

. Afterward, any entries that are less than or equal to their index are worth one point.

For example, if we have

`nums = [2,4,1,3,0]`

, and we rotate by

`k = 2`

, it becomes

`[1,3,0,2,4]`

. This is worth

3

points because

$1 > 0$

[no points],

$3 > 1$

[no points],

$0 \leq 2$

[one point],

$2 \leq 3$

[one point],

$4 \leq 4$

[one point].

Return

the rotation index

k

that corresponds to the highest score we can achieve if we rotated

nums

by it

. If there are multiple answers, return the smallest such index

k

.

Example 1:

Input:

nums = [2,3,1,4,0]

Output:

3

Explanation:

Scores for each k are listed below: k = 0, nums = [2,3,1,4,0], score 2 k = 1, nums = [3,1,4,0,2], score 3 k = 2, nums = [1,4,0,2,3], score 3 k = 3, nums = [4,0,2,3,1], score 4 k = 4, nums = [0,2,3,1,4], score 3 So we should choose k = 3, which has the highest score.

Example 2:

Input:

nums = [1,3,0,2,4]

Output:

0

Explanation:

nums will always have 3 points no matter how it shifts. So we will choose the smallest k, which is 0.

Constraints:

1 <= nums.length <= 10

5

0 <= nums[i] < nums.length

Code Snippets

C++:

```
class Solution {
public:
    int bestRotation(vector<int>& nums) {

    }
};
```

Java:

```
class Solution {
    public int bestRotation(int[] nums) {

    }
}
```

Python3:

```
class Solution:
    def bestRotation(self, nums: List[int]) -> int:
```

Python:

```
class Solution(object):
    def bestRotation(self, nums):
        """
        :type nums: List[int]
        :rtype: int
        """
```

JavaScript:

```

/**
 * @param {number[]} nums
 * @return {number}
 */
var bestRotation = function(nums) {

};

```

TypeScript:

```

function bestRotation(nums: number[]): number {

};

```

C#:

```

public class Solution {
    public int BestRotation(int[] nums) {

    }
}

```

C:

```

int bestRotation(int* nums, int numsSize) {

}

```

Go:

```

func bestRotation(nums []int) int {

}

```

Kotlin:

```

class Solution {
    fun bestRotation(nums: IntArray): Int {

    }
}

```

Swift:

```

class Solution {
    func bestRotation(_ nums: [Int]) -> Int {

    }
}

```

Rust:

```

impl Solution {
    pub fn best_rotation(nums: Vec<i32>) -> i32 {

    }
}

```

Ruby:

```

# @param {Integer[]} nums
# @return {Integer}
def best_rotation(nums)

end

```

PHP:

```

class Solution {

    /**
     * @param Integer[] $nums
     * @return Integer
     */
    function bestRotation($nums) {

    }

}

```

Dart:

```

class Solution {
    int bestRotation(List<int> nums) {

    }
}

```

Scala:

```
object Solution {  
  def bestRotation(nums: Array[Int]): Int = {  
  
  }  
}
```

Elixir:

```
defmodule Solution do  
  @spec best_rotation(nums :: [integer]) :: integer  
  def best_rotation(nums) do  
  
  end  
end
```

Erlang:

```
-spec best_rotation(Nums :: [integer()]) -> integer().  
best_rotation(Nums) ->  
.
```

Racket:

```
(define/contract (best-rotation nums)  
  (-> (listof exact-integer?) exact-integer?)  
)
```

Solutions

C++ Solution:

```
/*  
 * Problem: Smallest Rotation with Highest Score  
 * Difficulty: Hard  
 * Tags: array  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(1) to O(n) depending on approach  
 */
```

```

class Solution {
public:
    int bestRotation(vector<int>& nums) {

    }
};

```

Java Solution:

```

/**
 * Problem: Smallest Rotation with Highest Score
 * Difficulty: Hard
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public int bestRotation(int[] nums) {

    }
}

```

Python3 Solution:

```

"""
Problem: Smallest Rotation with Highest Score
Difficulty: Hard
Tags: array

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def bestRotation(self, nums: List[int]) -> int:
        # TODO: Implement optimized solution

```



```
pass
```

Python Solution:

```
class Solution(object):
    def bestRotation(self, nums):
        """
        :type nums: List[int]
        :rtype: int
        """
```

JavaScript Solution:

```
/**
 * Problem: Smallest Rotation with Highest Score
 * Difficulty: Hard
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number[]} nums
 * @return {number}
 */
var bestRotation = function(nums) {

};
```

TypeScript Solution:

```
/**
 * Problem: Smallest Rotation with Highest Score
 * Difficulty: Hard
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
```

```

*/

function bestRotation(nums: number[]): number {

};

```

C# Solution:

```

/*
 * Problem: Smallest Rotation with Highest Score
 * Difficulty: Hard
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public int BestRotation(int[] nums) {

    }
}

```

C Solution:

```

/*
 * Problem: Smallest Rotation with Highest Score
 * Difficulty: Hard
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

int bestRotation(int* nums, int numsSize) {

}

```

Go Solution:

```

// Problem: Smallest Rotation with Highest Score
// Difficulty: Hard
// Tags: array
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func bestRotation(nums []int) int {

}

```

Kotlin Solution:

```

class Solution {
    fun bestRotation(nums: IntArray): Int {

    }
}

```

Swift Solution:

```

class Solution {
    func bestRotation(_ nums: [Int]) -> Int {

    }
}

```

Rust Solution:

```

// Problem: Smallest Rotation with Highest Score
// Difficulty: Hard
// Tags: array
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn best_rotation(nums: Vec<i32>) -> i32 {

    }
}

```

```
}
```

Ruby Solution:

```
# @param {Integer[]} nums
# @return {Integer}
def best_rotation(nums)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $nums
     * @return Integer
     */
    function bestRotation($nums) {

    }

}
```

Dart Solution:

```
class Solution {
  int bestRotation(List<int> nums) {

  }

}
```

Scala Solution:

```
object Solution {
  def bestRotation(nums: Array[Int]): Int = {

  }

}
```

Elixir Solution:

```
defmodule Solution do
  @spec best_rotation(nums :: [integer]) :: integer
  def best_rotation(nums) do

  end
end
```

Erlang Solution:

```
-spec best_rotation(Nums :: [integer()]) -> integer().
best_rotation(Nums) ->
.
```

Racket Solution:

```
(define/contract (best-rotation nums)
  (-> (listof exact-integer?) exact-integer?)
  )
```