

# Problem 641: Design Circular Deque

## Problem Information

**Difficulty:** Medium

**Acceptance Rate:** 64.39%

**Paid Only:** No

**Tags:** Array, Linked List, Design, Queue

## Problem Description

Design your implementation of the circular double-ended queue (deque).

Implement the `MyCircularDeque` class:

```
* `MyCircularDeque(int k)` Initializes the deque with a maximum size of `k`. * `boolean insertFront()` Adds an item at the front of Deque. Returns `true` if the operation is successful, or `false` otherwise. * `boolean insertLast()` Adds an item at the rear of Deque. Returns `true` if the operation is successful, or `false` otherwise. * `boolean deleteFront()` Deletes an item from the front of Deque. Returns `true` if the operation is successful, or `false` otherwise. * `boolean deleteLast()` Deletes an item from the rear of Deque. Returns `true` if the operation is successful, or `false` otherwise. * `int getFront()` Returns the front item from the Deque. Returns `-1` if the deque is empty. * `int getRear()` Returns the last item from Deque. Returns `-1` if the deque is empty. * `boolean isEmpty()` Returns `true` if the deque is empty, or `false` otherwise. * `boolean isFull()` Returns `true` if the deque is full, or `false` otherwise.
```

**Example 1:**

```
Input ["MyCircularDeque", "insertLast", "insertLast", "insertFront", "insertFront", "getRear", "isFull", "deleteLast", "insertFront", "getFront"] [[3], [1], [2], [3], [4], [], [], [], [4], []] Output [null, true, true, true, false, 2, true, true, true, 4] Explanation MyCircularDeque myCircularDeque = new MyCircularDeque(3); myCircularDeque.insertLast(1); // return True myCircularDeque.insertLast(2); // return True myCircularDeque.insertFront(3); // return True myCircularDeque.insertFront(4); // return False, the queue is full. myCircularDeque.getRear(); // return 2 myCircularDeque.isFull(); // return True myCircularDeque.deleteLast(); // return True myCircularDeque.insertFront(4); // return True myCircularDeque.getFront(); // return 4
```

**Constraints:**

\*`1 <= k <= 1000` \*`0 <= value <= 1000` \* At most `2000` calls will be made to `insertFront`, `insertLast`, `deleteFront`, `deleteLast`, `getFront`, `getRear`, `isEmpty`, `isFull`.

## Code Snippets

### C++:

```
class MyCircularDeque {
public:
    MyCircularDeque(int k) {

    }

    bool insertFront(int value) {

    }

    bool insertLast(int value) {

    }

    bool deleteFront() {

    }

    bool deleteLast() {

    }

    int getFront() {

    }

    int getRear() {

    }

    bool isEmpty() {

    }
}
```

```

bool isFull() {

}

};

/**
 * Your MyCircularDeque object will be instantiated and called as such:
 * MyCircularDeque* obj = new MyCircularDeque(k);
 * bool param_1 = obj->insertFront(value);
 * bool param_2 = obj->insertLast(value);
 * bool param_3 = obj->deleteFront();
 * bool param_4 = obj->deleteLast();
 * int param_5 = obj->getFront();
 * int param_6 = obj->getRear();
 * bool param_7 = obj->isEmpty();
 * bool param_8 = obj->isFull();
 */

```

## Java:

```

class MyCircularDeque {

    public MyCircularDeque(int k) {

    }

    public boolean insertFront(int value) {

    }

    public boolean insertLast(int value) {

    }

    public boolean deleteFront() {

    }

    public boolean deleteLast() {

    }

}

```

```

public int getFront() {

}

public int getRear() {

}

public boolean isEmpty() {

}

public boolean isFull() {

}

}

/**
 * Your MyCircularDeque object will be instantiated and called as such:
 * MyCircularDeque obj = new MyCircularDeque(k);
 * boolean param_1 = obj.insertFront(value);
 * boolean param_2 = obj.insertLast(value);
 * boolean param_3 = obj.deleteFront();
 * boolean param_4 = obj.deleteLast();
 * int param_5 = obj.getFront();
 * int param_6 = obj.getRear();
 * boolean param_7 = obj.isEmpty();
 * boolean param_8 = obj.isFull();
 */

```

### Python3:

```

class MyCircularDeque:

    def __init__(self, k: int):

    def insertFront(self, value: int) -> bool:

    def insertLast(self, value: int) -> bool:

```

```
def deleteFront(self) -> bool:
```

```
def deleteLast(self) -> bool:
```

```
def getFront(self) -> int:
```

```
def getRear(self) -> int:
```

```
def isEmpty(self) -> bool:
```

```
def isFull(self) -> bool:
```

```
# Your MyCircularDeque object will be instantiated and called as such:
```

```
# obj = MyCircularDeque(k)
```

```
# param_1 = obj.insertFront(value)
```

```
# param_2 = obj.insertLast(value)
```

```
# param_3 = obj.deleteFront()
```

```
# param_4 = obj.deleteLast()
```

```
# param_5 = obj.getFront()
```

```
# param_6 = obj.getRear()
```

```
# param_7 = obj.isEmpty()
```

```
# param_8 = obj.isFull()
```