

# Problem 2022: Convert 1D Array Into 2D Array

## Problem Information

Difficulty: [Easy](#)

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given a

0-indexed

1-dimensional (1D) integer array

original

, and two integers,

m

and

n

. You are tasked with creating a 2-dimensional (2D) array with

m

rows and

n

columns using

all

the elements from

original

.

The elements from indices

0

to

$n - 1$

(

inclusive

) of

original

should form the first row of the constructed 2D array, the elements from indices

$n$

to

$2 * n - 1$

(

inclusive

) should form the second row of the constructed 2D array, and so on.

Return


an

$m \times n$

2D array constructed according to the above procedure, or an empty 2D array if it is impossible

.

Example 1:



Input:

original = [1,2,3,4],  $m = 2$ ,  $n = 2$

Output:

[[1,2],[3,4]]

Explanation:

The constructed 2D array should contain 2 rows and 2 columns. The first group of  $n=2$  elements in original, [1,2], becomes the first row in the constructed 2D array. The second group of  $n=2$  elements in original, [3,4], becomes the second row in the constructed 2D array.

Example 2:

Input:

original = [1,2,3],  $m = 1$ ,  $n = 3$

Output:

[[1,2,3]]

Explanation:

The constructed 2D array should contain 1 row and 3 columns. Put all three elements in original into the first row of the constructed 2D array.

Example 3:

Input:

original = [1,2], m = 1, n = 1

Output:

[]

Explanation:

There are 2 elements in original. It is impossible to fit 2 elements in a 1x1 2D array, so return an empty 2D array.

Constraints:

$1 \leq \text{original.length} \leq 5 * 10$

4

$1 \leq \text{original}[i] \leq 10$

5

$1 \leq m, n \leq 4 * 10$

4

## Code Snippets

### C++:

```
class Solution {
public:
    vector<vector<int>> construct2DArray(vector<int>& original, int m, int n) {

    }
};
```

### Java:

```
class Solution {
    public int[][] construct2DArray(int[] original, int m, int n) {

    }
}
```

### Python3:

```
class Solution:
    def construct2DArray(self, original: List[int], m: int, n: int) ->
        List[List[int]]:
```

### Python:

```
class Solution(object):
    def construct2DArray(self, original, m, n):
        """
        :type original: List[int]
        :type m: int
        :type n: int
        :rtype: List[List[int]]
        """
```

### JavaScript:

```
/**
 * @param {number[]} original
 * @param {number} m
 * @param {number} n
 * @return {number[][]}
```

```

*/
var construct2DArray = function(original, m, n) {

};

```

### TypeScript:

```

function construct2DArray(original: number[], m: number, n: number):
number[][] {

};

```

### C#:

```

public class Solution {
public int[][] Construct2DArray(int[] original, int m, int n) {

}

}

```

### C:

```

/**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume
 caller calls free().
 */
int** construct2DArray(int* original, int originalSize, int m, int n, int*
returnSize, int** returnColumnSizes) {

}

```

### Go:

```

func construct2DArray(original []int, m int, n int) [][]int {

}

```

### Kotlin:

```

class Solution {
    fun construct2DArray(original: IntArray, m: Int, n: Int): Array<IntArray> {

    }
}

```

### Swift:

```

class Solution {
    func construct2DArray(_ original: [Int], _ m: Int, _ n: Int) -> [[Int]] {

    }
}

```

### Rust:

```

impl Solution {
    pub fn construct2_d_array(original: Vec<i32>, m: i32, n: i32) ->
        Vec<Vec<i32>> {

    }
}

```

### Ruby:

```

# @param {Integer[]} original
# @param {Integer} m
# @param {Integer} n
# @return {Integer[][]}
def construct2_d_array(original, m, n)

end

```

### PHP:

```

class Solution {

    /**
     * @param Integer[] $original
     * @param Integer $m
     * @param Integer $n
     * @return Integer[][]
     */
}

```

```
function construct2DArray($original, $m, $n) {

}

}
```

#### Dart:

```
class Solution {
  List<List<int>> construct2DArray(List<int> original, int m, int n) {

  }
}
```

#### Scala:

```
object Solution {
  def construct2DArray(original: Array[Int], m: Int, n: Int): Array[Array[Int]]
  = {

  }
}
```

#### Elixir:

```
defmodule Solution do
  @spec construct2_d_array(original :: [integer], m :: integer, n :: integer)
  :: [[integer]]
  def construct2_d_array(original, m, n) do

  end
end
```

#### Erlang:

```
-spec construct2_d_array(Original :: [integer()], M :: integer(), N ::
integer()) -> [[integer()]].
construct2_d_array(Original, M, N) ->
.
```

#### Racket:



```
(define/contract (construct2-d-array original m n)
  (-> (listof exact-integer?) exact-integer? exact-integer? (listof (listof
    exact-integer?))))
)
```

## Solutions

### C++ Solution:

```
/*
 * Problem: Convert 1D Array Into 2D Array
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    vector<vector<int>> construct2DArray(vector<int>& original, int m, int n) {

    }
};
```

### Java Solution:

```
/**
 * Problem: Convert 1D Array Into 2D Array
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public int[][] construct2DArray(int[] original, int m, int n) {
```

```
}  
}
```

### Python3 Solution:

```
"""  
Problem: Convert 1D Array Into 2D Array  
Difficulty: Easy  
Tags: array  
  
Approach: Use two pointers or sliding window technique  
Time Complexity: O(n) or O(n log n)  
Space Complexity: O(1) to O(n) depending on approach  
"""  
  
class Solution:  
    def construct2DArray(self, original: List[int], m: int, n: int) ->  
        List[List[int]]:  
        # TODO: Implement optimized solution  
        pass
```

### Python Solution:

```
class Solution(object):  
    def construct2DArray(self, original, m, n):  
        """  
        :type original: List[int]  
        :type m: int  
        :type n: int  
        :rtype: List[List[int]]  
        """
```

### JavaScript Solution:

```
/**  
 * Problem: Convert 1D Array Into 2D Array  
 * Difficulty: Easy  
 * Tags: array  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)
```

```

* Space Complexity: O(1) to O(n) depending on approach
*/

/**
* @param {number[]} original
* @param {number} m
* @param {number} n
* @return {number[][]}
*/
var construct2DArray = function(original, m, n) {

};

```

### TypeScript Solution:

```

/**
* Problem: Convert 1D Array Into 2D Array
* Difficulty: Easy
* Tags: array
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

function construct2DArray(original: number[], m: number, n: number):
number[][] {

};

```

### C# Solution:

```

/*
* Problem: Convert 1D Array Into 2D Array
* Difficulty: Easy
* Tags: array
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

```

```

public class Solution {
public int[][] Construct2DArray(int[] original, int m, int n) {

}

}

```

## C Solution:

```

/*
 * Problem: Convert 1D Array Into 2D Array
 * Difficulty: Easy
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume
 caller calls free().
 */
int** construct2DArray(int* original, int originalSize, int m, int n, int*
returnSize, int** returnColumnSizes) {

}

```

## Go Solution:

```

// Problem: Convert 1D Array Into 2D Array
// Difficulty: Easy
// Tags: array
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func construct2DArray(original []int, m int, n int) [][]int {

```

```
}
```

### Kotlin Solution:

```
class Solution {  
    fun construct2DArray(original: IntArray, m: Int, n: Int): Array<IntArray> {  
  
    }  
}
```

### Swift Solution:

```
class Solution {  
    func construct2DArray(_ original: [Int], _ m: Int, _ n: Int) -> [[Int]] {  
  
    }  
}
```

### Rust Solution:

```
// Problem: Convert 1D Array Into 2D Array  
// Difficulty: Easy  
// Tags: array  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(1) to O(n) depending on approach  
  
impl Solution {  
    pub fn construct2_d_array(original: Vec<i32>, m: i32, n: i32) ->  
        Vec<Vec<i32>> {  
  
    }  
}
```

### Ruby Solution:

```
# @param {Integer[]} original  
# @param {Integer} m  
# @param {Integer} n
```

```
# @return {Integer[][]}
def construct2_d_array(original, m, n)

end
```

### PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $original
     * @param Integer $m
     * @param Integer $n
     * @return Integer[][]
     */
    function construct2DArray($original, $m, $n) {

    }

}
```

### Dart Solution:

```
class Solution {
  List<List<int>> construct2DArray(List<int> original, int m, int n) {

  }

}
```

### Scala Solution:

```
object Solution {
  def construct2DArray(original: Array[Int], m: Int, n: Int): Array[Array[Int]]
  = {

  }

}
```

### Elixir Solution:

```
defmodule Solution do
  @spec construct2_d_array(original :: [integer], m :: integer, n :: integer)
```

```
:: [[integer]]  
def construct2_d_array(original, m, n) do  
  
end  
end
```

### Erlang Solution:

```
-spec construct2_d_array(Original :: [integer()], M :: integer(), N ::  
integer()) -> [[integer()]].  
construct2_d_array(Original, M, N) ->  
.
```

### Racket Solution:

```
(define/contract (construct2-d-array original m n)  
  (-> (listof exact-integer?) exact-integer? exact-integer? (listof (listof  
    exact-integer?)))  
  )
```