

# Problem 1735: Count Ways to Make Array With Product

## Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

You are given a 2D integer array,

`queries`

. For each

`queries[i]`

, where

`queries[i] = [n`

`i`

, `k`

`i`

`]`

, find the number of different ways you can place positive integers into an array of size

`n`

`i`

such that the product of the integers is

k

i

. As the number of ways may be too large, the answer to the

i

th

query is the number of ways

modulo

10

9

+ 7

.

Return

an integer array

answer

where

answer.length == queries.length

, and

answer[i]

is the answer to the

i

th

query.

Example 1:

Input:

queries = [[2,6],[5,1],[73,660]]

Output:

[4,1,50734910]

Explanation:

Each query is independent. [2,6]: There are 4 ways to fill an array of size 2 that multiply to 6: [1,6], [2,3], [3,2], [6,1]. [5,1]: There is 1 way to fill an array of size 5 that multiply to 1: [1,1,1,1,1]. [73,660]: There are 1050734917 ways to fill an array of size 73 that multiply to 660. 1050734917 modulo 10

9

+ 7 = 50734910.

Example 2:

Input:

queries = [[1,1],[2,2],[3,3],[4,4],[5,5]]

Output:

[1,2,3,10,5]

Constraints:

$1 \leq \text{queries.length} \leq 10$

4

$1 \leq n$

i

, k

i

$\leq 10$

4

## Code Snippets

**C++:**

```
class Solution {
public:
    vector<int> waysToFillArray(vector<vector<int>>& queries) {

    }
};
```

**Java:**

```
class Solution {
    public int[] waysToFillArray(int[][] queries) {

    }
}
```

**Python3:**

```
class Solution:
def waysToFillArray(self, queries: List[List[int]]) -> List[int]:
```

## Python:

```
class Solution(object):
def waysToFillArray(self, queries):
"""
:type queries: List[List[int]]
:rtype: List[int]
"""
```

## JavaScript:

```
/**
 * @param {number[][]} queries
 * @return {number[]}
 */
var waysToFillArray = function(queries) {

};
```

## TypeScript:

```
function waysToFillArray(queries: number[][]): number[] {

};
```

## C#:

```
public class Solution {
public int[] WaysToFillArray(int[][] queries) {

}
}
```

## C:

```
/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* waysToFillArray(int** queries, int queriesSize, int* queriesColSize,
int* returnSize) {
```

```
}
```

### Go:

```
func waysToFillArray(queries [][]int) []int {  
  
}
```

### Kotlin:

```
class Solution {  
    fun waysToFillArray(queries: Array<IntArray>): IntArray {  
  
    }  
}
```

### Swift:

```
class Solution {  
    func waysToFillArray(_ queries: [[Int]]) -> [Int] {  
  
    }  
}
```

### Rust:

```
impl Solution {  
    pub fn ways_to_fill_array(queries: Vec<Vec<i32>>) -> Vec<i32> {  
  
    }  
}
```

### Ruby:

```
# @param {Integer[][]} queries  
# @return {Integer[]}  
def ways_to_fill_array(queries)  
  
end
```

### PHP:

```

class Solution {

  /**
   * @param Integer[][] $queries
   * @return Integer[]
   */
  function waysToFillArray($queries) {

  }

}

```

### Dart:

```

class Solution {
  List<int> waysToFillArray(List<List<int>> queries) {

  }

}

```

### Scala:

```

object Solution {
  def waysToFillArray(queries: Array[Array[Int]]): Array[Int] = {

  }

}

```

### Elixir:

```

defmodule Solution do
  @spec ways_to_fill_array(queries :: [[integer]]) :: [integer]
  def ways_to_fill_array(queries) do

  end

end

```

### Erlang:

```

-spec ways_to_fill_array(Queries :: [[integer()]]) -> [integer()].
ways_to_fill_array(Queries) ->
.

```

### Racket:

```
(define/contract (ways-to-fill-array queries)
  (-> (listof (listof exact-integer?)) (listof exact-integer?))
)
```

## Solutions

### C++ Solution:

```
/*
 * Problem: Count Ways to Make Array With Product
 * Difficulty: Hard
 * Tags: array, dp, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
public:
    vector<int> waysToFillArray(vector<vector<int>>& queries) {

    }
};
```

### Java Solution:

```
/**
 * Problem: Count Ways to Make Array With Product
 * Difficulty: Hard
 * Tags: array, dp, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
    public int[] waysToFillArray(int[][] queries) {

    }
}
```



```
}
```

### Python3 Solution:

```
"""
Problem: Count Ways to Make Array With Product
Difficulty: Hard
Tags: array, dp, math

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) or O(n * m) for DP table
"""

class Solution:
    def waysToFillArray(self, queries: List[List[int]]) -> List[int]:
        # TODO: Implement optimized solution
        pass
```

### Python Solution:

```
class Solution(object):
    def waysToFillArray(self, queries):
        """
        :type queries: List[List[int]]
        :rtype: List[int]
        """
```

### JavaScript Solution:

```
/**
 * Problem: Count Ways to Make Array With Product
 * Difficulty: Hard
 * Tags: array, dp, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
```

```

* @param {number[][]} queries
* @return {number[]}
*/
var waysToFillArray = function(queries) {

};

```

### TypeScript Solution:

```

/**
 * Problem: Count Ways to Make Array With Product
 * Difficulty: Hard
 * Tags: array, dp, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

function waysToFillArray(queries: number[][]): number[] {

};

```

### C# Solution:

```

/*
 * Problem: Count Ways to Make Array With Product
 * Difficulty: Hard
 * Tags: array, dp, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

public class Solution {
    public int[] WaysToFillArray(int[][] queries) {

    }
}

```

## C Solution:

```
/*
 * Problem: Count Ways to Make Array With Product
 * Difficulty: Hard
 * Tags: array, dp, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) or O(n * m) for DP table
 */

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* waysToFillArray(int** queries, int queriesSize, int* queriesColSize,
int* returnSize) {

}
```

## Go Solution:

```
// Problem: Count Ways to Make Array With Product
// Difficulty: Hard
// Tags: array, dp, math
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) or O(n * m) for DP table

func waysToFillArray(queries [][]int) []int {

}
```

## Kotlin Solution:

```
class Solution {
fun waysToFillArray(queries: Array<IntArray>): IntArray {

}

}
```

### Swift Solution:

```
class Solution {  
    func waysToFillArray(_ queries: [[Int]]) -> [Int] {  
  
    }  
}
```

### Rust Solution:

```
// Problem: Count Ways to Make Array With Product  
// Difficulty: Hard  
// Tags: array, dp, math  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(n) or O(n * m) for DP table  
  
impl Solution {  
    pub fn ways_to_fill_array(queries: Vec<Vec<i32>>) -> Vec<i32> {  
  
    }  
}
```

### Ruby Solution:

```
# @param {Integer[][]} queries  
# @return {Integer[]}  
def ways_to_fill_array(queries)  
  
end
```

### PHP Solution:

```
class Solution {  
  
    /**  
     * @param Integer[][] $queries  
     * @return Integer[]  
     */  
    function waysToFillArray($queries) {
```

```
}  
}
```

### Dart Solution:

```
class Solution {  
  List<int> waysToFillArray(List<List<int>> queries) {  
  
  }  
}
```

### Scala Solution:

```
object Solution {  
  def waysToFillArray(queries: Array[Array[Int]]): Array[Int] = {  
  
  }  
}
```

### Elixir Solution:

```
defmodule Solution do  
  @spec ways_to_fill_array(queries :: [[integer]]) :: [integer]  
  def ways_to_fill_array(queries) do  
  
  end  
end
```

### Erlang Solution:

```
-spec ways_to_fill_array(Queries :: [[integer()]]) -> [integer()].  
ways_to_fill_array(Queries) ->  
.
```

### Racket Solution:

```
(define/contract (ways-to-fill-array queries)  
  (-> (listof (listof exact-integer?)) (listof exact-integer?))  
)
```