

Problem 1469: Find All The Lonely Nodes

Problem Information

Difficulty: Easy

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

In a binary tree, a

lonely

node is a node that is the only child of its parent node. The root of the tree is not lonely because it does not have a parent node.

Given the

root

of a binary tree, return


an array containing the values of all lonely nodes

in the tree. Return the list

in any order

.

Example 1:



Input:

root = [1,2,3,null,4]


Output:

[4]

Explanation:

Light blue node is the only lonely node. Node 1 is the root and is not lonely. Nodes 2 and 3 have the same parent and are not lonely.

Example 2:



Input:

root = [7,1,4,6,null,5,3,null,null,null,null,2]


Output:

[6,2]

Explanation:

Light blue nodes are lonely nodes. Please remember that order doesn't matter, [2,6] is also an acceptable answer.

Example 3:



Input:

```
root = [11,99,88,77,null,null,66,55,null,null,44,33,null,null,22]
```

Output:

```
[77,55,33,66,44,22]
```

Explanation:

Nodes 99 and 88 share the same parent. Node 11 is the root. All other nodes are lonely.

Constraints:

The number of nodes in the

tree

is in the range

[1, 1000].

$1 \leq \text{Node.val} \leq 10$

Code Snippets

C++:

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *   int val;
 *   TreeNode *left;
 *   TreeNode *right;
 *   TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *   TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *   TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
right(right) {}
 * };
 */
class Solution {
public:
    vector<int> getLonelyNodes(TreeNode* root) {

    }
};
```

Java:

```
/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *   int val;
 *   TreeNode left;
 *   TreeNode right;
 *   TreeNode() {}
 *   TreeNode(int val) { this.val = val; }
 *   TreeNode(int val, TreeNode left, TreeNode right) {
 *     this.val = val;
 *     this.left = left;
 *     this.right = right;
 *   }
 * }
 */
class Solution {
    public List<Integer> getLonelyNodes(TreeNode root) {
```

```
}  
}
```

Python3:

```
# Definition for a binary tree node.  
# class TreeNode:  
#     def __init__(self, val=0, left=None, right=None):  
#         self.val = val  
#         self.left = left  
#         self.right = right  
class Solution:  
    def getLonelyNodes(self, root: Optional[TreeNode]) -> List[int]:
```

Python:

```
# Definition for a binary tree node.  
# class TreeNode(object):  
#     def __init__(self, val=0, left=None, right=None):  
#         self.val = val  
#         self.left = left  
#         self.right = right  
class Solution(object):  
    def getLonelyNodes(self, root):  
        """  
        :type root: Optional[TreeNode]  
        :rtype: List[int]  
        """
```

JavaScript:

```
/**  
 * Definition for a binary tree node.  
 * function TreeNode(val, left, right) {  
 *     this.val = (val===undefined ? 0 : val)  
 *     this.left = (left===undefined ? null : left)  
 *     this.right = (right===undefined ? null : right)  
 * }  
 */  
/**  
 * @param {TreeNode} root  
 * @return {number[]}
```

```

*/
var getLonelyNodes = function(root) {

};

```

TypeScript:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   val: number
 *   left: TreeNode | null
 *   right: TreeNode | null
 *   constructor(val?: number, left?: TreeNode | null, right?: TreeNode | null)
 *   {
 *     this.val = (val===undefined ? 0 : val)
 *     this.left = (left===undefined ? null : left)
 *     this.right = (right===undefined ? null : right)
 *   }
 * }
 */

function getLonelyNodes(root: TreeNode | null): number[] {

};

```

C#:

```

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *   public int val;
 *   public TreeNode left;
 *   public TreeNode right;
 *   public TreeNode(int val=0, TreeNode left=null, TreeNode right=null) {
 *     this.val = val;
 *     this.left = left;
 *     this.right = right;
 *   }
 * }
 */

public class Solution {

```

```

public IList<int> GetLonelyNodes(TreeNode root) {

}

}

```

C:

```

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */
/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* getLonelyNodes(struct TreeNode* root, int* returnSize) {

}

```

Go:

```

/**
 * Definition for a binary tree node.
 * type TreeNode struct {
 *     Val int
 *     Left *TreeNode
 *     Right *TreeNode
 * }
 */
func getLonelyNodes(root *TreeNode) []int {

}

```

Kotlin:

```

/**
 * Example:
 * var ti = TreeNode(5)
 * var v = ti.`val`

```



```

* Definition for a binary tree node.
* class TreeNode(var `val`: Int) {
*   var left: TreeNode? = null
*   var right: TreeNode? = null
* }
*/
class Solution {
fun getLonelyNodes(root: TreeNode?): List<Int> {

}
}

```

Swift:

```

/**
* Definition for a binary tree node.
* public class TreeNode {
*   public var val: Int
*   public var left: TreeNode?
*   public var right: TreeNode?
*   public init() { self.val = 0; self.left = nil; self.right = nil; }
*   public init(_ val: Int) { self.val = val; self.left = nil; self.right =
nil; }
*   public init(_ val: Int, _ left: TreeNode?, _ right: TreeNode?) {
*     self.val = val
*     self.left = left
*     self.right = right
*   }
* }
*/
class Solution {
func getLonelyNodes(_ root: TreeNode?) -> [Int] {

}
}

```

Rust:

```

// Definition for a binary tree node.
// #[derive(Debug, PartialEq, Eq)]
// pub struct TreeNode {
//   pub val: i32,

```

```

// pub left: Option<Rc<RefCell<TreeNode>>>,
// pub right: Option<Rc<RefCell<TreeNode>>>,
// }
//
// impl TreeNode {
// #[inline]
// pub fn new(val: i32) -> Self {
//   TreeNode {
//     val,
//     left: None,
//     right: None
//   }
// }
// }
// }

use std::rc::Rc;
use std::cell::RefCell;
impl Solution {
pub fn get_lonely_nodes(root: Option<Rc<RefCell<TreeNode>>>) -> Vec<i32> {

}

}

```

Ruby:

```

# Definition for a binary tree node.
# class TreeNode
#   attr_accessor :val, :left, :right
#   def initialize(val = 0, left = nil, right = nil)
#     @val = val
#     @left = left
#     @right = right
#   end
# end

# @param {TreeNode} root
# @return {Integer[]}
def get_lonely_nodes(root)

end

```

PHP:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 * public $val = null;
 * public $left = null;
 * public $right = null;
 * function __construct($val = 0, $left = null, $right = null) {
 * $this->val = $val;
 * $this->left = $left;
 * $this->right = $right;
 * }
 * }
 */
class Solution {

/**
 * @param TreeNode $root
 * @return Integer[]
 */
function getLonelyNodes($root) {

}

}

```

Dart:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 * int val;
 * TreeNode? left;
 * TreeNode? right;
 * TreeNode([this.val = 0, this.left, this.right]);
 * }
 */
class Solution {
List<int> getLonelyNodes(TreeNode? root) {

}

}

```

Scala:

```

/**
 * Definition for a binary tree node.
 * class TreeNode(_value: Int = 0, _left: TreeNode = null, _right: TreeNode =
null) {
 *   var value: Int = _value
 *   var left: TreeNode = _left
 *   var right: TreeNode = _right
 * }
 */
object Solution {
  def getLonelyNodes(root: TreeNode): List[Int] = {

  }
}

```

Elixir:

```

# Definition for a binary tree node.
#
# defmodule TreeNode do
#   @type t :: %__MODULE__{
#     val: integer,
#     left: TreeNode.t() | nil,
#     right: TreeNode.t() | nil
#   }
#   defstruct val: 0, left: nil, right: nil
# end

defmodule Solution do
  @spec get_lonely_nodes(root :: TreeNode.t | nil) :: [integer]
  def get_lonely_nodes(root) do

  end

end

```

Erlang:

```

%% Definition for a binary tree node.
%%
%% -record(tree_node, {val = 0 :: integer(),
%% left = null :: 'null' | #tree_node{},
%% right = null :: 'null' | #tree_node{}}).

```

```
-spec get_lonely_nodes(Root :: #tree_node{} | null) -> [integer()].
get_lonely_nodes(Root) ->
.
```

Racket:

```
; Definition for a binary tree node.
#|

; val : integer?
; left : (or/c tree-node? #f)
; right : (or/c tree-node? #f)
(struct tree-node
  (val left right) #:mutable #:transparent)

; constructor
(define (make-tree-node [val 0])
  (tree-node val #f #f))

|#

(define/contract (get-lonely-nodes root)
  (-> (or/c tree-node? #f) (listof exact-integer?))
  )
```

Solutions

C++ Solution:

```
/*
 * Problem: Find All The Lonely Nodes
 * Difficulty: Easy
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
```

```

* Definition for a binary tree node.
* struct TreeNode {
*   int val;
*   TreeNode *left;
*   TreeNode *right;
*   TreeNode() : val(0), left(nullptr), right(nullptr) {}
*   TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
*   TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left),
right(right) {}
* };
*/
class Solution {
public:
vector<int> getLonelyNodes(TreeNode* root) {

}
};

```

Java Solution:

```

/**
 * Problem: Find All The Lonely Nodes
 * Difficulty: Easy
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *   int val;
 *   TreeNode left;
 *   TreeNode right;
 *   TreeNode() {}
 *   TreeNode(int val) { this.val = val; }
 *   TreeNode(int val, TreeNode left, TreeNode right) {
 *     this.val = val;
 *     this.left = left;

```

```

* this.right = right;
* }
* }
*/
class Solution {
public List<Integer> getLonelyNodes(TreeNode root) {

}
}

```

Python3 Solution:

```

"""
Problem: Find All The Lonely Nodes
Difficulty: Easy
Tags: array, tree, search

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(h) for recursion stack where h is height
"""

# Definition for a binary tree node.
# class TreeNode:
# def __init__(self, val=0, left=None, right=None):
# self.val = val
# self.left = left
# self.right = right
class Solution:
def getLonelyNodes(self, root: Optional[TreeNode]) -> List[int]:
# TODO: Implement optimized solution
pass

```

Python Solution:

```

# Definition for a binary tree node.
# class TreeNode(object):
# def __init__(self, val=0, left=None, right=None):
# self.val = val
# self.left = left
# self.right = right

```

```

class Solution(object):
def getLonelyNodes(self, root):
    """
    :type root: Optional[TreeNode]
    :rtype: List[int]
    """

```

JavaScript Solution:

```

/**
 * Problem: Find All The Lonely Nodes
 * Difficulty: Easy
 * Tags: array, tree, search
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

/**
 * Definition for a binary tree node.
 * function TreeNode(val, left, right) {
 *   this.val = (val===undefined ? 0 : val)
 *   this.left = (left===undefined ? null : left)
 *   this.right = (right===undefined ? null : right)
 * }
 */

/**
 * @param {TreeNode} root
 * @return {number[]}
 */
var getLonelyNodes = function(root) {

};

```

TypeScript Solution:

```

/**
 * Problem: Find All The Lonely Nodes
 * Difficulty: Easy
 * Tags: array, tree, search

```



```

*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(h) for recursion stack where h is height
*/

/**
* Definition for a binary tree node.
* class TreeNode {
*   val: number
*   left: TreeNode | null
*   right: TreeNode | null
*   constructor(val?: number, left?: TreeNode | null, right?: TreeNode | null)
*   {
*     this.val = (val===undefined ? 0 : val)
*     this.left = (left===undefined ? null : left)
*     this.right = (right===undefined ? null : right)
*   }
* }
*/

function getLonelyNodes(root: TreeNode | null): number[] {

};

```

C# Solution:

```

/*
* Problem: Find All The Lonely Nodes
* Difficulty: Easy
* Tags: array, tree, search
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(h) for recursion stack where h is height
*/

/**
* Definition for a binary tree node.
* public class TreeNode {
*   public int val;

```

```

* public TreeNode left;
* public TreeNode right;
* public TreeNode(int val=0, TreeNode left=null, TreeNode right=null) {
* this.val = val;
* this.left = left;
* this.right = right;
* }
* }
*/

public class Solution {
public IList<int> GetLonelyNodes(TreeNode root) {

}

}

```

C Solution:

```

/*
* Problem: Find All The Lonely Nodes
* Difficulty: Easy
* Tags: array, tree, search
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(h) for recursion stack where h is height
*/

/**
* Definition for a binary tree node.
* struct TreeNode {
* int val;
* struct TreeNode *left;
* struct TreeNode *right;
* };
*/

/**
* Note: The returned array must be malloced, assume caller calls free().
*/
int* getLonelyNodes(struct TreeNode* root, int* returnSize) {

}

```

Go Solution:

```
// Problem: Find All The Lonely Nodes
// Difficulty: Easy
// Tags: array, tree, search
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

/**
 * Definition for a binary tree node.
 * type TreeNode struct {
 *     Val int
 *     Left *TreeNode
 *     Right *TreeNode
 * }
 */
func getLonelyNodes(root *TreeNode) []int {

}
```

Kotlin Solution:

```
/**
 * Example:
 * var ti = TreeNode(5)
 * var v = ti.`val`
 * Definition for a binary tree node.
 * class TreeNode(var `val`: Int) {
 *     var left: TreeNode? = null
 *     var right: TreeNode? = null
 * }
 */
class Solution {
fun getLonelyNodes(root: TreeNode?): List<Int> {

}

}
```

Swift Solution:

```

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 * public var val: Int
 * public var left: TreeNode?
 * public var right: TreeNode?
 * public init() { self.val = 0; self.left = nil; self.right = nil; }
 * public init(_ val: Int) { self.val = val; self.left = nil; self.right =
nil; }
 * public init(_ val: Int, _ left: TreeNode?, _ right: TreeNode?) {
 * self.val = val
 * self.left = left
 * self.right = right
 * }
 * }
 */
class Solution {
func getLonelyNodes(_ root: TreeNode?) -> [Int] {

}

}

```

Rust Solution:

```

// Problem: Find All The Lonely Nodes
// Difficulty: Easy
// Tags: array, tree, search
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

// Definition for a binary tree node.
// #[derive(Debug, PartialEq, Eq)]
// pub struct TreeNode {
// pub val: i32,
// pub left: Option<Rc<RefCell<TreeNode>>>,
// pub right: Option<Rc<RefCell<TreeNode>>>,
// }
//
// impl TreeNode {
// #[inline]

```

```

// pub fn new(val: i32) -> Self {
//   TreeNode {
//     val,
//     left: None,
//     right: None
//   }
// }
// }
// }

use std::rc::Rc;
use std::cell::RefCell;
impl Solution {
pub fn get_lonely_nodes(root: Option<Rc<RefCell<TreeNode>>>) -> Vec<i32> {

}
}

```

Ruby Solution:

```

# Definition for a binary tree node.
# class TreeNode
#   attr_accessor :val, :left, :right
#   def initialize(val = 0, left = nil, right = nil)
#     @val = val
#     @left = left
#     @right = right
#   end
# end

# @param {TreeNode} root
# @return {Integer[]}
def get_lonely_nodes(root)

end

```

PHP Solution:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   public $val = null;
 *   public $left = null;
 *   public $right = null;

```

```

* function __construct($val = 0, $left = null, $right = null) {
* $this->val = $val;
* $this->left = $left;
* $this->right = $right;
* }
* }
*/
class Solution {

/**
 * @param TreeNode $root
 * @return Integer[]
 */
function getLonelyNodes($root) {

}

}

```

Dart Solution:

```

/**
 * Definition for a binary tree node.
 * class TreeNode {
 *   int val;
 *   TreeNode? left;
 *   TreeNode? right;
 *   TreeNode([this.val = 0, this.left, this.right]);
 * }
 */
class Solution {
  List<int> getLonelyNodes(TreeNode? root) {

  }

}

```

Scala Solution:

```

/**
 * Definition for a binary tree node.
 * class TreeNode(_value: Int = 0, _left: TreeNode = null, _right: TreeNode =
 * null) {

```

```

* var value: Int = _value
* var left: TreeNode = _left
* var right: TreeNode = _right
* }
*/
object Solution {
def getLonelyNodes(root: TreeNode): List[Int] = {

}
}

```

Elixir Solution:

```

# Definition for a binary tree node.
#
# defmodule TreeNode do
#   @type t :: %__MODULE__{
#     val: integer,
#     left: TreeNode.t() | nil,
#     right: TreeNode.t() | nil
#   }
#   defstruct val: 0, left: nil, right: nil
# end

defmodule Solution do
  @spec get_lonely_nodes(root :: TreeNode.t() | nil) :: [integer]
  def get_lonely_nodes(root) do

  end
end

```

Erlang Solution:

```

%% Definition for a binary tree node.
%%
%% -record(tree_node, {val = 0 :: integer(),
%%   left = null :: 'null' | #tree_node{},
%%   right = null :: 'null' | #tree_node{}}).

-spec get_lonely_nodes(Root :: #tree_node{} | null) -> [integer()].
get_lonely_nodes(Root) ->

```

.

Racket Solution:

```
; Definition for a binary tree node.
#|

; val : integer?
; left : (or/c tree-node? #f)
; right : (or/c tree-node? #f)
(struct tree-node
  (val left right) #:mutable #:transparent)

; constructor
(define (make-tree-node [val 0])
  (tree-node val #f #f))

|#

(define/contract (get-lonely-nodes root)
  (-> (or/c tree-node? #f) (listof exact-integer?))
  )
```