

Problem 2457: Minimum Addition to Make Integer Beautiful

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given two positive integers

n

and

$target$

.

An integer is considered

beautiful

if the sum of its digits is less than or equal to

$target$

.

Return the

minimum

non-negative

integer

x

such that

$n + x$

is beautiful

. The input will be generated such that it is always possible to make

n

beautiful.

Example 1:

Input:

$n = 16$, target = 6

Output:

4

Explanation:

Initially n is 16 and its digit sum is $1 + 6 = 7$. After adding 4, n becomes 20 and digit sum becomes $2 + 0 = 2$. It can be shown that we can not make n beautiful with adding non-negative integer less than 4.

Example 2:

Input:

$n = 467$, target = 6

Output:

33

Explanation:

Initially n is 467 and its digit sum is $4 + 6 + 7 = 17$. After adding 33, n becomes 500 and digit sum becomes $5 + 0 + 0 = 5$. It can be shown that we can not make n beautiful with adding non-negative integer less than 33.

Example 3:

Input:

$n = 1$, target = 1

Output:

0

Explanation:

Initially n is 1 and its digit sum is 1, which is already smaller than or equal to target.

Constraints:

$1 \leq n \leq 10$

12

$1 \leq \text{target} \leq 150$

The input will be generated such that it is always possible to make

n

beautiful.

Code Snippets

C++:

```
class Solution {
public:
    long long makeIntegerBeautiful(long long n, int target) {

    }
};
```

Java:

```
class Solution {
    public long makeIntegerBeautiful(long n, int target) {

    }
}
```

Python3:

```
class Solution:
    def makeIntegerBeautiful(self, n: int, target: int) -> int:
```

Python:

```
class Solution(object):
    def makeIntegerBeautiful(self, n, target):
        """
        :type n: int
        :type target: int
        :rtype: int
        """
```

JavaScript:

```
/**
 * @param {number} n
 * @param {number} target
 * @return {number}
 */
var makeIntegerBeautiful = function(n, target) {

};
```

TypeScript:

```
function makeIntegerBeautiful(n: number, target: number): number {  
  
};
```

C#:

```
public class Solution {  
    public long MakeIntegerBeautiful(long n, int target) {  
  
    }  
}
```

C:

```
long long makeIntegerBeautiful(long long n, int target) {  
  
}
```

Go:

```
func makeIntegerBeautiful(n int64, target int) int64 {  
  
}
```

Kotlin:

```
class Solution {  
    fun makeIntegerBeautiful(n: Long, target: Int): Long {  
  
    }  
}
```

Swift:

```
class Solution {  
    func makeIntegerBeautiful(_ n: Int, _ target: Int) -> Int {  
  
    }  
}
```

Rust:

```

impl Solution {
  pub fn make_integer_beautiful(n: i64, target: i32) -> i64 {

  }
}

```

Ruby:

```

# @param {Integer} n
# @param {Integer} target
# @return {Integer}
def make_integer_beautiful(n, target)

end

```

PHP:

```

class Solution {

    /**
     * @param Integer $n
     * @param Integer $target
     * @return Integer
     */
    function makeIntegerBeautiful($n, $target) {

    }

}

```

Dart:

```

class Solution {
  int makeIntegerBeautiful(int n, int target) {

  }
}

```

Scala:

```

object Solution {
  def makeIntegerBeautiful(n: Long, target: Int): Long = {

  }
}

```

```
}
```

Elixir:

```
defmodule Solution do
  @spec make_integer_beautiful(n :: integer, target :: integer) :: integer
  def make_integer_beautiful(n, target) do

  end
end
```

Erlang:

```
-spec make_integer_beautiful(N :: integer(), Target :: integer()) ->
integer().
make_integer_beautiful(N, Target) ->
.
```

Racket:

```
(define/contract (make-integer-beautiful n target)
  (-> exact-integer? exact-integer? exact-integer?)
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Minimum Addition to Make Integer Beautiful
 * Difficulty: Medium
 * Tags: greedy, math
 *
 * Approach: Greedy algorithm with local optimal choices
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
```

```

long long makeIntegerBeautiful(long long n, int target) {

}

};

```

Java Solution:

```

/**
 * Problem: Minimum Addition to Make Integer Beautiful
 * Difficulty: Medium
 * Tags: greedy, math
 *
 * Approach: Greedy algorithm with local optimal choices
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public long makeIntegerBeautiful(long n, int target) {

    }
}

```

Python3 Solution:

```

"""
Problem: Minimum Addition to Make Integer Beautiful
Difficulty: Medium
Tags: greedy, math

Approach: Greedy algorithm with local optimal choices
Time Complexity: O(n) to O(n^2) depending on approach
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def makeIntegerBeautiful(self, n: int, target: int) -> int:
        # TODO: Implement optimized solution
        pass

```

Python Solution:


```

class Solution(object):
    def makeIntegerBeautiful(self, n, target):
        """
        :type n: int
        :type target: int
        :rtype: int
        """

```

JavaScript Solution:

```

/**
 * Problem: Minimum Addition to Make Integer Beautiful
 * Difficulty: Medium
 * Tags: greedy, math
 *
 * Approach: Greedy algorithm with local optimal choices
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number} n
 * @param {number} target
 * @return {number}
 */
var makeIntegerBeautiful = function(n, target) {

};

```

TypeScript Solution:

```

/**
 * Problem: Minimum Addition to Make Integer Beautiful
 * Difficulty: Medium
 * Tags: greedy, math
 *
 * Approach: Greedy algorithm with local optimal choices
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

function makeIntegerBeautiful(n: number, target: number): number {

```

```
};
```

C# Solution:

```
/*
 * Problem: Minimum Addition to Make Integer Beautiful
 * Difficulty: Medium
 * Tags: greedy, math
 *
 * Approach: Greedy algorithm with local optimal choices
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public long MakeIntegerBeautiful(long n, int target) {

    }
}
```

C Solution:

```
/*
 * Problem: Minimum Addition to Make Integer Beautiful
 * Difficulty: Medium
 * Tags: greedy, math
 *
 * Approach: Greedy algorithm with local optimal choices
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

long long makeIntegerBeautiful(long long n, int target) {

}
```

Go Solution:

```
// Problem: Minimum Addition to Make Integer Beautiful
// Difficulty: Medium
```

```

// Tags: greedy, math
//
// Approach: Greedy algorithm with local optimal choices
// Time Complexity: O(n) to O(n^2) depending on approach
// Space Complexity: O(1) to O(n) depending on approach

func makeIntegerBeautiful(n int64, target int) int64 {

}

```

Kotlin Solution:

```

class Solution {
    fun makeIntegerBeautiful(n: Long, target: Int): Long {

    }
}

```

Swift Solution:

```

class Solution {
    func makeIntegerBeautiful(_ n: Int, _ target: Int) -> Int {

    }
}

```

Rust Solution:

```

// Problem: Minimum Addition to Make Integer Beautiful
// Difficulty: Medium
// Tags: greedy, math
//
// Approach: Greedy algorithm with local optimal choices
// Time Complexity: O(n) to O(n^2) depending on approach
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn make_integer_beautiful(n: i64, target: i32) -> i64 {

    }
}

```

Ruby Solution:

```
# @param {Integer} n
# @param {Integer} target
# @return {Integer}
def make_integer_beautiful(n, target)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer $n
     * @param Integer $target
     * @return Integer
     */
    function makeIntegerBeautiful($n, $target) {

    }

}
```

Dart Solution:

```
class Solution {
  int makeIntegerBeautiful(int n, int target) {

  }
}
```

Scala Solution:

```
object Solution {
  def makeIntegerBeautiful(n: Long, target: Int): Long = {

  }
}
```

Elixir Solution:

```
defmodule Solution do
  @spec make_integer_beautiful(n :: integer, target :: integer) :: integer
  def make_integer_beautiful(n, target) do

  end
end
```

Erlang Solution:

```
-spec make_integer_beautiful(N :: integer(), Target :: integer()) ->
integer().
make_integer_beautiful(N, Target) ->
.
```

Racket Solution:

```
(define/contract (make-integer-beautiful n target)
  (-> exact-integer? exact-integer? exact-integer?)
)
```