

Problem 3007: Maximum Number That Sum of the Prices Is Less Than or Equal to K

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given an integer

k

and an integer

x

. The price of a number

num

is calculated by the count of

set bits

at positions

x

,

$2x$

,

3x

, etc., in its binary representation, starting from the least significant bit. The following table contains examples of how price is calculated.

x

num

Binary Representation

Price

1

13

0

0

0

0

0

1

1

0

1

3

2

13

0

0

0

0

0

1

1

0

1

1

2

233

0

1

1

1

0

1

0

0

1

3

3

13

0

00

0

01

1

01

1

3

362

1

01

1

01

0

10

2

The

accumulated price

of

num

is the

total

price of numbers from

1

to

num

.

num

is considered

cheap

if its accumulated price is less than or equal to

k

.

Return the

greatest

cheap number.

Example 1:

Input:

$k = 9, x = 1$

Output:

6

Explanation:

As shown in the table below,

6

is the greatest cheap number.

x

num

Binary Representation

Price

Accumulated Price

1

1

0

0

1

1

1

1

2

0

1

0

1

2

1

3

0

1

1

2

4

1

4

1

0

0

1

5

1

5

1

0

1

2

7

1

6

1

1

0

2

9

1

7

1

1

1

3

12

Example 2:

Input:

$k = 7, x = 2$

Output:

9

Explanation:

As shown in the table below,

9

is the greatest cheap number.

x

num

Binary Representation

Price

Accumulated Price

2

1

0

0

0

1

0

0

2

2

0

0

1

0

1

1

2

3

0

0

1

1

1

2

2

4

0

1

0

0

0

2

2

5

0

1

0

1

0

2

2

6

0

1

1

0

1

3

2

7

0

1

1

1

1

4

2

8

1

0

0

0

1

5

2

9

1

0

0

1

1

6

2

10

1

0

1

0

2

8

Constraints:

$1 \leq k \leq 10$

15

$1 \leq x \leq 8$

Code Snippets

C++:

```
class Solution {  
public:  
    long long findMaximumNumber(long long k, int x) {  
  
    }  
};
```

Java:

```
class Solution {  
    public long findMaximumNumber(long k, int x) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def findMaximumNumber(self, k: int, x: int) -> int:
```

Python:

```
class Solution(object):  
    def findMaximumNumber(self, k, x):  
        """  
        :type k: int  
        :type x: int  
        :rtype: int  
        """
```

JavaScript:

```
/**  
 * @param {number} k  
 * @param {number} x  
 * @return {number}  
 */  
var findMaximumNumber = function(k, x) {  
  
};
```

TypeScript:

```
function findMaximumNumber(k: number, x: number): number {  
  
};
```

C#:

```
public class Solution {  
    public long FindMaximumNumber(long k, int x) {  
  
    }  
}
```

C:

```
long long findMaximumNumber(long long k, int x) {  
  
}
```

Go:

```
func findMaximumNumber(k int64, x int) int64 {

}
```

Kotlin:

```
class Solution {
    fun findMaximumNumber(k: Long, x: Int): Long {

    }
}
```

Swift:

```
class Solution {
    func findMaximumNumber(_ k: Int, _ x: Int) -> Int {

    }
}
```

Rust:

```
impl Solution {
    pub fn find_maximum_number(k: i64, x: i32) -> i64 {

    }
}
```

Ruby:

```
# @param {Integer} k
# @param {Integer} x
# @return {Integer}
def find_maximum_number(k, x)

end
```

PHP:

```
class Solution {

    /**
     * @param Integer $k
```

```

* @param Integer $x
* @return Integer
*/
function findMaximumNumber($k, $x) {

}
}

```

Dart:

```

class Solution {
  int findMaximumNumber(int k, int x) {

  }
}

```

Scala:

```

object Solution {
  def findMaximumNumber(k: Long, x: Int): Long = {

  }
}

```

Elixir:

```

defmodule Solution do
  @spec find_maximum_number(k :: integer, x :: integer) :: integer
  def find_maximum_number(k, x) do

  end
end

```

Erlang:

```

-spec find_maximum_number(K :: integer(), X :: integer()) -> integer().
find_maximum_number(K, X) ->
.

```

Racket:

```
(define/contract (find-maximum-number k x)
  (-> exact-integer? exact-integer? exact-integer?)
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Maximum Number That Sum of the Prices Is Less Than or Equal to K
 * Difficulty: Medium
 * Tags: dp, math, search, heap
 *
 * Approach: Dynamic programming with memoization or tabulation
 * Time Complexity: O(n * m) where n and m are problem dimensions
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
public:
    long long findMaximumNumber(long long k, int x) {

    }
};
```

Java Solution:

```
/**
 * Problem: Maximum Number That Sum of the Prices Is Less Than or Equal to K
 * Difficulty: Medium
 * Tags: dp, math, search, heap
 *
 * Approach: Dynamic programming with memoization or tabulation
 * Time Complexity: O(n * m) where n and m are problem dimensions
 * Space Complexity: O(n) or O(n * m) for DP table
 */

class Solution {
    public long findMaximumNumber(long k, int x) {

    }
}
```

```
}
```

Python3 Solution:

```
"""
Problem: Maximum Number That Sum of the Prices Is Less Than or Equal to K
Difficulty: Medium
Tags: dp, math, search, heap

Approach: Dynamic programming with memoization or tabulation
Time Complexity: O(n * m) where n and m are problem dimensions
Space Complexity: O(n) or O(n * m) for DP table
"""

class Solution:
    def findMaximumNumber(self, k: int, x: int) -> int:
        # TODO: Implement optimized solution
        pass
```

Python Solution:

```
class Solution(object):
    def findMaximumNumber(self, k, x):
        """
        :type k: int
        :type x: int
        :rtype: int
        """
```

JavaScript Solution:

```
/**
 * Problem: Maximum Number That Sum of the Prices Is Less Than or Equal to K
 * Difficulty: Medium
 * Tags: dp, math, search, heap
 *
 * Approach: Dynamic programming with memoization or tabulation
 * Time Complexity: O(n * m) where n and m are problem dimensions
 * Space Complexity: O(n) or O(n * m) for DP table
 */
```

```

/**
 * @param {number} k
 * @param {number} x
 * @return {number}
 */
var findMaximumNumber = function(k, x) {

};

```

TypeScript Solution:

```

/**
 * Problem: Maximum Number That Sum of the Prices Is Less Than or Equal to K
 * Difficulty: Medium
 * Tags: dp, math, search, heap
 *
 * Approach: Dynamic programming with memoization or tabulation
 * Time Complexity: O(n * m) where n and m are problem dimensions
 * Space Complexity: O(n) or O(n * m) for DP table
 */

function findMaximumNumber(k: number, x: number): number {

};

```

C# Solution:

```

/*
 * Problem: Maximum Number That Sum of the Prices Is Less Than or Equal to K
 * Difficulty: Medium
 * Tags: dp, math, search, heap
 *
 * Approach: Dynamic programming with memoization or tabulation
 * Time Complexity: O(n * m) where n and m are problem dimensions
 * Space Complexity: O(n) or O(n * m) for DP table
 */

public class Solution {
    public long FindMaximumNumber(long k, int x) {

    }
}

```

```
}
```

C Solution:

```
/*
 * Problem: Maximum Number That Sum of the Prices Is Less Than or Equal to K
 * Difficulty: Medium
 * Tags: dp, math, search, heap
 *
 * Approach: Dynamic programming with memoization or tabulation
 * Time Complexity: O(n * m) where n and m are problem dimensions
 * Space Complexity: O(n) or O(n * m) for DP table
 */

long long findMaximumNumber(long long k, int x) {

}
```

Go Solution:

```
// Problem: Maximum Number That Sum of the Prices Is Less Than or Equal to K
// Difficulty: Medium
// Tags: dp, math, search, heap
//
// Approach: Dynamic programming with memoization or tabulation
// Time Complexity: O(n * m) where n and m are problem dimensions
// Space Complexity: O(n) or O(n * m) for DP table

func findMaximumNumber(k int64, x int) int64 {

}
```

Kotlin Solution:

```
class Solution {
    fun findMaximumNumber(k: Long, x: Int): Long {

    }
}
```

Swift Solution:

```

class Solution {
    func findMaximumNumber(_ k: Int, _ x: Int) -> Int {

    }
}

```

Rust Solution:

```

// Problem: Maximum Number That Sum of the Prices Is Less Than or Equal to K
// Difficulty: Medium
// Tags: dp, math, search, heap
//
// Approach: Dynamic programming with memoization or tabulation
// Time Complexity: O(n * m) where n and m are problem dimensions
// Space Complexity: O(n) or O(n * m) for DP table

impl Solution {
    pub fn find_maximum_number(k: i64, x: i32) -> i64 {

    }
}

```

Ruby Solution:

```

# @param {Integer} k
# @param {Integer} x
# @return {Integer}
def find_maximum_number(k, x)

end

```

PHP Solution:

```

class Solution {

    /**
     * @param Integer $k
     * @param Integer $x
     * @return Integer
     */
    function findMaximumNumber($k, $x) {

```

```
}  
}
```

Dart Solution:

```
class Solution {  
  int findMaximumNumber(int k, int x) {  
  
  }  
}
```

Scala Solution:

```
object Solution {  
  def findMaximumNumber(k: Long, x: Int): Long = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec find_maximum_number(k :: integer, x :: integer) :: integer  
  def find_maximum_number(k, x) do  
  
  end  
end
```

Erlang Solution:

```
-spec find_maximum_number(K :: integer(), X :: integer()) -> integer().  
find_maximum_number(K, X) ->  
.
```

Racket Solution:

```
(define/contract (find-maximum-number k x)  
  (-> exact-integer? exact-integer? exact-integer?)  
)
```