

Problem 2464: Minimum Subarrays in a Valid Split

Problem Information

Difficulty: **Medium**

Acceptance Rate: 64.86%

Paid Only: Yes

Tags: Array, Math, Dynamic Programming, Number Theory

Problem Description

You are given an integer array `nums``.

Splitting of an integer array `nums`` into **subarrays** is **valid** if:

- * the `_greatest common divisor_` of the first and last elements of each subarray is **greater** than `1``, and
- * each element of `nums`` belongs to exactly one subarray.

Return `_the minimum` number of subarrays in a **valid** subarray splitting of `nums``. If a valid subarray splitting is not possible, return `-1``.

Note that:

- * The **greatest common divisor** of two numbers is the largest positive integer that evenly divides both numbers.
- * A **subarray** is a contiguous non-empty part of an array.

Example 1:

Input: `nums = [2,6,3,4,3]` **Output:** `2` **Explanation:** We can create a valid split in the following way: `[2,6] | [3,4,3]`. - The starting element of the 1st subarray is 2 and the ending is 6. Their greatest common divisor is 2, which is greater than 1. - The starting element of the 2nd subarray is 3 and the ending is 3. Their greatest common divisor is 3, which is greater than 1. It can be proved that 2 is the minimum number of subarrays that we can obtain in a valid split.

Example 2:

****Input:**** nums = [3,5] ****Output:**** 2 ****Explanation:**** We can create a valid split in the following way: [3] | [5]. - The starting element of the 1st subarray is 3 and the ending is 3. Their greatest common divisor is 3, which is greater than 1. - The starting element of the 2nd subarray is 5 and the ending is 5. Their greatest common divisor is 5, which is greater than 1. It can be proved that 2 is the minimum number of subarrays that we can obtain in a valid split.

****Example 3:****

****Input:**** nums = [1,2,1] ****Output:**** -1 ****Explanation:**** It is impossible to create valid split.

****Constraints:****

`*`1 <= nums.length <= 1000` *`1 <= nums[i] <= 105``

Code Snippets

C++:

```
class Solution {
public:
    int validSubarraySplit(vector<int>& nums) {

    }
};
```

Java:

```
class Solution {
    public int validSubarraySplit(int[] nums) {

    }
}
```

Python3:

```
class Solution:
    def validSubarraySplit(self, nums: List[int]) -> int:
```