

Problem 75: Sort Colors

Problem Information

Difficulty: Medium

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given an array

nums

with

n

objects colored red, white, or blue, sort them

in-place

so that objects of the same color are adjacent, with the colors in the order red, white, and blue.

We will use the integers

0

,

1

, and

2

to represent the color red, white, and blue, respectively.

You must solve this problem without using the library's sort function.

Example 1:

Input:

nums = [2,0,2,1,1,0]

Output:

[0,0,1,1,2,2]

Example 2:

Input:

nums = [2,0,1]

Output:

[0,1,2]

Constraints:

$n == \text{nums.length}$

$1 \leq n \leq 300$

$\text{nums}[i]$

is either

0

,

1

, or

2

.

Follow up:

Could you come up with a one-pass algorithm using only constant extra space?

Code Snippets

C++:

```
class Solution {  
public:  
    void sortColors(vector<int>& nums) {  
  
    }  
};
```

Java:

```
class Solution {  
    public void sortColors(int[] nums) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def sortColors(self, nums: List[int]) -> None:  
        """  
        Do not return anything, modify nums in-place instead.  
        """
```

Python:

```

class Solution(object):
def sortColors(self, nums):
    """
    :type nums: List[int]
    :rtype: None Do not return anything, modify nums in-place instead.
    """

```

JavaScript:

```

/**
 * @param {number[]} nums
 * @return {void} Do not return anything, modify nums in-place instead.
 */
var sortColors = function(nums) {

};

```

TypeScript:

```

/**
Do not return anything, modify nums in-place instead.
 */
function sortColors(nums: number[]): void {

};

```

C#:

```

public class Solution {
    public void SortColors(int[] nums) {

    }
}

```

C:

```

void sortColors(int* nums, int numsSize) {

}

```

Go:

```
func sortColors(nums []int) {  
  
}
```

Kotlin:

```
class Solution {  
    fun sortColors(nums: IntArray): Unit {  
  
    }  
}
```

Swift:

```
class Solution {  
    func sortColors(_ nums: inout [Int]) {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn sort_colors(nums: &mut Vec<i32>) {  
  
    }  
}
```

Ruby:

```
# @param {Integer[]} nums  
# @return {Void} Do not return anything, modify nums in-place instead.  
def sort_colors(nums)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param Integer[] $nums  
     * @return NULL  
     */  
}
```

```

*/
function sortColors(&$nums) {

}

}

```

Dart:

```

class Solution {
void sortColors(List<int> nums) {

}

}

```

Scala:

```

object Solution {
def sortColors(nums: Array[Int]): Unit = {

}

}

```

Solutions

C++ Solution:

```

/*
* Problem: Sort Colors
* Difficulty: Medium
* Tags: array, sort
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

class Solution {
public:
void sortColors(vector<int>& nums) {

```

```
}  
};
```

Java Solution:

```
/**  
 * Problem: Sort Colors  
 * Difficulty: Medium  
 * Tags: array, sort  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity:  $O(n)$  or  $O(n \log n)$   
 * Space Complexity:  $O(1)$  to  $O(n)$  depending on approach  
 */  
  
class Solution {  
    public void sortColors(int[] nums) {  
  
    }  
}
```

Python3 Solution:

```
"""  
Problem: Sort Colors  
Difficulty: Medium  
Tags: array, sort  
  
Approach: Use two pointers or sliding window technique  
Time Complexity:  $O(n)$  or  $O(n \log n)$   
Space Complexity:  $O(1)$  to  $O(n)$  depending on approach  
"""  
  
class Solution:  
    def sortColors(self, nums: List[int]) -> None:  
        # TODO: Implement optimized solution  
        pass
```

Python Solution:

```

class Solution(object):
def sortColors(self, nums):
    """
    :type nums: List[int]
    :rtype: None Do not return anything, modify nums in-place instead.
    """

```

JavaScript Solution:

```

/**
 * Problem: Sort Colors
 * Difficulty: Medium
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number[]} nums
 * @return {void} Do not return anything, modify nums in-place instead.
 */
var sortColors = function(nums) {

};

```

TypeScript Solution:

```

/**
 * Problem: Sort Colors
 * Difficulty: Medium
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
Do not return anything, modify nums in-place instead.
 */

```



```
function sortColors(nums: number[]): void {  
  
};
```

C# Solution:

```
/*  
 * Problem: Sort Colors  
 * Difficulty: Medium  
 * Tags: array, sort  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(1) to O(n) depending on approach  
 */  
  
public class Solution {  
    public void SortColors(int[] nums) {  
  
    }  
}
```

C Solution:

```
/*  
 * Problem: Sort Colors  
 * Difficulty: Medium  
 * Tags: array, sort  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(1) to O(n) depending on approach  
 */  
  
void sortColors(int* nums, int numsSize) {  
  
}
```

Go Solution:

```
// Problem: Sort Colors
// Difficulty: Medium
// Tags: array, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func sortColors(nums []int) {

}
```

Kotlin Solution:

```
class Solution {
    fun sortColors(nums: IntArray): Unit {

    }
}
```

Swift Solution:

```
class Solution {
    func sortColors(_ nums: inout [Int]) {

    }
}
```

Rust Solution:

```
// Problem: Sort Colors
// Difficulty: Medium
// Tags: array, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn sort_colors(nums: &mut Vec<i32>) {

    }
}
```

```
}
```

Ruby Solution:

```
# @param {Integer[]} nums
# @return {Void} Do not return anything, modify nums in-place instead.
def sort_colors(nums)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer[] $nums
     * @return NULL
     */
    function sortColors(&$nums) {

    }

}
```

Dart Solution:

```
class Solution {
    void sortColors(List<int> nums) {

    }

}
```

Scala Solution:

```
object Solution {
    def sortColors(nums: Array[Int]): Unit = {

    }

}
```