

Problem 382: Linked List Random Node

Problem Information

Difficulty: Medium

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given a singly linked list, return a random node's value from the linked list. Each node must have the

same probability

of being chosen.

Implement the

Solution

class:

Solution(ListNode head)

Initializes the object with the head of the singly-linked list


head

.

int getRandom()

Chooses a node randomly from the list and returns its value. All the nodes of the list should be equally likely to be chosen.

Example 1:



Input

["Solution", "getRandom", "getRandom", "getRandom", "getRandom", "getRandom"] [[[1, 2, 3]], [], [], [], [], [], []]

Output

[null, 1, 3, 2, 2, 3]

Explanation

Solution solution = new Solution([1, 2, 3]); solution.getRandom(); // return 1
solution.getRandom(); // return 3 solution.getRandom(); // return 2 solution.getRandom(); //
return 2 solution.getRandom(); // return 3 // getRandom() should return either 1, 2, or 3
randomly. Each element should have equal probability of returning.

Constraints:

The number of nodes in the linked list will be in the range

[1, 10

4

]

.

-10

4

<= Node.val <= 10

4

At most

10

4

calls will be made to

getRandom

.

Follow up:

What if the linked list is extremely large and its length is unknown to you?

Could you solve this efficiently without using extra space?

Code Snippets

C++:

```
/**
 * Definition for singly-linked list.
 * struct ListNode {
 *   int val;
 *   ListNode *next;
 *   ListNode() : val(0), next(nullptr) {}
 *   ListNode(int x) : val(x), next(nullptr) {}
 *   ListNode(int x, ListNode *next) : val(x), next(next) {}
 * };
 */
class Solution {
public:
    Solution(ListNode* head) {

    }
```

```

int getRandom() {

}

};

/**
 * Your Solution object will be instantiated and called as such:
 * Solution* obj = new Solution(head);
 * int param_1 = obj->getRandom();
 */

```

Java:

```

/**
 * Definition for singly-linked list.
 * public class ListNode {
 *   int val;
 *   ListNode next;
 *   ListNode() {}
 *   ListNode(int val) { this.val = val; }
 *   ListNode(int val, ListNode next) { this.val = val; this.next = next; }
 * }
 */
class Solution {

    public Solution(ListNode head) {

    }

    public int getRandom() {

    }

}

/**
 * Your Solution object will be instantiated and called as such:
 * Solution obj = new Solution(head);
 * int param_1 = obj.getRandom();
 */

```

Python3:

```
# Definition for singly-linked list.
# class ListNode:
#     def __init__(self, val=0, next=None):
#         self.val = val
#         self.next = next
class Solution:

    def __init__(self, head: Optional[ListNode]):

    def getRandom(self) -> int:

# Your Solution object will be instantiated and called as such:
# obj = Solution(head)
# param_1 = obj.getRandom()
```

Python:

```
# Definition for singly-linked list.
# class ListNode(object):
#     def __init__(self, val=0, next=None):
#         self.val = val
#         self.next = next
class Solution(object):

    def __init__(self, head):
        """
        :type head: Optional[ListNode]
        """

    def getRandom(self):
        """
        :rtype: int
        """

# Your Solution object will be instantiated and called as such:
```

```
# obj = Solution(head)
# param_1 = obj.getRandom()
```

JavaScript:

```
/**
 * Definition for singly-linked list.
 * function ListNode(val, next) {
 *   this.val = (val===undefined ? 0 : val)
 *   this.next = (next===undefined ? null : next)
 * }
 */
/**
 * @param {ListNode} head
 */
var Solution = function(head) {

};

/**
 * @return {number}
 */
Solution.prototype.getRandom = function() {

};

/**
 * Your Solution object will be instantiated and called as such:
 * var obj = new Solution(head)
 * var param_1 = obj.getRandom()
 */
```

TypeScript:

```
/**
 * Definition for singly-linked list.
 * class ListNode {
 *   val: number
 *   next: ListNode | null
 *   constructor(val?: number, next?: ListNode | null) {
 *     this.val = (val===undefined ? 0 : val)
 *     this.next = (next===undefined ? null : next)
 *   }
 * }
```

```

* }
* }
*/

class Solution {
  constructor(head: ListNode | null) {

  }

  getRandom(): number {

  }
}

/**
 * Your Solution object will be instantiated and called as such:
 * var obj = new Solution(head)
 * var param_1 = obj.getRandom()
 */

```

C#:

```

/**
 * Definition for singly-linked list.
 * public class ListNode {
 *   public int val;
 *   public ListNode next;
 *   public ListNode(int val=0, ListNode next=null) {
 *     this.val = val;
 *     this.next = next;
 *   }
 * }
 */
public class Solution {

  public Solution(ListNode head) {

  }

  public int GetRandom() {

  }
}

```

```

}

/**
 * Your Solution object will be instantiated and called as such:
 * Solution obj = new Solution(head);
 * int param_1 = obj.GetRandom();
 */

```

C:

```

/**
 * Definition for singly-linked list.
 * struct ListNode {
 *   int val;
 *   struct ListNode *next;
 * };
 */

typedef struct {

} Solution;

Solution* solutionCreate(struct ListNode* head) {

}

int solutionGetRandom(Solution* obj) {

}

void solutionFree(Solution* obj) {

}

/**
 * Your Solution struct will be instantiated and called as such:
 * Solution* obj = solutionCreate(head);
 * int param_1 = solutionGetRandom(obj);
 */

```



```

* solutionFree(obj);
*/

```

Go:

```

/**
 * Definition for singly-linked list.
 * type ListNode struct {
 *     Val int
 *     Next *ListNode
 * }
 */
type Solution struct {

}

func Constructor(head *ListNode) Solution {

}

func (this *Solution) GetRandom() int {

}

/**
 * Your Solution object will be instantiated and called as such:
 * obj := Constructor(head);
 * param_1 := obj.GetRandom();
 */

```

Kotlin:

```

/**
 * Example:
 * var li = ListNode(5)
 * var v = li.`val`
 * Definition for singly-linked list.
 * class ListNode(var `val`: Int) {
 *     var next: ListNode? = null

```

```

* }
*/
class Solution(head: ListNode?) {

    fun getRandom(): Int {

    }

}

/**
 * Your Solution object will be instantiated and called as such:
 * var obj = Solution(head)
 * var param_1 = obj.getRandom()
 */

```

Swift:

```

/**
 * Definition for singly-linked list.
 * public class ListNode {
 *     public var val: Int
 *     public var next: ListNode?
 *     public init() { self.val = 0; self.next = nil; }
 *     public init(_ val: Int) { self.val = val; self.next = nil; }
 *     public init(_ val: Int, _ next: ListNode?) { self.val = val; self.next =
next; }
 * }
 */

class Solution {

    init(_ head: ListNode?) {

    }

    func getRandom() -> Int {

    }

}

/**

```

```

* Your Solution object will be instantiated and called as such:
* let obj = Solution(head)
* let ret_1: Int = obj.getRandom()
*/

```

Rust:

```

// Definition for singly-linked list.
// #[derive(PartialEq, Eq, Clone, Debug)]
// pub struct ListNode {
//     pub val: i32,
//     pub next: Option<Box<ListNode>>
// }
//
// impl ListNode {
//     #[inline]
//     fn new(val: i32) -> Self {
//         ListNode {
//             next: None,
//             val
//         }
//     }
// }
struct Solution {

}

/**
 * `&self` means the method takes an immutable reference.
 * If you need a mutable reference, change it to `&mut self` instead.
 */
impl Solution {

    fn new(head: Option<Box<ListNode>>) -> Self {

    }

    fn get_random(&self) -> i32 {

    }

}

```

```

/**
 * Your Solution object will be instantiated and called as such:
 * let obj = Solution::new(head);
 * let ret_1: i32 = obj.get_random();
 */

```

Ruby:

```

# Definition for singly-linked list.
# class ListNode
# attr_accessor :val, :next
# def initialize(val = 0, _next = nil)
# @val = val
# @next = _next
# end
# end

class Solution

  =begin
  :type head: ListNode
  =end
  def initialize(head)

  end

  =begin
  :rtype: Integer
  =end
  def get_random()

  end

end

# Your Solution object will be instantiated and called as such:
# obj = Solution.new(head)
# param_1 = obj.get_random()

```

PHP:

```
/**
 * Definition for a singly-linked list.
 * class ListNode {
 * public $val = 0;
 * public $next = null;
 * function __construct($val = 0, $next = null) {
 * $this->val = $val;
 * $this->next = $next;
 * }
 * }
 */
class Solution {
/**
 * @param ListNode $head
 */
function __construct($head) {

}

/**
 * @return Integer
 */
function getRandom() {

}
}

/**
 * Your Solution object will be instantiated and called as such:
 * $obj = Solution($head);
 * $ret_1 = $obj->getRandom();
 */
```

Dart:

```
/**
 * Definition for singly-linked list.
 * class ListNode {
 * int val;
 * ListNode? next;
 * ListNode([this.val = 0, this.next]);
 */
```

```

* }
*/
class Solution {

    Solution(ListNode? head) {

    }

    int getRandom() {

    }

}

/**
 * Your Solution object will be instantiated and called as such:
 * Solution obj = Solution(head);
 * int param1 = obj.getRandom();
 */

```

Scala:

```

/**
 * Definition for singly-linked list.
 * class ListNode(_x: Int = 0, _next: ListNode = null) {
 *   var next: ListNode = _next
 *   var x: Int = _x
 * }
 */
class Solution(_head: ListNode) {

    def getRandom(): Int = {

    }

}

/**
 * Your Solution object will be instantiated and called as such:
 * val obj = new Solution(head)
 * val param_1 = obj.getRandom()
 */

```

Elixir:

```
# Definition for singly-linked list.
#
# defmodule ListNode do
# @type t :: %__MODULE__{
#   val: integer,
#   next: ListNode.t() | nil
# }
# defstruct val: 0, next: nil
# end

defmodule Solution do
  @spec init_(head :: ListNode.t | nil) :: any
  def init_(head) do

  end

  @spec get_random() :: integer
  def get_random() do

  end
end

# Your functions will be called as such:
# Solution.init_(head)
# param_1 = Solution.get_random()

# Solution.init_ will be called before every test case, in which you can do
some necessary initializations.
```

Erlang:

```
%% Definition for singly-linked list.
%%
%% -record(list_node, {val = 0 :: integer(),
%%   next = null :: 'null' | #list_node{}}).

-spec solution_init_(Head :: #list_node{} | null) -> any().
solution_init_(Head) ->
.
.
```

```

-spec solution_get_random() -> integer().
solution_get_random() ->
.

%% Your functions will be called as such:
%% solution_init_(Head),
%% Param_1 = solution_get_random(),

%% solution_init_ will be called before every test case, in which you can do
some necessary initializations.

```

Racket:

```

; Definition for singly-linked list:
#|

; val : integer?
; next : (or/c list-node? #f)
(struct list-node
  (val next) #:mutable #:transparent)

; constructor
(define (make-list-node [val 0])
  (list-node val #f))

|#

(define solution%
  (class object%
    (super-new)

    ; head : (or/c list-node? #f)
    (init-field
      head)

    ; get-random : -> exact-integer?
    (define/public (get-random)
      )))

;; Your solution% object will be instantiated and called as such:
;; (define obj (new solution% [head head]))

```



```
:: (define param_1 (send obj get-random))
```

Solutions

C++ Solution:

```
/*
 * Problem: Linked List Random Node
 * Difficulty: Medium
 * Tags: math, linked_list
 *
 * Approach: Optimized algorithm based on problem constraints
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Definition for singly-linked list.
 * struct ListNode {
 *   int val;
 *   ListNode *next;
 *   ListNode() : val(0), next(nullptr) {
 * // TODO: Implement optimized solution
 * return 0;
 * }
 *   ListNode(int x) : val(x), next(nullptr) {
 * // TODO: Implement optimized solution
 * return 0;
 * }
 *   ListNode(int x, ListNode *next) : val(x), next(next) {
 * // TODO: Implement optimized solution
 * return 0;
 * }
 * };
 */
class Solution {
public:
    Solution(ListNode* head) {

    }
}
```

```

int getRandom() {

}

};

/**
 * Your Solution object will be instantiated and called as such:
 * Solution* obj = new Solution(head);
 * int param_1 = obj->getRandom();
 */

```

Java Solution:

```

/**
 * Problem: Linked List Random Node
 * Difficulty: Medium
 * Tags: math, linked_list
 *
 * Approach: Optimized algorithm based on problem constraints
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Definition for singly-linked list.
 * public class ListNode {
 *     int val;
 *     ListNode next;
 *     ListNode() {
 *         // TODO: Implement optimized solution
 *     }
 *     return 0;
 * }
 *
 * ListNode(int val) { this.val = val; }
 * ListNode(int val, ListNode next) { this.val = val; this.next = next; }
 */

class Solution {

    public Solution(ListNode head) {

```

```

}

public int getRandom() {

}

}

/**
 * Your Solution object will be instantiated and called as such:
 * Solution obj = new Solution(head);
 * int param_1 = obj.getRandom();
 */

```

Python3 Solution:

```

"""
Problem: Linked List Random Node
Difficulty: Medium
Tags: math, linked_list

Approach: Optimized algorithm based on problem constraints
Time Complexity: O(n) to O(n^2) depending on approach
Space Complexity: O(1) to O(n) depending on approach
"""

# Definition for singly-linked list.
# class ListNode:
#     def __init__(self, val=0, next=None):
#         self.val = val
#         self.next = next
class Solution:

    def __init__(self, head: Optional[ListNode]):

    def getRandom(self) -> int:
        # TODO: Implement optimized solution
        pass

```

Python Solution:

```

# Definition for singly-linked list.
# class ListNode(object):
#     def __init__(self, val=0, next=None):
#         self.val = val
#         self.next = next
class Solution(object):

    def __init__(self, head):
        """
        :type head: Optional[ListNode]
        """

    def getRandom(self):
        """
        :rtype: int
        """

# Your Solution object will be instantiated and called as such:
# obj = Solution(head)
# param_1 = obj.getRandom()

```

JavaScript Solution:

```

/**
 * Problem: Linked List Random Node
 * Difficulty: Medium
 * Tags: math, linked_list
 *
 * Approach: Optimized algorithm based on problem constraints
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Definition for singly-linked list.
 * function ListNode(val, next) {
 *   this.val = (val===undefined ? 0 : val)
 *   this.next = (next===undefined ? null : next)
 * }

```

```

*/
/**
 * @param {ListNode} head
 */
var Solution = function(head) {

};

/**
 * @return {number}
 */
Solution.prototype.getRandom = function() {

};

/**
 * Your Solution object will be instantiated and called as such:
 * var obj = new Solution(head)
 * var param_1 = obj.getRandom()
 */

```

TypeScript Solution:

```

/**
 * Problem: Linked List Random Node
 * Difficulty: Medium
 * Tags: math, linked_list
 *
 * Approach: Optimized algorithm based on problem constraints
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Definition for singly-linked list.
 * class ListNode {
 *   val: number
 *   next: ListNode | null
 *   constructor(val?: number, next?: ListNode | null) {
 *     this.val = (val===undefined ? 0 : val)
 *     this.next = (next===undefined ? null : next)
 *   }
 * }
 */

```

```

* }
* }
*/

class Solution {
  constructor(head: ListNode | null) {

  }

  getRandom(): number {

  }
}

/**
 * Your Solution object will be instantiated and called as such:
 * var obj = new Solution(head)
 * var param_1 = obj.getRandom()
 */

```

C# Solution:

```

/*
 * Problem: Linked List Random Node
 * Difficulty: Medium
 * Tags: math, linked_list
 *
 * Approach: Optimized algorithm based on problem constraints
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Definition for singly-linked list.
 * public class ListNode {
 *   public int val;
 *   public ListNode next;
 *   public ListNode(int val=0, ListNode next=null) {
 *     this.val = val;
 *     this.next = next;
 *   }
 */

```

```

* }
*/
public class Solution {

    public Solution(ListNode head) {

    }

    public int GetRandom() {

    }

}

/**
 * Your Solution object will be instantiated and called as such:
 * Solution obj = new Solution(head);
 * int param_1 = obj.GetRandom();
 */

```

C Solution:

```

/*
 * Problem: Linked List Random Node
 * Difficulty: Medium
 * Tags: math, linked_list
 *
 * Approach: Optimized algorithm based on problem constraints
 * Time Complexity: O(n) to O(n^2) depending on approach
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Definition for singly-linked list.
 * struct ListNode {
 *     int val;
 *     struct ListNode *next;
 * };
 */

```

```

typedef struct {

} Solution;

Solution* solutionCreate(struct ListNode* head) {

}

int solutionGetRandom(Solution* obj) {

}

void solutionFree(Solution* obj) {

}

/**
 * Your Solution struct will be instantiated and called as such:
 * Solution* obj = solutionCreate(head);
 * int param_1 = solutionGetRandom(obj);
 *
 * solutionFree(obj);
 */

```

Go Solution:

```

// Problem: Linked List Random Node
// Difficulty: Medium
// Tags: math, linked_list
//
// Approach: Optimized algorithm based on problem constraints
// Time Complexity: O(n) to O(n^2) depending on approach
// Space Complexity: O(1) to O(n) depending on approach

/**
 * Definition for singly-linked list.
 * type ListNode struct {
 *     Val int
 *     Next *ListNode
 * }
 */

```



```

*/
type Solution struct {

}

func Constructor(head *ListNode) Solution {

}

func (this *Solution) GetRandom() int {

}

/**
 * Your Solution object will be instantiated and called as such:
 * obj := Constructor(head);
 * param_1 := obj.GetRandom();
 */

```

Kotlin Solution:

```

/**
 * Example:
 * var li = ListNode(5)
 * var v = li.`val`
 * Definition for singly-linked list.
 * class ListNode(var `val`: Int) {
 *   var next: ListNode? = null
 * }
 */
class Solution(head: ListNode?) {

    fun getRandom(): Int {

    }

}

```

```

/**
 * Your Solution object will be instantiated and called as such:
 * var obj = Solution(head)
 * var param_1 = obj.getRandom()
 */

```

Swift Solution:

```

/**
 * Definition for singly-linked list.
 * public class ListNode {
 *     public var val: Int
 *     public var next: ListNode?
 *     public init() { self.val = 0; self.next = nil; }
 *     public init(_ val: Int) { self.val = val; self.next = nil; }
 *     public init(_ val: Int, _ next: ListNode?) { self.val = val; self.next =
next; }
 * }
 */

class Solution {

    init(_ head: ListNode?) {

    }

    func getRandom() -> Int {

    }

}

/**
 * Your Solution object will be instantiated and called as such:
 * let obj = Solution(head)
 * let ret_1: Int = obj.getRandom()
 */

```

Rust Solution:

```

// Problem: Linked List Random Node
// Difficulty: Medium

```

```

// Tags: math, linked_list
//
// Approach: Optimized algorithm based on problem constraints
// Time Complexity:  $O(n)$  to  $O(n^2)$  depending on approach
// Space Complexity:  $O(1)$  to  $O(n)$  depending on approach

// Definition for singly-linked list.
// #[derive(PartialEq, Eq, Clone, Debug)]
// pub struct ListNode {
//     pub val: i32,
//     pub next: Option<Box<ListNode>>
// }
//
// impl ListNode {
//     #[inline]
//     fn new(val: i32) -> Self {
//         ListNode {
//             next: None,
//             val
//         }
//     }
// }

struct Solution {

}

/**
 * `&self` means the method takes an immutable reference.
 * If you need a mutable reference, change it to `&mut self` instead.
 */
impl Solution {

    fn new(head: Option<Box<ListNode>>) -> Self {

    }

    fn get_random(&self) -> i32 {

    }
}

```

```

/**
 * Your Solution object will be instantiated and called as such:
 * let obj = Solution::new(head);
 * let ret_1: i32 = obj.get_random();
 */

```

Ruby Solution:

```

# Definition for singly-linked list.
# class ListNode
# attr_accessor :val, :next
# def initialize(val = 0, _next = nil)
# @val = val
# @next = _next
# end
# end
class Solution

  =begin
  :type head: ListNode
  =end
  def initialize(head)

  end

  =begin
  :rtype: Integer
  =end
  def get_random()

  end

end

# Your Solution object will be instantiated and called as such:
# obj = Solution.new(head)
# param_1 = obj.get_random()

```

PHP Solution:

```

/**
 * Definition for a singly-linked list.
 * class ListNode {
 * public $val = 0;
 * public $next = null;
 * function __construct($val = 0, $next = null) {
 * $this->val = $val;
 * $this->next = $next;
 * }
 * }
 */
class Solution {
/**
 * @param ListNode $head
 */
function __construct($head) {

}

/**
 * @return Integer
 */
function getRandom() {

}
}

/**
 * Your Solution object will be instantiated and called as such:
 * $obj = Solution($head);
 * $ret_1 = $obj->getRandom();
 */

```

Dart Solution:

```

/**
 * Definition for singly-linked list.
 * class ListNode {
 * int val;
 * ListNode? next;
 * ListNode([this.val = 0, this.next]);
 * }

```

```

*/
class Solution {

    Solution(ListNode? head) {

    }

    int getRandom() {

    }
}

/**
 * Your Solution object will be instantiated and called as such:
 * Solution obj = Solution(head);
 * int param1 = obj.getRandom();
 */

```

Scala Solution:

```

/**
 * Definition for singly-linked list.
 * class ListNode(_x: Int = 0, _next: ListNode = null) {
 *   var next: ListNode = _next
 *   var x: Int = _x
 * }
 */
class Solution(_head: ListNode) {

    def getRandom(): Int = {

    }

}

/**
 * Your Solution object will be instantiated and called as such:
 * val obj = new Solution(head)
 * val param_1 = obj.getRandom()
 */

```

Elixir Solution:

```
# Definition for singly-linked list.
#
# defmodule ListNode do
#   @type t :: %__MODULE__{
#     val: integer,
#     next: ListNode.t() | nil
#   }
#   defstruct val: 0, next: nil
# end

defmodule Solution do
  @spec init_(head :: ListNode.t() | nil) :: any
  def init_(head) do

  end

  @spec get_random() :: integer
  def get_random() do

  end
end

# Your functions will be called as such:
# Solution.init_(head)
# param_1 = Solution.get_random()

# Solution.init_ will be called before every test case, in which you can do
# some necessary initializations.
```

Erlang Solution:

```
%% Definition for singly-linked list.
%%
%% -record(list_node, {val = 0 :: integer(),
%% next = null :: 'null' | #list_node{}}).

-spec solution_init_(Head :: #list_node{} | null) -> any().
solution_init_(Head) ->
.

-spec solution_get_random() -> integer().
```

```

solution_get_random() ->
.

%% Your functions will be called as such:
%% solution_init_(Head),
%% Param_1 = solution_get_random(),

%% solution_init_ will be called before every test case, in which you can do
some necessary initializations.

```

Racket Solution:

```

; Definition for singly-linked list:
#|

; val : integer?
; next : (or/c list-node? #f)
(struct list-node
  (val next) #:mutable #:transparent)

; constructor
(define (make-list-node [val 0])
  (list-node val #f))

|#

(define solution%
  (class object%
    (super-new)

    ; head : (or/c list-node? #f)
    (init-field
      head)

    ; get-random : -> exact-integer?
    (define/public (get-random)
      )))

;; Your solution% object will be instantiated and called as such:
;; (define obj (new solution% [head head]))

```



```
;; (define param_1 (send obj get-random))
```