

# Problem 2438: Range Product Queries of Powers

## Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

Given a positive integer

$n$

, there exists a

0-indexed

array called

powers

, composed of the

minimum

number of powers of

2

that sum to

$n$

. The array is sorted in

non-decreasing

order, and there is

only one

way to form the array.

You are also given a

0-indexed

2D integer array

queries

, where

`queries[i] = [left`

`i`

`, right`

`i`

`]`

. Each

`queries[i]`

represents a query where you have to find the product of all

`powers[j]`

with

left

i

$\leq j \leq \text{right}$

i

.

Return

an array

answers

, equal in length to

queries

, where

answers[i]

is the answer to the

i

th

query

. Since the answer to the

i

th

query may be too large, each

answers[i]

should be returned

modulo

10

9

+ 7

.

Example 1:

Input:

$n = 15$ , queries = [[0,1],[2,2],[0,3]]

Output:

[2,4,64]

Explanation:

For  $n = 15$ , powers = [1,2,4,8]. It can be shown that powers cannot be a smaller size. Answer to 1st query:  $\text{powers}[0] * \text{powers}[1] = 1 * 2 = 2$ . Answer to 2nd query:  $\text{powers}[2] = 4$ . Answer to 3rd query:  $\text{powers}[0] * \text{powers}[1] * \text{powers}[2] * \text{powers}[3] = 1 * 2 * 4 * 8 = 64$ . Each answer modulo 10

9

+ 7 yields the same answer, so [2,4,64] is returned.

Example 2:

Input:

`n = 2, queries = [[0,0]]`

Output:

`[2]`

Explanation:

For `n = 2`, `powers = [2]`. The answer to the only query is `powers[0] = 2`. The answer modulo 10

9

+ 7 is the same, so `[2]` is returned.

Constraints:

`1 <= n <= 10`

9

`1 <= queries.length <= 10`

5

`0 <= start`

`i`

`<= end`

`i`

`< powers.length`

## Code Snippets

**C++:**

```

class Solution {
public:
    vector<int> productQueries(int n, vector<vector<int>>& queries) {

    }
};

```

### Java:

```

class Solution {
    public int[] productQueries(int n, int[][] queries) {

    }
}

```

### Python3:

```

class Solution:
    def productQueries(self, n: int, queries: List[List[int]]) -> List[int]:

```

### Python:

```

class Solution(object):
    def productQueries(self, n, queries):
        """
        :type n: int
        :type queries: List[List[int]]
        :rtype: List[int]
        """

```

### JavaScript:

```

/**
 * @param {number} n
 * @param {number[][]} queries
 * @return {number[]}
 */
var productQueries = function(n, queries) {

};

```

### TypeScript:

```
function productQueries(n: number, queries: number[][]): number[] {

};
```

### C#:

```
public class Solution {
    public int[] ProductQueries(int n, int[][] queries) {

    }
}
```

### C:

```
/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* productQueries(int n, int** queries, int queriesSize, int*
queriesColSize, int* returnSize) {

}
```

### Go:

```
func productQueries(n int, queries [][]int) []int {

}
```

### Kotlin:

```
class Solution {
    fun productQueries(n: Int, queries: Array<IntArray>): IntArray {

    }
}
```

### Swift:

```
class Solution {
    func productQueries(_ n: Int, _ queries: [[Int]]) -> [Int] {

    }
}
```

### Rust:

```
impl Solution {  
    pub fn product_queries(n: i32, queries: Vec<Vec<i32>>) -> Vec<i32> {  
  
    }  
}
```

### Ruby:

```
# @param {Integer} n  
# @param {Integer[][]} queries  
# @return {Integer[]}  
def product_queries(n, queries)  
  
end
```

### PHP:

```
class Solution {  
  
    /**  
     * @param Integer $n  
     * @param Integer[][] $queries  
     * @return Integer[]  
     */  
    function productQueries($n, $queries) {  
  
    }  
}
```

### Dart:

```
class Solution {  
    List<int> productQueries(int n, List<List<int>> queries) {  
  
    }  
}
```

### Scala:

```
object Solution {  
    def productQueries(n: Int, queries: Array[Array[Int]]): Array[Int] = {  
  
    }  
}
```



```
}  
}
```

### Elixir:

```
defmodule Solution do  
  @spec product_queries(n :: integer, queries :: [[integer]]) :: [integer]  
  def product_queries(n, queries) do  
  
  end  
end
```

### Erlang:

```
-spec product_queries(N :: integer(), Queries :: [[integer()]]) ->  
[integer()].  
product_queries(N, Queries) ->  
.
```

### Racket:

```
(define/contract (product-queries n queries)  
  (-> exact-integer? (listof (listof exact-integer?)) (listof exact-integer?))  
)
```

## Solutions

### C++ Solution:

```
/*  
 * Problem: Range Product Queries of Powers  
 * Difficulty: Medium  
 * Tags: array, sort  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(1) to O(n) depending on approach  
 */
```

```

class Solution {
public:
    vector<int> productQueries(int n, vector<vector<int>>& queries) {

    }
};

```

### Java Solution:

```

/**
 * Problem: Range Product Queries of Powers
 * Difficulty: Medium
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public int[] productQueries(int n, int[][] queries) {

    }
}

```

### Python3 Solution:

```

"""
Problem: Range Product Queries of Powers
Difficulty: Medium
Tags: array, sort

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def productQueries(self, n: int, queries: List[List[int]]) -> List[int]:
        # TODO: Implement optimized solution
        pass

```

### Python Solution:

```
class Solution(object):
    def productQueries(self, n, queries):
        """
        :type n: int
        :type queries: List[List[int]]
        :rtype: List[int]
        """
```

### JavaScript Solution:

```
/**
 * Problem: Range Product Queries of Powers
 * Difficulty: Medium
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number} n
 * @param {number[][]} queries
 * @return {number[]}
 */
var productQueries = function(n, queries) {

};
```

### TypeScript Solution:

```
/**
 * Problem: Range Product Queries of Powers
 * Difficulty: Medium
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */
```

```
function productQueries(n: number, queries: number[][]): number[] {

};
```

## C# Solution:

```
/*
 * Problem: Range Product Queries of Powers
 * Difficulty: Medium
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public int[] ProductQueries(int n, int[][] queries) {

    }
}
```

## C Solution:

```
/*
 * Problem: Range Product Queries of Powers
 * Difficulty: Medium
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* productQueries(int n, int** queries, int queriesSize, int*
queriesColSize, int* returnSize) {
```

```
}
```

### Go Solution:

```
// Problem: Range Product Queries of Powers
// Difficulty: Medium
// Tags: array, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func productQueries(n int, queries [][]int) []int {

}
```

### Kotlin Solution:

```
class Solution {
    fun productQueries(n: Int, queries: Array<IntArray>): IntArray {

    }
}
```

### Swift Solution:

```
class Solution {
    func productQueries(_ n: Int, _ queries: [[Int]]) -> [Int] {

    }
}
```

### Rust Solution:

```
// Problem: Range Product Queries of Powers
// Difficulty: Medium
// Tags: array, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach
```

```

impl Solution {
  pub fn product_queries(n: i32, queries: Vec<Vec<i32>>) -> Vec<i32> {

  }
}

```

### Ruby Solution:

```

# @param {Integer} n
# @param {Integer[][]} queries
# @return {Integer[]}
def product_queries(n, queries)

end

```

### PHP Solution:

```

class Solution {

    /**
     * @param Integer $n
     * @param Integer[][] $queries
     * @return Integer[]
     */
    function productQueries($n, $queries) {

    }

}

```

### Dart Solution:

```

class Solution {
  List<int> productQueries(int n, List<List<int>> queries) {

  }
}

```

### Scala Solution:

```

object Solution {
  def productQueries(n: Int, queries: Array[Array[Int]]): Array[Int] = {

  }
}

```

### Elixir Solution:

```

defmodule Solution do
  @spec product_queries(n :: integer, queries :: [[integer]]) :: [integer]
  def product_queries(n, queries) do

  end
end

```

### Erlang Solution:

```

-spec product_queries(N :: integer(), Queries :: [[integer()]]) ->
[integer()].
product_queries(N, Queries) ->
.

```

### Racket Solution:

```

(define/contract (product-queries n queries)
  (-> exact-integer? (listof (listof exact-integer?)) (listof exact-integer?))
  )

```