

Problem 447: Number of Boomerangs

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given

n

points

in the plane that are all

distinct

, where

$\text{points}[i] = [x$

i

, y

i

$]$

. A

boomerang

is a tuple of points

(i, j, k)

such that the distance between

i

and

j

equals the distance between

i

and

k

(the order of the tuple matters)

.

Return

the number of boomerangs

.

Example 1:

Input:

`points = [[0,0],[1,0],[2,0]]`

Output:

2

Explanation:

The two boomerangs are $[[1,0],[0,0],[2,0]]$ and $[[1,0],[2,0],[0,0]]$.

Example 2:

Input:

`points = [[1,1],[2,2],[3,3]]`

Output:

2

Example 3:

Input:

`points = [[1,1]]`

Output:

0

Constraints:

`n == points.length`

`1 <= n <= 500`

`points[i].length == 2`

-10

4

`<= x`

i

, y

i

<= 10

4

All the points are

unique

.

Code Snippets

C++:

```
class Solution {  
public:  
    int numberOfBoomerangs(vector<vector<int>>& points) {  
  
    }  
};
```

Java:

```
class Solution {  
    public int numberOfBoomerangs(int[][] points) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def numberOfBoomerangs(self, points: List[List[int]]) -> int:
```

Python:

```
class Solution(object):
    def numberOfBoomerangs(self, points):
        """
        :type points: List[List[int]]
        :rtype: int
        """
```

JavaScript:

```
/**
 * @param {number[][]} points
 * @return {number}
 */
var numberOfBoomerangs = function(points) {

};
```

TypeScript:

```
function numberOfBoomerangs(points: number[][]): number {

};
```

C#:

```
public class Solution {
    public int NumberOfBoomerangs(int[][] points) {

    }
}
```

C:

```
int numberOfBoomerangs(int** points, int pointsSize, int* pointsColSize) {

}
```

Go:

```
func numberOfBoomerangs(points [][]int) int {
```

```
}
```

Kotlin:

```
class Solution {  
    fun numberOfBoomerangs(points: Array<IntArray>): Int {  
  
    }  
}
```

Swift:

```
class Solution {  
    func numberOfBoomerangs(_ points: [[Int]]) -> Int {  
  
    }  
}
```

Rust:

```
impl Solution {  
    pub fn number_of_boomerangs(points: Vec<Vec<i32>>) -> i32 {  
  
    }  
}
```

Ruby:

```
# @param {Integer[][]} points  
# @return {Integer}  
def number_of_boomerangs(points)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param Integer[][] $points  
     * @return Integer  
     */  
}
```

```
function numberOfBoomerangs($points) {

}

}
```

Dart:

```
class Solution {
  int numberOfBoomerangs(List<List<int>> points) {

  }
}
```

Scala:

```
object Solution {
  def numberOfBoomerangs(points: Array[Array[Int]]): Int = {

  }
}
```

Elixir:

```
defmodule Solution do
  @spec number_of_boomerangs(points :: [[integer]]) :: integer
  def number_of_boomerangs(points) do

  end
end
```

Erlang:

```
-spec number_of_boomerangs(Points :: [[integer()]]) -> integer().
number_of_boomerangs(Points) ->
.
```

Racket:

```
(define/contract (number-of-boomerangs points)
  (-> (listof (listof exact-integer?)) exact-integer?)
)
```

Solutions

C++ Solution:

```
/*
 * Problem: Number of Boomerangs
 * Difficulty: Medium
 * Tags: array, math, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
public:
    int numberOfBoomerangs(vector<vector<int>>& points) {

    }
};
```

Java Solution:

```
/**
 * Problem: Number of Boomerangs
 * Difficulty: Medium
 * Tags: array, math, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

class Solution {
    public int numberOfBoomerangs(int[][] points) {

    }
}
```

Python3 Solution:


```

"""
Problem: Number of Boomerangs
Difficulty: Medium
Tags: array, math, hash

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(n) for hash map
"""

class Solution:
    def numberOfBoomerangs(self, points: List[List[int]]) -> int:
        # TODO: Implement optimized solution
        pass

```

Python Solution:

```

class Solution(object):
    def numberOfBoomerangs(self, points):
        """
        :type points: List[List[int]]
        :rtype: int
        """

```

JavaScript Solution:

```

/**
 * Problem: Number of Boomerangs
 * Difficulty: Medium
 * Tags: array, math, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

/**
 * @param {number[][]} points
 * @return {number}
 */
var numberOfBoomerangs = function(points) {

```

```
};
```

TypeScript Solution:

```
/**
 * Problem: Number of Boomerangs
 * Difficulty: Medium
 * Tags: array, math, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

function numberOfBoomerangs(points: number[][]): number {

};
```

C# Solution:

```
/*
 * Problem: Number of Boomerangs
 * Difficulty: Medium
 * Tags: array, math, hash
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(n) for hash map
 */

public class Solution {
    public int NumberOfBoomerangs(int[][] points) {

    }
}
```

C Solution:

```
/*
 * Problem: Number of Boomerangs
 * Difficulty: Medium
```

```

* Tags: array, math, hash
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(n) for hash map
*/

int numberOfBoomerangs(int** points, int pointsSize, int* pointsColSize) {

}

```

Go Solution:

```

// Problem: Number of Boomerangs
// Difficulty: Medium
// Tags: array, math, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

func numberOfBoomerangs(points [][]int) int {

}

```

Kotlin Solution:

```

class Solution {
    fun numberOfBoomerangs(points: Array<IntArray>): Int {

    }
}

```

Swift Solution:

```

class Solution {
    func numberOfBoomerangs(_ points: [[Int]]) -> Int {

    }
}

```

Rust Solution:

```
// Problem: Number of Boomerangs
// Difficulty: Medium
// Tags: array, math, hash
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(n) for hash map

impl Solution {
    pub fn number_of_boomerangs(points: Vec<Vec<i32>>)> -> i32 {

    }
}
```

Ruby Solution:

```
# @param {Integer[][]} points
# @return {Integer}
def number_of_boomerangs(points)

end
```

PHP Solution:

```
class Solution {

    /**
     * @param Integer[][] $points
     * @return Integer
     */
    function numberOfBoomerangs($points) {

    }

}
```

Dart Solution:

```
class Solution {
    int numberOfBoomerangs(List<List<int>> points) {
```

```
}  
}
```

Scala Solution:

```
object Solution {  
  def numberOfBoomerangs(points: Array[Array[Int]]): Int = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec number_of_boomerangs(points :: [[integer]]) :: integer  
  def number_of_boomerangs(points) do  
  
  end  
end
```

Erlang Solution:

```
-spec number_of_boomerangs(Points :: [[integer()]]) -> integer().  
number_of_boomerangs(Points) ->  
.
```

Racket Solution:

```
(define/contract (number-of-boomerangs points)  
  (-> (listof (listof exact-integer?)) exact-integer?)  
)
```