

Problem 3405: Count the Number of Arrays with K Matching Adjacent Elements

Problem Information

Difficulty: **Hard**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given three integers

n

,

m

,

k

. A

good array

arr

of size

n

is defined as follows:

Each element in

arr

is in the

inclusive

range

[1, m]

.

Exactly

k

indices

i

(where

$1 \leq i < n$

) satisfy the condition

$arr[i - 1] == arr[i]$

.

Return the number of

good arrays

that can be formed.

Since the answer may be very large, return it

modulo

10

9

+ 7

.

Example 1:

Input:

$n = 3, m = 2, k = 1$

Output:

4

Explanation:

There are 4 good arrays. They are

[1, 1, 2]

,

[1, 2, 2]

,

[2, 1, 1]

and

[2, 2, 1]

.

Hence, the answer is 4.

Example 2:

Input:

$n = 4, m = 2, k = 2$

Output:

6

Explanation:

The good arrays are

[1, 1, 1, 2]

,

[1, 1, 2, 2]

,

[1, 2, 2, 2]

,

[2, 1, 1, 1]

,

[2, 2, 1, 1]

and

[2, 2, 2, 1]

.

Hence, the answer is 6.

Example 3:

Input:

$n = 5, m = 2, k = 0$

Output:

2

Explanation:

The good arrays are

[1, 2, 1, 2, 1]

and

[2, 1, 2, 1, 2]

. Hence, the answer is 2.

Constraints:

$1 \leq n \leq 10$

5

$1 \leq m \leq 10$

5

$0 \leq k \leq n - 1$

Code Snippets

C++:

```
class Solution {
public:
    int countGoodArrays(int n, int m, int k) {

    }
};
```

Java:

```
class Solution {
    public int countGoodArrays(int n, int m, int k) {

    }
}
```

Python3:

```
class Solution:
    def countGoodArrays(self, n: int, m: int, k: int) -> int:
```

Python:

```
class Solution(object):
    def countGoodArrays(self, n, m, k):
        """
        :type n: int
        :type m: int
        :type k: int
        :rtype: int
        """
```

JavaScript:

```
/**
 * @param {number} n
 * @param {number} m
 * @param {number} k
 * @return {number}
 */
```

```
var countGoodArrays = function(n, m, k) {  
  
};
```

TypeScript:

```
function countGoodArrays(n: number, m: number, k: number): number {  
  
};
```

C#:

```
public class Solution {  
    public int CountGoodArrays(int n, int m, int k) {  
  
    }  
}
```

C:

```
int countGoodArrays(int n, int m, int k) {  
  
}
```

Go:

```
func countGoodArrays(n int, m int, k int) int {  
  
}
```

Kotlin:

```
class Solution {  
    fun countGoodArrays(n: Int, m: Int, k: Int): Int {  
  
    }  
}
```

Swift:

```
class Solution {  
    func countGoodArrays(_ n: Int, _ m: Int, _ k: Int) -> Int {
```

```
}  
}
```

Rust:

```
impl Solution {  
    pub fn count_good_arrays(n: i32, m: i32, k: i32) -> i32 {  
  
    }  
}
```

Ruby:

```
# @param {Integer} n  
# @param {Integer} m  
# @param {Integer} k  
# @return {Integer}  
def count_good_arrays(n, m, k)  
  
end
```

PHP:

```
class Solution {  
  
    /**  
     * @param Integer $n  
     * @param Integer $m  
     * @param Integer $k  
     * @return Integer  
     */  
    function countGoodArrays($n, $m, $k) {  
  
    }  
}
```

Dart:

```
class Solution {  
    int countGoodArrays(int n, int m, int k) {
```



```
}  
}
```

Scala:

```
object Solution {  
  def countGoodArrays(n: Int, m: Int, k: Int): Int = {  
  
  }  
}
```

Elixir:

```
defmodule Solution do  
  @spec count_good_arrays(n :: integer, m :: integer, k :: integer) :: integer  
  def count_good_arrays(n, m, k) do  
  
  end  
end
```

Erlang:

```
-spec count_good_arrays(N :: integer(), M :: integer(), K :: integer()) ->  
integer().  
count_good_arrays(N, M, K) ->  
.
```

Racket:

```
(define/contract (count-good-arrays n m k)  
  (-> exact-integer? exact-integer? exact-integer? exact-integer?)  
  )
```

Solutions

C++ Solution:

```
/*  
 * Problem: Count the Number of Arrays with K Matching Adjacent Elements  
 * Difficulty: Hard
```

```

* Tags: array, math
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

class Solution {
public:
    int countGoodArrays(int n, int m, int k) {

    }
};

```

Java Solution:

```

/**
 * Problem: Count the Number of Arrays with K Matching Adjacent Elements
 * Difficulty: Hard
 * Tags: array, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public int countGoodArrays(int n, int m, int k) {

    }
}

```

Python3 Solution:

```

"""
Problem: Count the Number of Arrays with K Matching Adjacent Elements
Difficulty: Hard
Tags: array, math

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)

```

```

Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def countGoodArrays(self, n: int, m: int, k: int) -> int:
        # TODO: Implement optimized solution
        pass

```

Python Solution:

```

class Solution(object):
    def countGoodArrays(self, n, m, k):
        """
        :type n: int
        :type m: int
        :type k: int
        :rtype: int
        """

```

JavaScript Solution:

```

/**
 * Problem: Count the Number of Arrays with K Matching Adjacent Elements
 * Difficulty: Hard
 * Tags: array, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number} n
 * @param {number} m
 * @param {number} k
 * @return {number}
 */
var countGoodArrays = function(n, m, k) {

};

```

TypeScript Solution:

```
/**
 * Problem: Count the Number of Arrays with K Matching Adjacent Elements
 * Difficulty: Hard
 * Tags: array, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function countGoodArrays(n: number, m: number, k: number): number {

};
```

C# Solution:

```
/*
 * Problem: Count the Number of Arrays with K Matching Adjacent Elements
 * Difficulty: Hard
 * Tags: array, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public int CountGoodArrays(int n, int m, int k) {

    }
}
```

C Solution:

```
/*
 * Problem: Count the Number of Arrays with K Matching Adjacent Elements
 * Difficulty: Hard
 * Tags: array, math
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
```

```

* Space Complexity: O(1) to O(n) depending on approach
*/

int countGoodArrays(int n, int m, int k) {

}

```

Go Solution:

```

// Problem: Count the Number of Arrays with K Matching Adjacent Elements
// Difficulty: Hard
// Tags: array, math
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func countGoodArrays(n int, m int, k int) int {

}

```

Kotlin Solution:

```

class Solution {
    fun countGoodArrays(n: Int, m: Int, k: Int): Int {

    }
}

```

Swift Solution:

```

class Solution {
    func countGoodArrays(_ n: Int, _ m: Int, _ k: Int) -> Int {

    }
}

```

Rust Solution:

```

// Problem: Count the Number of Arrays with K Matching Adjacent Elements
// Difficulty: Hard

```

```
// Tags: array, math
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
  pub fn count_good_arrays(n: i32, m: i32, k: i32) -> i32 {

  }
}
```

Ruby Solution:

```
# @param {Integer} n
# @param {Integer} m
# @param {Integer} k
# @return {Integer}
def count_good_arrays(n, m, k)

end
```

PHP Solution:

```
class Solution {

  /**
   * @param Integer $n
   * @param Integer $m
   * @param Integer $k
   * @return Integer
   */
  function countGoodArrays($n, $m, $k) {

  }
}
```

Dart Solution:

```
class Solution {
  int countGoodArrays(int n, int m, int k) {
```

```
}  
}
```

Scala Solution:

```
object Solution {  
  def countGoodArrays(n: Int, m: Int, k: Int): Int = {  
  
  }  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec count_good_arrays(n :: integer, m :: integer, k :: integer) :: integer  
  def count_good_arrays(n, m, k) do  
  
  end  
end
```

Erlang Solution:

```
-spec count_good_arrays(N :: integer(), M :: integer(), K :: integer()) ->  
integer().  
count_good_arrays(N, M, K) ->  
.
```

Racket Solution:

```
(define/contract (count-good-arrays n m k)  
  (-> exact-integer? exact-integer? exact-integer? exact-integer?)  
  )
```