

Problem 1600: Throne Inheritance

Problem Information

Difficulty: Medium

Acceptance Rate: 66.50%

Paid Only: No

Tags: Hash Table, Tree, Depth-First Search, Design

Problem Description

A kingdom consists of a king, his children, his grandchildren, and so on. Every once in a while, someone in the family dies or a child is born.

The kingdom has a well-defined order of inheritance that consists of the king as the first member. Let's define the recursive function `Successor(x, curOrder)`, which given a person `x` and the inheritance order so far, returns who should be the next person after `x` in the order of inheritance.

`Successor(x, curOrder)`: if `x` has no children or all of `x`'s children are in `curOrder`: if `x` is the king return null else return `Successor(x's parent, curOrder)` else return `x`'s oldest child who's not in `curOrder`

For example, assume we have a kingdom that consists of the king, his children Alice and Bob (Alice is older than Bob), and finally Alice's son Jack.

1. In the beginning, `curOrder` will be `["king"]`. 2. Calling `Successor(king, curOrder)` will return Alice, so we append to `curOrder` to get `["king", "Alice"]`. 3. Calling `Successor(Alice, curOrder)` will return Jack, so we append to `curOrder` to get `["king", "Alice", "Jack"]`. 4. Calling `Successor(Jack, curOrder)` will return Bob, so we append to `curOrder` to get `["king", "Alice", "Jack", "Bob"]`. 5. Calling `Successor(Bob, curOrder)` will return `null`. Thus the order of inheritance will be `["king", "Alice", "Jack", "Bob"]`.

Using the above function, we can always obtain a unique order of inheritance.

Implement the `ThroneInheritance` class:

* `ThroneInheritance(string kingName)` Initializes an object of the `ThroneInheritance` class. The name of the king is given as part of the constructor. * `void birth(string parentName, string childName)` Indicates that `parentName` gave birth to `childName`. * `void death(string name)` Indicates the death of `name`. The death of the person doesn't affect the `Successor` function nor the current inheritance order. You can treat it as just marking the person as dead. * `string[] getInheritanceOrder()` Returns a list representing the current order of inheritance **excluding** dead people.

Example 1:

```
**Input** ["ThroneInheritance", "birth", "birth", "birth", "birth", "birth", "birth",
"getInheritanceOrder", "death", "getInheritanceOrder"] [["king"], ["king", "andy"], ["king", "bob"],
["king", "catherine"], ["andy", "matthew"], ["bob", "alex"], ["bob", "asha"], [null], ["bob"], [null]]
**Output** [null, null, null, null, null, null, null, ["king", "andy", "matthew", "bob", "alex", "asha",
"catherine"], null, ["king", "andy", "matthew", "alex", "asha", "catherine"]] **Explanation**
ThroneInheritance t= new ThroneInheritance("king"); // order: king t.birth("king", "andy"); //
order: king > andy t.birth("king", "bob"); // order: king > andy > bob t.birth("king",
"catherine"); // order: king > andy > bob > catherine t.birth("andy", "matthew"); // order:
king > andy > matthew > bob > catherine t.birth("bob", "alex"); // order: king > andy >
matthew > bob > alex > catherine t.birth("bob", "asha"); // order: king > andy > matthew >
bob > alex > asha > catherine t.getInheritanceOrder(); // return ["king", "andy", "matthew",
"bob", "alex", "asha", "catherine"] t.death("bob"); // order: king > andy > matthew >
~~bob~~ > alex > asha > catherine t.getInheritanceOrder(); // return ["king", "andy",
"matthew", "alex", "asha", "catherine"]
```

Constraints:

* `1 <= kingName.length, parentName.length, childName.length, name.length <= 15` *
`kingName`, `parentName`, `childName`, and `name` consist of lowercase English letters only. * All arguments `childName` and `kingName` are **distinct**. * All `name` arguments of `death` will be passed to either the constructor or as `childName` to `birth` first. * For each call to `birth(parentName, childName)`, it is guaranteed that `parentName` is alive. * At most `105` calls will be made to `birth` and `death`. * At most `10` calls will be made to `getInheritanceOrder`.

Code Snippets

C++:

```

class ThroneInheritance {
public:
    ThroneInheritance(string kingName) {

    }

    void birth(string parentName, string childName) {

    }

    void death(string name) {

    }

    vector<string> getInheritanceOrder() {

    }
};

/**
 * Your ThroneInheritance object will be instantiated and called as such:
 * ThroneInheritance* obj = new ThroneInheritance(kingName);
 * obj->birth(parentName,childName);
 * obj->death(name);
 * vector<string> param_3 = obj->getInheritanceOrder();
 */

```

Java:

```

class ThroneInheritance {

    public ThroneInheritance(String kingName) {

    }

    public void birth(String parentName, String childName) {

    }

    public void death(String name) {

    }

}

```

```

public List<String> getInheritanceOrder() {

}

}

/**
 * Your ThroneInheritance object will be instantiated and called as such:
 * ThroneInheritance obj = new ThroneInheritance(kingName);
 * obj.birth(parentName,childName);
 * obj.death(name);
 * List<String> param_3 = obj.getInheritanceOrder();
 */

```

Python3:

```

class ThroneInheritance:

    def __init__(self, kingName: str):

    def birth(self, parentName: str, childName: str) -> None:

    def death(self, name: str) -> None:

    def getInheritanceOrder(self) -> List[str]:

    # Your ThroneInheritance object will be instantiated and called as such:
    # obj = ThroneInheritance(kingName)
    # obj.birth(parentName,childName)
    # obj.death(name)
    # param_3 = obj.getInheritanceOrder()

```