

Problem 2102: Sequentially Ordinal Rank Tracker

Problem Information

Difficulty: Hard

Acceptance Rate: 61.49%

Paid Only: No

Tags: Design, Heap (Priority Queue), Data Stream, Ordered Set

Problem Description

A scenic location is represented by its `name` and attractiveness `score`, where `name` is a **unique** string among all locations and `score` is an integer. Locations can be ranked from the best to the worst. The **higher** the score, the better the location. If the scores of two locations are equal, then the location with the **lexicographically smaller** name is better.

You are building a system that tracks the ranking of locations with the system initially starting with no locations. It supports:

Adding scenic locations, **one at a time**. **Querying** the `i`th **best** location of **all locations already added**, where `i` is the number of times the system has been queried (including the current query). For example, when the system is queried for the `4th` time, it returns the `4th` best location of all locations already added.

Note that the test data are generated so that **at any time**, the number of queries **does not exceed** the number of locations added to the system.

Implement the `SORTTracker` class:

`SORTTracker()` Initializes the tracker system. `void add(string name, int score)` Adds a scenic location with `name` and `score` to the system. `string get()` Queries and returns the `i`th best location, where `i` is the number of times this method has been invoked (including this invocation).

Example 1:

```

**Input** ["SORTracker", "add", "add", "get", "add", "get", "add", "get", "add", "get", "add",
"get", "get"] [], ["bradford", 2], ["branford", 3], [], ["alps", 2], [], ["orland", 2], [], ["orlando", 3], [],
["alpine", 2], [], [] **Output** [null, null, null, "branford", null, "alps", null, "bradford", null,
"bradford", null, "bradford", "orland"] **Explanation** SORTracker tracker = new
SORTracker(); // Initialize the tracker system. tracker.add("bradford", 2); // Add location with
name="bradford" and score=2 to the system. tracker.add("branford", 3); // Add location with
name="branford" and score=3 to the system. tracker.get(); // The sorted locations, from best
to worst, are: branford, bradford. // Note that branford precedes bradford due to its **higher
score** (3 > 2). // This is the 1st time get() is called, so return the best location: "branford".
tracker.add("alps", 2); // Add location with name="alps" and score=2 to the system.
tracker.get(); // Sorted locations: branford, alps, bradford. // Note that alps precedes bradford
even though they have the same score (2). // This is because "alps" is **lexicographically
smaller** than "bradford". // Return the 2nd best location "alps", as it is the 2nd time get() is
called. tracker.add("orland", 2); // Add location with name="orland" and score=2 to the system.
tracker.get(); // Sorted locations: branford, alps, bradford, orland. // Return "bradford", as it is
the 3rd time get() is called. tracker.add("orlando", 3); // Add location with name="orlando" and
score=3 to the system. tracker.get(); // Sorted locations: branford, orlando, alps, bradford,
orland. // Return "bradford". tracker.add("alpine", 2); // Add location with name="alpine" and
score=2 to the system. tracker.get(); // Sorted locations: branford, orlando, alpine, alps,
bradford, orland. // Return "bradford". tracker.get(); // Sorted locations: branford, orlando,
alpine, alps, bradford, orland. // Return "orland".

```

****Constraints:****

* `name` consists of lowercase English letters, and is unique among all locations. * `1 <= name.length <= 10` * `1 <= score <= 105` * At any time, the number of calls to `get` does not exceed the number of calls to `add`. * At most `4 * 10^4` calls ****in total**** will be made to `add` and `get`.

Code Snippets

C++:

```

class SORTracker {
public:
    SORTracker() {

    }

    void add(string name, int score) {

```

```

}

string get() {

}

};

/**
 * Your SORTracker object will be instantiated and called as such:
 * SORTracker* obj = new SORTracker();
 * obj->add(name,score);
 * string param_2 = obj->get();
 */

```

Java:

```

class SORTracker {

public SORTracker() {

}

public void add(String name, int score) {

}

public String get() {

}

}

/**
 * Your SORTracker object will be instantiated and called as such:
 * SORTracker obj = new SORTracker();
 * obj.add(name,score);
 * String param_2 = obj.get();
 */

```

Python3:

```

class SORTracker:

```

```
def __init__(self):
```

```
def add(self, name: str, score: int) -> None:
```

```
def get(self) -> str:
```

```
# Your SORTracker object will be instantiated and called as such:
```

```
# obj = SORTracker()
```

```
# obj.add(name,score)
```

```
# param_2 = obj.get()
```