

# Problem 3387: Maximize Amount After Two Days of Conversions

## Problem Information

**Difficulty:** Medium

**Acceptance Rate:** 60.48%

**Paid Only:** No

**Tags:** Array, String, Depth-First Search, Breadth-First Search, Graph

## Problem Description

You are given a string `initialCurrency`, and you start with `1.0` of `initialCurrency`.

You are also given four arrays with currency pairs (strings) and rates (real numbers):

\* `pairs1[i] = [startCurrencyi, targetCurrencyi]` denotes that you can convert from `startCurrencyi` to `targetCurrencyi` at a rate of `rates1[i]` on **day 1**. \* `pairs2[i] = [startCurrencyi, targetCurrencyi]` denotes that you can convert from `startCurrencyi` to `targetCurrencyi` at a rate of `rates2[i]` on **day 2**. \* Also, each `targetCurrency` can be converted back to its corresponding `startCurrency` at a rate of `1 / rate`.

You can perform **any** number of conversions, **including zero**, using `rates1` on day 1, **followed** by any number of additional conversions, **including zero**, using `rates2` on day 2.

Return the **maximum** amount of `initialCurrency` you can have after performing any number of conversions on both days **in order**.

**Note:** Conversion rates are valid, and there will be no contradictions in the rates for either day. The rates for the days are independent of each other.

**Example 1:**

**Input:** `initialCurrency = "EUR"`, `pairs1 = [["EUR","USD"],["USD","JPY"]]`, `rates1 = [2.0,3.0]`, `pairs2 = [["JPY","USD"],["USD","CHF"],["CHF","EUR"]]`, `rates2 = [4.0,5.0,6.0]`

**\*\*Output:\*\*** 720.00000

**\*\*Explanation:\*\***

To get the maximum amount of **\*\*EUR\*\*** , starting with 1.0 **\*\*EUR\*\*** :

\* On Day 1: \* Convert **\*\*EUR\*\*** to **\*\*USD\*\*** to get 2.0 **\*\*USD\*\***. \* Convert **\*\*USD\*\*** to **\*\*JPY\*\*** to get 6.0 **\*\*JPY\*\***. \* On Day 2: \* Convert **\*\*JPY\*\*** to **\*\*USD\*\*** to get 24.0 **\*\*USD\*\***. \* Convert **\*\*USD\*\*** to **\*\*CHF\*\*** to get 120.0 **\*\*CHF\*\***. \* Finally, convert **\*\*CHF\*\*** to **\*\*EUR\*\*** to get 720.0 **\*\*EUR\*\***.

**\*\*Example 2:\*\***

**\*\*Input:\*\*** initialCurrency = "NGN", pairs1 = [["NGN","EUR"]], rates1 = [9.0], pairs2 = [["NGN","EUR"]], rates2 = [6.0]

**\*\*Output:\*\*** 1.50000

**\*\*Explanation:\*\***

Converting **\*\*NGN\*\*** to **\*\*EUR\*\*** on day 1 and **\*\*EUR\*\*** to **\*\*NGN\*\*** using the inverse rate on day 2 gives the maximum amount.

**\*\*Example 3:\*\***

**\*\*Input:\*\*** initialCurrency = "USD", pairs1 = [["USD","EUR"]], rates1 = [1.0], pairs2 = [["EUR","JPY"]], rates2 = [10.0]

**\*\*Output:\*\*** 1.00000

**\*\*Explanation:\*\***

In this example, there is no need to make any conversions on either day.

**\*\*Constraints:\*\***

\* 1 <= initialCurrency.length <= 3 \* initialCurrency consists only of uppercase English letters. \* 1 <= n == pairs1.length <= 10 \* 1 <= m == pairs2.length <= 10 \* pairs1[i] == [startCurrencyi, targetCurrencyi] \* pairs2[i] == [startCurrencyi, targetCurrencyi] \* 1 <= startCurrencyi.length, targetCurrencyi.length <= 3 \* startCurrencyi and targetCurrencyi

consist only of uppercase English letters. \* `rates1.length == n` \* `rates2.length == m` \* `1.0 <= rates1[i], rates2[i] <= 10.0` \* The input is generated such that there are no contradictions or cycles in the conversion graphs for either day. \* The input is generated such that the output is **at most** `5 \* 10<sup>10</sup>`.

## Code Snippets

### C++:

```
class Solution {
public:
    double maxAmount(string initialCurrency, vector<vector<string>>& pairs1,
        vector<double>& rates1, vector<vector<string>>& pairs2, vector<double>&
        rates2) {

    }
};
```

### Java:

```
class Solution {
    public double maxAmount(String initialCurrency, List<List<String>> pairs1,
        double[] rates1, List<List<String>> pairs2, double[] rates2) {

    }
}
```

### Python3:

```
class Solution:
    def maxAmount(self, initialCurrency: str, pairs1: List[List[str]], rates1:
        List[float], pairs2: List[List[str]], rates2: List[float]) -> float:
```