

# Problem 3491: Phone Number Prefix

## Problem Information

**Difficulty:** Easy

**Acceptance Rate:** 0.00%

**Paid Only:** No

## Problem Description

You are given a string array

numbers

that represents phone numbers. Return

true

if no phone number is a prefix of any other phone number; otherwise, return

false

.

Example 1:

Input:

numbers = ["1","2","4","3"]

Output:

true

Explanation:

No number is a prefix of another number, so the output is

true

.

Example 2:

Input:

```
numbers = ["001","007","15","00153"]
```

Output:

false

Explanation:

The string

"001"

is a prefix of the string

"00153"

. Thus, the output is

false

.

Constraints:

$2 \leq \text{numbers.length} \leq 50$

$1 \leq \text{numbers}[i].\text{length} \leq 50$

All numbers contain only digits

'0'

to

'9'

.

## Code Snippets

### C++:

```
class Solution {  
public:  
    bool phonePrefix(vector<string>& numbers) {  
  
    }  
};
```

### Java:

```
class Solution {  
    public boolean phonePrefix(String[] numbers) {  
  
    }  
}
```

### Python3:

```
class Solution:  
    def phonePrefix(self, numbers: List[str]) -> bool:
```

### Python:

```
class Solution(object):  
    def phonePrefix(self, numbers):  
        """  
        :type numbers: List[str]  
        :rtype: bool  
        """
```

### JavaScript:

```
/**
 * @param {string[]} numbers
 * @return {boolean}
 */
var phonePrefix = function(numbers) {

};
```

### TypeScript:

```
function phonePrefix(numbers: string[]): boolean {

};
```

### C#:

```
public class Solution {
    public bool PhonePrefix(string[] numbers) {

    }
}
```

### C:

```
bool phonePrefix(char** numbers, int numbersSize) {

}
```

### Go:

```
func phonePrefix(numbers []string) bool {

}
```

### Kotlin:

```
class Solution {
    fun phonePrefix(numbers: Array<String>): Boolean {

    }
}
```

### Swift:

```
class Solution {  
    func phonePrefix(_ numbers: [String]) -> Bool {  
  
    }  
}
```

### Rust:

```
impl Solution {  
    pub fn phone_prefix(numbers: Vec<String>) -> bool {  
  
    }  
}
```

### Ruby:

```
# @param {String[]} numbers  
# @return {Boolean}  
def phone_prefix(numbers)  
  
end
```

### PHP:

```
class Solution {  
  
    /**  
     * @param String[] $numbers  
     * @return Boolean  
     */  
    function phonePrefix($numbers) {  
  
    }  
}
```

### Dart:

```
class Solution {  
    bool phonePrefix(List<String> numbers) {  
  
    }  
}
```

```
}
```

### Scala:

```
object Solution {  
  def phonePrefix(numbers: Array[String]): Boolean = {  
  
  }  
}
```

### Elixir:

```
defmodule Solution do  
  @spec phone_prefix(numbers :: [String.t]) :: boolean  
  def phone_prefix(numbers) do  
  
  end  
end
```

### Erlang:

```
-spec phone_prefix(Numbers :: [unicode:unicode_binary()]) -> boolean().  
phone_prefix(Numbers) ->  
.
```

### Racket:

```
(define/contract (phone-prefix numbers)  
  (-> (listof string?) boolean?)  
)
```

## Solutions

### C++ Solution:

```
/*  
 * Problem: Phone Number Prefix  
 * Difficulty: Easy  
 * Tags: array, string, sort  
 */
```

```

* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

class Solution {
public:
    bool phonePrefix(vector<string>& numbers) {

    }
};

```

### Java Solution:

```

/**
 * Problem: Phone Number Prefix
 * Difficulty: Easy
 * Tags: array, string, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public boolean phonePrefix(String[] numbers) {

    }
}

```

### Python3 Solution:

```

"""
Problem: Phone Number Prefix
Difficulty: Easy
Tags: array, string, sort

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

```

```

class Solution:
def phonePrefix(self, numbers: List[str]) -> bool:
# TODO: Implement optimized solution
pass

```

## Python Solution:

```

class Solution(object):
def phonePrefix(self, numbers):
"""
:type numbers: List[str]
:rtype: bool
"""

```

## JavaScript Solution:

```

/**
 * Problem: Phone Number Prefix
 * Difficulty: Easy
 * Tags: array, string, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {string[]} numbers
 * @return {boolean}
 */
var phonePrefix = function(numbers) {

};

```

## TypeScript Solution:

```

/**
 * Problem: Phone Number Prefix
 * Difficulty: Easy
 * Tags: array, string, sort

```



```

*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

function phonePrefix(numbers: string[]): boolean {

};

```

### C# Solution:

```

/*
* Problem: Phone Number Prefix
* Difficulty: Easy
* Tags: array, string, sort
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

public class Solution {
    public bool PhonePrefix(string[] numbers) {

    }
}

```

### C Solution:

```

/*
* Problem: Phone Number Prefix
* Difficulty: Easy
* Tags: array, string, sort
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

bool phonePrefix(char** numbers, int numbersSize) {

```

```
}
```

### Go Solution:

```
// Problem: Phone Number Prefix
// Difficulty: Easy
// Tags: array, string, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func phonePrefix(numbers []string) bool {

}
```

### Kotlin Solution:

```
class Solution {
    fun phonePrefix(numbers: Array<String>): Boolean {

    }
}
```

### Swift Solution:

```
class Solution {
    func phonePrefix(_ numbers: [String]) -> Bool {

    }
}
```

### Rust Solution:

```
// Problem: Phone Number Prefix
// Difficulty: Easy
// Tags: array, string, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
```

```
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn phone_prefix(numbers: Vec<String>) -> bool {

    }
}
```

### Ruby Solution:

```
# @param {String[]} numbers
# @return {Boolean}
def phone_prefix(numbers)

end
```

### PHP Solution:

```
class Solution {

    /**
     * @param String[] $numbers
     * @return Boolean
     */
    function phonePrefix($numbers) {

    }
}
```

### Dart Solution:

```
class Solution {
    bool phonePrefix(List<String> numbers) {

    }
}
```

### Scala Solution:

```
object Solution {
    def phonePrefix(numbers: Array[String]): Boolean = {
```

```
}  
}
```

### Elixir Solution:

```
defmodule Solution do  
  @spec phone_prefix(numbers :: [String.t]) :: boolean  
  def phone_prefix(numbers) do  
  
  end  
end
```

### Erlang Solution:

```
-spec phone_prefix(Numbers :: [unicode:unicode_binary()]) -> boolean().  
phone_prefix(Numbers) ->  
.
```

### Racket Solution:

```
(define/contract (phone-prefix numbers)  
  (-> (listof string?) boolean?)  
)
```