

Problem 88: Merge Sorted Array

Problem Information

Difficulty: [Easy](#)

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given two integer arrays

`nums1`

and

`nums2`

, sorted in

non-decreasing order

, and two integers

`m`

and

`n`

, representing the number of elements in

`nums1`

and

nums2

respectively.

Merge

nums1

and

nums2

into a single array sorted in

non-decreasing order

.

The final sorted array should not be returned by the function, but instead be

stored inside the array

nums1

. To accommodate this,

nums1

has a length of

$m + n$

, where the first

m

elements denote the elements that should be merged, and the last

n

elements are set to

0

and should be ignored.

nums2

has a length of

n

.

Example 1:

Input:

nums1 = [1,2,3,0,0,0], m = 3, nums2 = [2,5,6], n = 3

Output:

[1,2,2,3,5,6]

Explanation:

The arrays we are merging are [1,2,3] and [2,5,6]. The result of the merge is [

1

,

2

,2,

3

,5,6] with the underlined elements coming from nums1.

Example 2:

Input:

nums1 = [1], m = 1, nums2 = [], n = 0

Output:

[1]

Explanation:

The arrays we are merging are [1] and []. The result of the merge is [1].

Example 3:

Input:

nums1 = [0], m = 0, nums2 = [1], n = 1

Output:

[1]

Explanation:

The arrays we are merging are [] and [1]. The result of the merge is [1]. Note that because m = 0, there are no elements in nums1. The 0 is only there to ensure the merge result can fit in nums1.

Constraints:

nums1.length == m + n

nums2.length == n

0 <= m, n <= 200

$1 \leq m + n \leq 200$

-10

9

$\leq \text{nums1}[i], \text{nums2}[j] \leq 10$

9

Follow up:

Can you come up with an algorithm that runs in

$O(m + n)$

time?

Code Snippets

C++:

```
class Solution {
public:
    void merge(vector<int>& nums1, int m, vector<int>& nums2, int n) {

    }
};
```

Java:

```
class Solution {
    public void merge(int[] nums1, int m, int[] nums2, int n) {

    }
}
```

Python3:

```

class Solution:
def merge(self, nums1: List[int], m: int, nums2: List[int], n: int) -> None:
    """
    Do not return anything, modify nums1 in-place instead.
    """

```

Python:

```

class Solution(object):
def merge(self, nums1, m, nums2, n):
    """
    :type nums1: List[int]
    :type m: int
    :type nums2: List[int]
    :type n: int
    :rtype: None Do not return anything, modify nums1 in-place instead.
    """

```

JavaScript:

```

/**
 * @param {number[]} nums1
 * @param {number} m
 * @param {number[]} nums2
 * @param {number} n
 * @return {void} Do not return anything, modify nums1 in-place instead.
 */
var merge = function(nums1, m, nums2, n) {

};

```

TypeScript:

```

/**
Do not return anything, modify nums1 in-place instead.
*/
function merge(nums1: number[], m: number, nums2: number[], n: number): void
{

};

```

C#:

```

public class Solution {
    public void Merge(int[] nums1, int m, int[] nums2, int n) {

    }
}

```

C:

```

void merge(int* nums1, int nums1Size, int m, int* nums2, int nums2Size, int
n) {

}

```

Go:

```

func merge(nums1 []int, m int, nums2 []int, n int) {

}

```

Kotlin:

```

class Solution {
    fun merge(nums1: IntArray, m: Int, nums2: IntArray, n: Int): Unit {

    }
}

```

Swift:

```

class Solution {
    func merge(_ nums1: inout [Int], _ m: Int, _ nums2: [Int], _ n: Int) {

    }
}

```

Rust:

```

impl Solution {
    pub fn merge(nums1: &mut Vec<i32>, m: i32, nums2: &mut Vec<i32>, n: i32) {

    }
}

```

Ruby:

```
# @param {Integer[]} nums1
# @param {Integer} m
# @param {Integer[]} nums2
# @param {Integer} n
# @return {Void} Do not return anything, modify nums1 in-place instead.
def merge(nums1, m, nums2, n)

end
```

PHP:

```
class Solution {

    /**
     * @param Integer[] $nums1
     * @param Integer $m
     * @param Integer[] $nums2
     * @param Integer $n
     * @return NULL
     */
    function merge(&$nums1, $m, $nums2, $n) {

    }

}
```

Dart:

```
class Solution {
  void merge(List<int> nums1, int m, List<int> nums2, int n) {

  }
}
```

Scala:

```
object Solution {
  def merge(nums1: Array[Int], m: Int, nums2: Array[Int], n: Int): Unit = {

  }
}
```


Solutions

C++ Solution:

```
/*
 * Problem: Merge Sorted Array
 * Difficulty: Easy
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    void merge(vector<int>& nums1, int m, vector<int>& nums2, int n) {

    }
};
```

Java Solution:

```
/**
 * Problem: Merge Sorted Array
 * Difficulty: Easy
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public void merge(int[] nums1, int m, int[] nums2, int n) {

    }
}
```

Python3 Solution:

```

"""
Problem: Merge Sorted Array
Difficulty: Easy
Tags: array, sort

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def merge(self, nums1: List[int], m: int, nums2: List[int], n: int) -> None:
        # TODO: Implement optimized solution
        pass

```

Python Solution:

```

class Solution(object):
    def merge(self, nums1, m, nums2, n):
        """
        :type nums1: List[int]
        :type m: int
        :type nums2: List[int]
        :type n: int
        :rtype: None Do not return anything, modify nums1 in-place instead.
        """

```

JavaScript Solution:

```

/**
 * Problem: Merge Sorted Array
 * Difficulty: Easy
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number[]} nums1
 * @param {number} m

```

```

* @param {number[]} nums2
* @param {number} n
* @return {void} Do not return anything, modify nums1 in-place instead.
*/
var merge = function(nums1, m, nums2, n) {

};

```

TypeScript Solution:

```

/**
 * Problem: Merge Sorted Array
 * Difficulty: Easy
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
Do not return anything, modify nums1 in-place instead.
*/
function merge(nums1: number[], m: number, nums2: number[], n: number): void
{

};

```

C# Solution:

```

/*
 * Problem: Merge Sorted Array
 * Difficulty: Easy
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {

```

```

public void Merge(int[] nums1, int m, int[] nums2, int n) {

}

}

```

C Solution:

```

/*
 * Problem: Merge Sorted Array
 * Difficulty: Easy
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

void merge(int* nums1, int nums1Size, int m, int* nums2, int nums2Size, int
n) {

}

```

Go Solution:

```

// Problem: Merge Sorted Array
// Difficulty: Easy
// Tags: array, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func merge(nums1 []int, m int, nums2 []int, n int) {

}

```

Kotlin Solution:

```

class Solution {
fun merge(nums1: IntArray, m: Int, nums2: IntArray, n: Int): Unit {

```

```
}  
}
```

Swift Solution:

```
class Solution {  
    func merge(_ nums1: inout [Int], _ m: Int, _ nums2: [Int], _ n: Int) {  
  
    }  
}
```

Rust Solution:

```
// Problem: Merge Sorted Array  
// Difficulty: Easy  
// Tags: array, sort  
//  
// Approach: Use two pointers or sliding window technique  
// Time Complexity: O(n) or O(n log n)  
// Space Complexity: O(1) to O(n) depending on approach  
  
impl Solution {  
    pub fn merge(nums1: &mut Vec<i32>, m: i32, nums2: &mut Vec<i32>, n: i32) {  
  
    }  
}
```

Ruby Solution:

```
# @param {Integer[]} nums1  
# @param {Integer} m  
# @param {Integer[]} nums2  
# @param {Integer} n  
# @return {Void} Do not return anything, modify nums1 in-place instead.  
def merge(nums1, m, nums2, n)  
  
end
```

PHP Solution:

```

class Solution {

    /**
     * @param Integer[] $nums1
     * @param Integer $m
     * @param Integer[] $nums2
     * @param Integer $n
     * @return NULL
     */
    function merge(&$nums1, $m, $nums2, $n) {

    }

}

```

Dart Solution:

```

class Solution {
    void merge(List<int> nums1, int m, List<int> nums2, int n) {

    }

}

```

Scala Solution:

```

object Solution {
    def merge(nums1: Array[Int], m: Int, nums2: Array[Int], n: Int): Unit = {

    }

}

```