

Problem 2421: Number of Good Paths

Problem Information

Difficulty: Hard

Acceptance Rate: 56.17%

Paid Only: No

Tags: Array, Hash Table, Tree, Union Find, Graph, Sorting

Problem Description

There is a tree (i.e. a connected, undirected graph with no cycles) consisting of n nodes numbered from 0 to $n - 1$ and exactly $n - 1$ edges.

You are given a **0-indexed** integer array `vals` of length n where `vals[i]` denotes the value of the i th node. You are also given a 2D integer array `edges` where `edges[i] = [ai, bi]` denotes that there exists an **undirected** edge connecting nodes ai and bi .


A **good path** is a simple path that satisfies the following conditions:

1. The starting node and the ending node have the **same** value.
2. All nodes between the starting node and the ending node have values **less than or equal to** the starting node (i.e. the starting node's value should be the maximum value along the path).

Return the number of distinct good paths.


Note that a path and its reverse are counted as the **same** path. For example, $0 \rightarrow 1$ is considered to be the same as $1 \rightarrow 0$. A single node is also considered as a valid path.

Example 1.

 (<https://assets.leetcode.com/uploads/2022/08/04/f9caaac15b383af9115c5586779dec5.png>)


Input: `vals = [1,3,2,1,3]`, `edges = [[0,1],[0,2],[2,3],[2,4]]` **Output:** 6 **Explanation:** There are 5 good paths consisting of a single node. There is 1 additional good path: $1 \rightarrow 0 \rightarrow 2 \rightarrow 4$. (The reverse path $4 \rightarrow 2 \rightarrow 0 \rightarrow 1$ is treated as the same as $1 \rightarrow 0 \rightarrow 2 \rightarrow 4$.) Note that $0 \rightarrow 2 \rightarrow 3$ is not a good path because `vals[2] > vals[0]`.

Example 2.



Input: vals = [1,1,2,2,3], edges = [[0,1],[1,2],[2,3],[2,4]] **Output:** 7 **Explanation:** There are 5 good paths consisting of a single node. There are 2 additional good paths: 0 -> 1 and 2 -> 3.

Example 3.



Input: vals = [1], edges = [] **Output:** 1 **Explanation:** The tree consists of only one node, so there is one good path.

Constraints:

* `n == vals.length` * `1 <= n <= 3 * 10^4` * `0 <= vals[i] <= 10^5` * `edges.length == n - 1` * `edges[i].length == 2` * `0 <= ai, bi < n` * `ai != bi` * `edges` represents a valid tree.

Code Snippets

C++:

```
class Solution {
public:
    int numberOfGoodPaths(vector<int>& vals, vector<vector<int>>& edges) {

    }
};
```

Java:

```
class Solution {
    public int numberOfGoodPaths(int[] vals, int[][] edges) {

    }
}
```

```
}
```

Python3:

```
class Solution:
    def numberOfGoodPaths(self, vals: List[int], edges: List[List[int]]) -> int:
```