

# Problem 1221: Split a String in Balanced Strings

## Problem Information

Difficulty: [Easy](#)

Acceptance Rate: 0.00%

Paid Only: No

## Problem Description

Balanced

strings are those that have an equal quantity of

'L'

and

'R'

characters.

Given a

balanced

string

s

, split it into some number of substrings such that:

Each substring is balanced.

Return

the

maximum

number of balanced strings you can obtain.

Example 1:

Input:

s = "RLRRLLRLRL"

Output:

4

Explanation:

s can be split into "RL", "RRLL", "RL", "RL", each substring contains same number of 'L' and 'R'.

Example 2:

Input:

s = "RLRRRLLRLL"

Output:

2

Explanation:

s can be split into "RL", "RRRLLRLL", each substring contains same number of 'L' and 'R'.  
Note that s cannot be split into "RL", "RR", "RL", "LR", "LL", because the 2

nd

and 5

th

substrings are not balanced.

Example 3:

Input:

s = "LLLLRRRR"

Output:

1

Explanation:

s can be split into "LLLLRRRR".

Constraints:

$2 \leq s.length \leq 1000$

s[i]

is either

'L'

or

'R'

.

s

is a

balanced

string.

## Code Snippets

### C++:

```
class Solution {
public:
    int balancedStringSplit(string s) {

    }
};
```

### Java:

```
class Solution {
    public int balancedStringSplit(String s) {

    }
}
```

### Python3:

```
class Solution:
    def balancedStringSplit(self, s: str) -> int:
```

### Python:

```
class Solution(object):
    def balancedStringSplit(self, s):
        """
        :type s: str
        :rtype: int
        """
```

### JavaScript:

```
/**
 * @param {string} s
```

```
* @return {number}
*/
var balancedStringSplit = function(s) {

};
```

### TypeScript:

```
function balancedStringSplit(s: string): number {

};
```

### C#:

```
public class Solution {
    public int BalancedStringSplit(string s) {

    }
}
```

### C:

```
int balancedStringSplit(char* s) {

}
```

### Go:

```
func balancedStringSplit(s string) int {

}
```

### Kotlin:

```
class Solution {
    fun balancedStringSplit(s: String): Int {

    }
}
```

### Swift:

```

class Solution {
  func balancedStringSplit(_ s: String) -> Int {

  }
}

```

### Rust:

```

impl Solution {
  pub fn balanced_string_split(s: String) -> i32 {

  }
}

```

### Ruby:

```

# @param {String} s
# @return {Integer}
def balanced_string_split(s)

end

```

### PHP:

```

class Solution {

  /**
   * @param String $s
   * @return Integer
   */
  function balancedStringSplit($s) {

  }
}

```

### Dart:

```

class Solution {
  int balancedStringSplit(String s) {

  }
}

```

### Scala:

```
object Solution {  
  def balancedStringSplit(s: String): Int = {  
  
  }  
}
```

### Elixir:

```
defmodule Solution do  
  @spec balanced_string_split(s :: String.t) :: integer  
  def balanced_string_split(s) do  
  
  end  
end
```

### Erlang:

```
-spec balanced_string_split(S :: unicode:unicode_binary()) -> integer().  
balanced_string_split(S) ->  
.
```

### Racket:

```
(define/contract (balanced-string-split s)  
  (-> string? exact-integer?)  
)
```

## Solutions

### C++ Solution:

```
/*  
 * Problem: Split a String in Balanced Strings  
 * Difficulty: Easy  
 * Tags: string, tree, greedy  
 *  
 * Approach: String manipulation with hash map or two pointers  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(h) for recursion stack where h is height  
 */
```

```

class Solution {
public:
    int balancedStringSplit(string s) {

    }

};

```

### Java Solution:

```

/**
 * Problem: Split a String in Balanced Strings
 * Difficulty: Easy
 * Tags: string, tree, greedy
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

class Solution {
public int balancedStringSplit(String s) {

}

}

```

### Python3 Solution:

```

"""
Problem: Split a String in Balanced Strings
Difficulty: Easy
Tags: string, tree, greedy

Approach: String manipulation with hash map or two pointers
Time Complexity: O(n) or O(n log n)
Space Complexity: O(h) for recursion stack where h is height
"""

class Solution:
    def balancedStringSplit(self, s: str) -> int:
        # TODO: Implement optimized solution

```



```
pass
```

### Python Solution:

```
class Solution(object):  
    def balancedStringSplit(self, s):  
        """  
        :type s: str  
        :rtype: int  
        """
```

### JavaScript Solution:

```
/**  
 * Problem: Split a String in Balanced Strings  
 * Difficulty: Easy  
 * Tags: string, tree, greedy  
 *  
 * Approach: String manipulation with hash map or two pointers  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(h) for recursion stack where h is height  
 */  
  
/**  
 * @param {string} s  
 * @return {number}  
 */  
var balancedStringSplit = function(s) {  
  
};
```

### TypeScript Solution:

```
/**  
 * Problem: Split a String in Balanced Strings  
 * Difficulty: Easy  
 * Tags: string, tree, greedy  
 *  
 * Approach: String manipulation with hash map or two pointers  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(h) for recursion stack where h is height
```

```

*/

function balancedStringSplit(s: string): number {

};

```

### C# Solution:

```

/*
 * Problem: Split a String in Balanced Strings
 * Difficulty: Easy
 * Tags: string, tree, greedy
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

public class Solution {
    public int BalancedStringSplit(string s) {

    }
}

```

### C Solution:

```

/*
 * Problem: Split a String in Balanced Strings
 * Difficulty: Easy
 * Tags: string, tree, greedy
 *
 * Approach: String manipulation with hash map or two pointers
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(h) for recursion stack where h is height
 */

int balancedStringSplit(char* s) {

}

```

### Go Solution:

```
// Problem: Split a String in Balanced Strings
// Difficulty: Easy
// Tags: string, tree, greedy
//
// Approach: String manipulation with hash map or two pointers
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

func balancedStringSplit(s string) int {

}
```

### Kotlin Solution:

```
class Solution {
    fun balancedStringSplit(s: String): Int {

    }
}
```

### Swift Solution:

```
class Solution {
    func balancedStringSplit(_ s: String) -> Int {

    }
}
```

### Rust Solution:

```
// Problem: Split a String in Balanced Strings
// Difficulty: Easy
// Tags: string, tree, greedy
//
// Approach: String manipulation with hash map or two pointers
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(h) for recursion stack where h is height

impl Solution {
    pub fn balanced_string_split(s: String) -> i32 {

    }
}
```

```
}
```

### Ruby Solution:

```
# @param {String} s
# @return {Integer}
def balanced_string_split(s)

end
```

### PHP Solution:

```
class Solution {

    /**
     * @param String $s
     * @return Integer
     */
    function balancedStringSplit($s) {

    }

}
```

### Dart Solution:

```
class Solution {
  int balancedStringSplit(String s) {

  }

}
```

### Scala Solution:

```
object Solution {
  def balancedStringSplit(s: String): Int = {

  }

}
```

### Elixir Solution:

```
defmodule Solution do
  @spec balanced_string_split(s :: String.t) :: integer
  def balanced_string_split(s) do

  end
end
```

### Erlang Solution:

```
-spec balanced_string_split(S :: unicode:unicode_binary()) -> integer().
balanced_string_split(S) ->
.
```

### Racket Solution:

```
(define/contract (balanced-string-split s)
  (-> string? exact-integer?)
)
```