

Problem 1560: Most Visited Sector in a Circular Track

Problem Information

Difficulty: [Easy](#)

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

Given an integer

n

and an integer array

rounds

. We have a circular track which consists of

n

sectors labeled from

1

to

n

. A marathon will be held on this track, the marathon consists of

m

rounds. The

i

th

round starts at sector

rounds[i - 1]

and ends at sector

rounds[i]

. For example, round 1 starts at sector

rounds[0]

and ends at sector

rounds[1]

Return

an array of the most visited sectors


sorted in

ascending

order.

Notice that you circulate the track in ascending order of sector numbers in the counter-clockwise direction (See the first example).

Example 1:



Input:

$n = 4$, rounds = [1,3,1,2]

Output:

[1,2]

Explanation:

The marathon starts at sector 1. The order of the visited sectors is as follows: 1 --> 2 --> 3 (end of round 1) --> 4 --> 1 (end of round 2) --> 2 (end of round 3 and the marathon). We can see that both sectors 1 and 2 are visited twice and they are the most visited sectors. Sectors 3 and 4 are visited only once.

Example 2:

Input:

$n = 2$, rounds = [2,1,2,1,2,1,2,1,2]

Output:

[2]

Example 3:

Input:

$n = 7$, rounds = [1,3,5,7]

Output:

[1,2,3,4,5,6,7]

Constraints:

$2 \leq n \leq 100$

$1 \leq m \leq 100$

rounds.length == $m + 1$

$1 \leq \text{rounds}[i] \leq n$

$\text{rounds}[i] \neq \text{rounds}[i + 1]$

for

$0 \leq i < m$

Code Snippets

C++:

```
class Solution {
public:
    vector<int> mostVisited(int n, vector<int>& rounds) {

    }
};
```

Java:

```
class Solution {  
    public List<Integer> mostVisited(int n, int[] rounds) {  
  
    }  
}
```

Python3:

```
class Solution:  
    def mostVisited(self, n: int, rounds: List[int]) -> List[int]:
```

Python:

```
class Solution(object):  
    def mostVisited(self, n, rounds):  
        """  
        :type n: int  
        :type rounds: List[int]  
        :rtype: List[int]  
        """
```

JavaScript:

```
/**  
 * @param {number} n  
 * @param {number[]} rounds  
 * @return {number[]}  
 */  
var mostVisited = function(n, rounds) {  
  
};
```

TypeScript:

```
function mostVisited(n: number, rounds: number[]): number[] {  
  
};
```

C#:

```

public class Solution {
    public IList<int> MostVisited(int n, int[] rounds) {

    }
}

```

C:

```

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* mostVisited(int n, int* rounds, int roundsSize, int* returnSize) {

}

```

Go:

```

func mostVisited(n int, rounds []int) []int {

}

```

Kotlin:

```

class Solution {
    fun mostVisited(n: Int, rounds: IntArray): List<Int> {

    }
}

```

Swift:

```

class Solution {
    func mostVisited(_ n: Int, _ rounds: [Int]) -> [Int] {

    }
}

```

Rust:

```

impl Solution {
    pub fn most_visited(n: i32, rounds: Vec<i32>) -> Vec<i32> {

    }
}

```

```
}
```

Ruby:

```
# @param {Integer} n
# @param {Integer[]} rounds
# @return {Integer[]}
def most_visited(n, rounds)

end
```

PHP:

```
class Solution {

    /**
     * @param Integer $n
     * @param Integer[] $rounds
     * @return Integer[]
     */
    function mostVisited($n, $rounds) {

    }

}
```

Dart:

```
class Solution {
  List<int> mostVisited(int n, List<int> rounds) {

  }

}
```

Scala:

```
object Solution {
  def mostVisited(n: Int, rounds: Array[Int]): List[Int] = {

  }

}
```

Elixir:

```

defmodule Solution do
  @spec most_visited(n :: integer, rounds :: [integer]) :: [integer]
  def most_visited(n, rounds) do

  end

end

```

Erlang:

```

-spec most_visited(N :: integer(), Rounds :: [integer()]) -> [integer()].
most_visited(N, Rounds) ->
.

```

Racket:

```

(define/contract (most-visited n rounds)
  (-> exact-integer? (listof exact-integer?) (listof exact-integer?))
  )

```

Solutions

C++ Solution:

```

/*
 * Problem: Most Visited Sector in a Circular Track
 * Difficulty: Easy
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
    vector<int> mostVisited(int n, vector<int>& rounds) {

    }

};

```

Java Solution:


```

/**
 * Problem: Most Visited Sector in a Circular Track
 * Difficulty: Easy
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public List<Integer> mostVisited(int n, int[] rounds) {

}

}

```

Python3 Solution:

```

"""
Problem: Most Visited Sector in a Circular Track
Difficulty: Easy
Tags: array, sort

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
def mostVisited(self, n: int, rounds: List[int]) -> List[int]:
# TODO: Implement optimized solution
pass

```

Python Solution:

```

class Solution(object):
def mostVisited(self, n, rounds):
"""
:type n: int
:type rounds: List[int]
:rtype: List[int]
"""

```

JavaScript Solution:

```
/**
 * Problem: Most Visited Sector in a Circular Track
 * Difficulty: Easy
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number} n
 * @param {number[]} rounds
 * @return {number[]}
 */
var mostVisited = function(n, rounds) {

};
```

TypeScript Solution:

```
/**
 * Problem: Most Visited Sector in a Circular Track
 * Difficulty: Easy
 * Tags: array, sort
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

function mostVisited(n: number, rounds: number[]): number[] {

};
```

C# Solution:

```
/*
 * Problem: Most Visited Sector in a Circular Track
 * Difficulty: Easy
```

```

* Tags: array, sort
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

public class Solution {
public IList<int> MostVisited(int n, int[] rounds) {

}
}

```

C Solution:

```

/*
* Problem: Most Visited Sector in a Circular Track
* Difficulty: Easy
* Tags: array, sort
*
* Approach: Use two pointers or sliding window technique
* Time Complexity: O(n) or O(n log n)
* Space Complexity: O(1) to O(n) depending on approach
*/

/**
* Note: The returned array must be malloced, assume caller calls free().
*/
int* mostVisited(int n, int* rounds, int roundsSize, int* returnSize) {

}

```

Go Solution:

```

// Problem: Most Visited Sector in a Circular Track
// Difficulty: Easy
// Tags: array, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

```

```

func mostVisited(n int, rounds []int) []int {

}

```

Kotlin Solution:

```

class Solution {
    fun mostVisited(n: Int, rounds: IntArray): List<Int> {

    }
}

```

Swift Solution:

```

class Solution {
    func mostVisited(_ n: Int, _ rounds: [Int]) -> [Int] {

    }
}

```

Rust Solution:

```

// Problem: Most Visited Sector in a Circular Track
// Difficulty: Easy
// Tags: array, sort
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn most_visited(n: i32, rounds: Vec<i32>) -> Vec<i32> {

    }
}

```

Ruby Solution:

```

# @param {Integer} n
# @param {Integer[]} rounds

```

```
# @return {Integer[]}  
def most_visited(n, rounds)  
  
end
```

PHP Solution:

```
class Solution {  
  
    /**  
     * @param Integer $n  
     * @param Integer[] $rounds  
     * @return Integer[]  
     */  
    function mostVisited($n, $rounds) {  
  
    }  
}
```

Dart Solution:

```
class Solution {  
    List<int> mostVisited(int n, List<int> rounds) {  
  
    }  
}
```

Scala Solution:

```
object Solution {  
    def mostVisited(n: Int, rounds: Array[Int]): List[Int] = {  
  
    }  
}
```

Elixir Solution:

```
defmodule Solution do  
    @spec most_visited(n :: integer, rounds :: [integer]) :: [integer]  
    def most_visited(n, rounds) do
```

```
end  
end
```

Erlang Solution:

```
-spec most_visited(N :: integer(), Rounds :: [integer()]) -> [integer()].  
most_visited(N, Rounds) ->  
.
```

Racket Solution:

```
(define/contract (most-visited n rounds)  
  (-> exact-integer? (listof exact-integer?) (listof exact-integer?))  
  )
```