

Problem 373: Find K Pairs with Smallest Sums

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given two integer arrays

nums1

and

nums2

sorted in

non-decreasing order

and an integer

k

.

Define a pair

(u, v)

which consists of one element from the first array and one element from the second array.

Return

the

k

pairs

(u

1

, v

1

), (u

2

, v

2

), ..., (u

k

, v

k

)

with the smallest sums

.

Example 1:

Input:

nums1 = [1,7,11], nums2 = [2,4,6], k = 3

Output:

[[1,2],[1,4],[1,6]]

Explanation:

The first 3 pairs are returned from the sequence:

[1,2],[1,4],[1,6],[7,2],[7,4],[11,2],[7,6],[11,4],[11,6]

Example 2:

Input:

nums1 = [1,1,2], nums2 = [1,2,3], k = 2

Output:

[[1,1],[1,1]]

Explanation:

The first 2 pairs are returned from the sequence: [1,1],[1,1],[1,2],[2,1],[1,2],[2,2],[1,3],[1,3],[2,3]

Constraints:

1 <= nums1.length, nums2.length <= 10

5

-10

9

<= nums1[i], nums2[i] <= 10

9

nums1

and

nums2

both are sorted in

non-decreasing order

.

$1 \leq k \leq 10$

4

$k \leq \text{nums1.length} * \text{nums2.length}$

Code Snippets

C++:

```
class Solution {
public:
    vector<vector<int>> kSmallestPairs(vector<int>& nums1, vector<int>& nums2,
    int k) {

    }
};
```

Java:

```
class Solution {
    public List<List<Integer>> kSmallestPairs(int[] nums1, int[] nums2, int k) {

    }
}
```

Python3:

```

class Solution:
    def kSmallestPairs(self, nums1: List[int], nums2: List[int], k: int) ->
        List[List[int]]:

```

Python:

```

class Solution(object):
    def kSmallestPairs(self, nums1, nums2, k):
        """
        :type nums1: List[int]
        :type nums2: List[int]
        :type k: int
        :rtype: List[List[int]]
        """

```

JavaScript:

```

/**
 * @param {number[]} nums1
 * @param {number[]} nums2
 * @param {number} k
 * @return {number[][]}
 */
var kSmallestPairs = function(nums1, nums2, k) {

};

```

TypeScript:

```

function kSmallestPairs(nums1: number[], nums2: number[], k: number):
    number[][] {

};

```

C#:

```

public class Solution {
    public IList<IList<int>> KSmallestPairs(int[] nums1, int[] nums2, int k) {

    }
}

```

C:

```

/**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume
 caller calls free().
 */
int** kSmallestPairs(int* nums1, int nums1Size, int* nums2, int nums2Size,
int k, int* returnSize, int** returnColumnSizes) {

}

```

Go:

```

func kSmallestPairs(nums1 []int, nums2 []int, k int) [][]int {

}

```

Kotlin:

```

class Solution {
fun kSmallestPairs(nums1: IntArray, nums2: IntArray, k: Int): List<List<Int>>
{

}

}

```

Swift:

```

class Solution {
func kSmallestPairs(_ nums1: [Int], _ nums2: [Int], _ k: Int) -> [[Int]] {

}

}

```

Rust:

```

impl Solution {
pub fn k_smallest_pairs(nums1: Vec<i32>, nums2: Vec<i32>, k: i32) ->
Vec<Vec<i32>> {

}

}

```

Ruby:

```
# @param {Integer[]} nums1
# @param {Integer[]} nums2
# @param {Integer} k
# @return {Integer[][]}
def k_smallest_pairs(nums1, nums2, k)

end
```

PHP:

```
class Solution {

    /**
     * @param Integer[] $nums1
     * @param Integer[] $nums2
     * @param Integer $k
     * @return Integer[][]
     */
    function kSmallestPairs($nums1, $nums2, $k) {

    }

}
```

Dart:

```
class Solution {
  List<List<int>> kSmallestPairs(List<int> nums1, List<int> nums2, int k) {

  }

}
```

Scala:

```
object Solution {
  def kSmallestPairs(nums1: Array[Int], nums2: Array[Int], k: Int):
    List[List[Int]] = {

    }

}
```

Elixir:

```

defmodule Solution do
  @spec k_smallest_pairs(nums1 :: [integer], nums2 :: [integer], k :: integer)
  :: [[integer]]
  def k_smallest_pairs(nums1, nums2, k) do

  end

end

```

Erlang:

```

-spec k_smallest_pairs(Nums1 :: [integer()], Nums2 :: [integer()], K ::
integer()) -> [[integer()]].
k_smallest_pairs(Nums1, Nums2, K) ->
.

```

Racket:

```

(define/contract (k-smallest-pairs nums1 nums2 k)
  (-> (listof exact-integer?) (listof exact-integer?) exact-integer? (listof
(listof exact-integer?)))
)

```

Solutions

C++ Solution:

```

/*
 * Problem: Find K Pairs with Smallest Sums
 * Difficulty: Medium
 * Tags: array, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
public:
  vector<vector<int>>> kSmallestPairs(vector<int>& nums1, vector<int>& nums2,
int k) {

```



```
}  
};
```

Java Solution:

```
/**  
 * Problem: Find K Pairs with Smallest Sums  
 * Difficulty: Medium  
 * Tags: array, sort, queue, heap  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(1) to O(n) depending on approach  
 */  
  
class Solution {  
    public List<List<Integer>> kSmallestPairs(int[] nums1, int[] nums2, int k) {  
  
    }  
}
```

Python3 Solution:

```
"""  
Problem: Find K Pairs with Smallest Sums  
Difficulty: Medium  
Tags: array, sort, queue, heap  
  
Approach: Use two pointers or sliding window technique  
Time Complexity: O(n) or O(n log n)  
Space Complexity: O(1) to O(n) depending on approach  
"""  
  
class Solution:  
    def kSmallestPairs(self, nums1: List[int], nums2: List[int], k: int) ->  
        List[List[int]]:  
        # TODO: Implement optimized solution  
        pass
```

Python Solution:

```

class Solution(object):
    def kSmallestPairs(self, nums1, nums2, k):
        """
        :type nums1: List[int]
        :type nums2: List[int]
        :type k: int
        :rtype: List[List[int]]
        """

```

JavaScript Solution:

```

/**
 * Problem: Find K Pairs with Smallest Sums
 * Difficulty: Medium
 * Tags: array, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * @param {number[]} nums1
 * @param {number[]} nums2
 * @param {number} k
 * @return {number[][]}
 */
var kSmallestPairs = function(nums1, nums2, k) {

};

```

TypeScript Solution:

```

/**
 * Problem: Find K Pairs with Smallest Sums
 * Difficulty: Medium
 * Tags: array, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

```

```
function kSmallestPairs(nums1: number[], nums2: number[], k: number):
number[][] {

};
```

C# Solution:

```
/*
 * Problem: Find K Pairs with Smallest Sums
 * Difficulty: Medium
 * Tags: array, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
public IList<IList<int>> KSmallestPairs(int[] nums1, int[] nums2, int k) {

}

}
```

C Solution:

```
/*
 * Problem: Find K Pairs with Smallest Sums
 * Difficulty: Medium
 * Tags: array, sort, queue, heap
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume
 caller calls free().
 */
```

```

*/
int** kSmallestPairs(int* nums1, int nums1Size, int* nums2, int nums2Size,
int k, int* returnSize, int** returnColumnSizes) {

}

```

Go Solution:

```

// Problem: Find K Pairs with Smallest Sums
// Difficulty: Medium
// Tags: array, sort, queue, heap
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func kSmallestPairs(nums1 []int, nums2 []int, k int) [][]int {

}

```

Kotlin Solution:

```

class Solution {
fun kSmallestPairs(nums1: IntArray, nums2: IntArray, k: Int): List<List<Int>>
{

}

}

```

Swift Solution:

```

class Solution {
func kSmallestPairs(_ nums1: [Int], _ nums2: [Int], _ k: Int) -> [[Int]] {

}

}

```

Rust Solution:

```

// Problem: Find K Pairs with Smallest Sums
// Difficulty: Medium

```

```

// Tags: array, sort, queue, heap
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

impl Solution {
    pub fn k_smallest_pairs(nums1: Vec<i32>, nums2: Vec<i32>, k: i32) ->
        Vec<Vec<i32>> {

    }
}

```

Ruby Solution:

```

# @param {Integer[]} nums1
# @param {Integer[]} nums2
# @param {Integer} k
# @return {Integer[][]}
def k_smallest_pairs(nums1, nums2, k)

end

```

PHP Solution:

```

class Solution {

    /**
     * @param Integer[] $nums1
     * @param Integer[] $nums2
     * @param Integer $k
     * @return Integer[][]
     */
    function kSmallestPairs($nums1, $nums2, $k) {

    }

}

```

Dart Solution:

```

class Solution {
  List<List<int>> kSmallestPairs(List<int> nums1, List<int> nums2, int k) {

  }
}

```

Scala Solution:

```

object Solution {
  def kSmallestPairs(nums1: Array[Int], nums2: Array[Int], k: Int):
  List[List[Int]] = {

  }
}

```

Elixir Solution:

```

defmodule Solution do
  @spec k_smallest_pairs(nums1 :: [integer], nums2 :: [integer], k :: integer)
  :: [[integer]]
  def k_smallest_pairs(nums1, nums2, k) do

  end
end

```

Erlang Solution:

```

-spec k_smallest_pairs(Nums1 :: [integer()], Nums2 :: [integer()], K ::
integer()) -> [[integer()]].
k_smallest_pairs(Nums1, Nums2, K) ->
.

```

Racket Solution:

```

(define/contract (k-smallest-pairs nums1 nums2 k)
  (-> (listof exact-integer?) (listof exact-integer?) exact-integer? (listof
(listof exact-integer?)))
)

```