

Problem 3315: Construct the Minimum Bitwise Array II

Problem Information

Difficulty: **Medium**

Acceptance Rate: 0.00%

Paid Only: No

Problem Description

You are given an array

nums

consisting of

n

prime

integers.

You need to construct an array

ans

of length

n

, such that, for each index

i

, the bitwise

OR

of

`ans[i]`

and

`ans[i] + 1`

is equal to

`nums[i]`

, i.e.

`ans[i] OR (ans[i] + 1) == nums[i]`

.

Additionally, you must

minimize

each value of

`ans[i]`

in the resulting array.

If it is

not possible

to find such a value for

`ans[i]`

that satisfies the

condition

, then set

$\text{ans}[i] = -1$

.

Example 1:

Input:

$\text{nums} = [2, 3, 5, 7]$

Output:

$[-1, 1, 4, 3]$

Explanation:

For

$i = 0$

, as there is no value for

$\text{ans}[0]$

that satisfies

$\text{ans}[0] \text{ OR } (\text{ans}[0] + 1) = 2$

, so

$\text{ans}[0] = -1$

.

For

$i = 1$

, the smallest

$ans[1]$

that satisfies

$ans[1] \text{ OR } (ans[1] + 1) = 3$

is

1

, because

$1 \text{ OR } (1 + 1) = 3$

.

For

$i = 2$

, the smallest

$ans[2]$

that satisfies

$ans[2] \text{ OR } (ans[2] + 1) = 5$

is

4

, because

$$4 \text{ OR } (4 + 1) = 5$$

.

For

$$i = 3$$

, the smallest

`ans[3]`

that satisfies

$$\text{ans}[3] \text{ OR } (\text{ans}[3] + 1) = 7$$

is

$$3$$

, because

$$3 \text{ OR } (3 + 1) = 7$$

.

Example 2:

Input:

`nums = [11,13,31]`

Output:

`[9,12,15]`

Explanation:

For

$i = 0$

, the smallest

$\text{ans}[0]$

that satisfies

$\text{ans}[0] \text{ OR } (\text{ans}[0] + 1) = 11$

is

9

, because

$9 \text{ OR } (9 + 1) = 11$

.

For

$i = 1$

, the smallest

$\text{ans}[1]$

that satisfies

$\text{ans}[1] \text{ OR } (\text{ans}[1] + 1) = 13$

is

12

, because

$$12 \text{ OR } (12 + 1) = 13$$

.

For

$$i = 2$$

, the smallest

ans[2]

that satisfies

$$\text{ans}[2] \text{ OR } (\text{ans}[2] + 1) = 31$$

is

$$15$$

, because

$$15 \text{ OR } (15 + 1) = 31$$

.

Constraints:

$$1 \leq \text{nums.length} \leq 100$$

$$2 \leq \text{nums}[i] \leq 10$$

$$9$$

nums[i]

is a prime number.

Code Snippets

C++:

```
class Solution {
public:
    vector<int> minBitwiseArray(vector<int>& nums) {

    }
};
```

Java:

```
class Solution {
    public int[] minBitwiseArray(List<Integer> nums) {

    }
}
```

Python3:

```
class Solution:
    def minBitwiseArray(self, nums: List[int]) -> List[int]:
```

Python:

```
class Solution(object):
    def minBitwiseArray(self, nums):
        """
        :type nums: List[int]
        :rtype: List[int]
        """
```

JavaScript:

```
/**
 * @param {number[]} nums
 * @return {number[]}
 */
var minBitwiseArray = function(nums) {
```



```
};
```

TypeScript:

```
function minBitwiseArray(nums: number[]): number[] {  
  
};
```

C#:

```
public class Solution {  
    public int[] MinBitwiseArray(IList<int> nums) {  
  
    }  
}
```

C:

```
/**  
 * Note: The returned array must be malloced, assume caller calls free().  
 */  
int* minBitwiseArray(int* nums, int numsSize, int* returnSize) {  
  
}
```

Go:

```
func minBitwiseArray(nums []int) []int {  
  
}
```

Kotlin:

```
class Solution {  
    fun minBitwiseArray(nums: List<Int>): IntArray {  
  
    }  
}
```

Swift:

```

class Solution {
  func minBitwiseArray(_ nums: [Int]) -> [Int] {

  }
}

```

Rust:

```

impl Solution {
  pub fn min_bitwise_array(nums: Vec<i32>) -> Vec<i32> {

  }
}

```

Ruby:

```

# @param {Integer[]} nums
# @return {Integer[]}
def min_bitwise_array(nums)

end

```

PHP:

```

class Solution {

  /**
   * @param Integer[] $nums
   * @return Integer[]
   */
  function minBitwiseArray($nums) {

  }
}

```

Dart:

```

class Solution {
  List<int> minBitwiseArray(List<int> nums) {

  }
}

```

Scala:

```
object Solution {  
  def minBitwiseArray(nums: List[Int]): Array[Int] = {  
  
  }  
}
```

Elixir:

```
defmodule Solution do  
  @spec min_bitwise_array(nums :: [integer]) :: [integer]  
  def min_bitwise_array(nums) do  
  
  end  
end
```

Erlang:

```
-spec min_bitwise_array(Nums :: [integer()]) -> [integer()].  
min_bitwise_array(Nums) ->  
.
```

Racket:

```
(define/contract (min-bitwise-array nums)  
  (-> (listof exact-integer?) (listof exact-integer?))  
)
```

Solutions

C++ Solution:

```
/*  
 * Problem: Construct the Minimum Bitwise Array II  
 * Difficulty: Medium  
 * Tags: array  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(1) to O(n) depending on approach  
 */
```

```

class Solution {
public:
    vector<int> minBitwiseArray(vector<int>& nums) {

    }
};

```

Java Solution:

```

/**
 * Problem: Construct the Minimum Bitwise Array II
 * Difficulty: Medium
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

class Solution {
    public int[] minBitwiseArray(List<Integer> nums) {

    }
}

```

Python3 Solution:

```

"""
Problem: Construct the Minimum Bitwise Array II
Difficulty: Medium
Tags: array

Approach: Use two pointers or sliding window technique
Time Complexity: O(n) or O(n log n)
Space Complexity: O(1) to O(n) depending on approach
"""

class Solution:
    def minBitwiseArray(self, nums: List[int]) -> List[int]:
        # TODO: Implement optimized solution

```

```
pass
```

Python Solution:

```
class Solution(object):  
    def minBitwiseArray(self, nums):  
        """  
        :type nums: List[int]  
        :rtype: List[int]  
        """
```

JavaScript Solution:

```
/**  
 * Problem: Construct the Minimum Bitwise Array II  
 * Difficulty: Medium  
 * Tags: array  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(1) to O(n) depending on approach  
 */  
  
/**  
 * @param {number[]} nums  
 * @return {number[]}  
 */  
var minBitwiseArray = function(nums) {  
  
};
```

TypeScript Solution:

```
/**  
 * Problem: Construct the Minimum Bitwise Array II  
 * Difficulty: Medium  
 * Tags: array  
 *  
 * Approach: Use two pointers or sliding window technique  
 * Time Complexity: O(n) or O(n log n)  
 * Space Complexity: O(1) to O(n) depending on approach  
 */
```

```

*/

function minBitwiseArray(nums: number[]): number[] {

};

```

C# Solution:

```

/*
 * Problem: Construct the Minimum Bitwise Array II
 * Difficulty: Medium
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

public class Solution {
    public int[] MinBitwiseArray(IList<int> nums) {

    }
}

```

C Solution:

```

/*
 * Problem: Construct the Minimum Bitwise Array II
 * Difficulty: Medium
 * Tags: array
 *
 * Approach: Use two pointers or sliding window technique
 * Time Complexity: O(n) or O(n log n)
 * Space Complexity: O(1) to O(n) depending on approach
 */

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* minBitwiseArray(int* nums, int numsSize, int* returnSize) {

```

```
}
```

Go Solution:

```
// Problem: Construct the Minimum Bitwise Array II
// Difficulty: Medium
// Tags: array
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach

func minBitwiseArray(nums []int) []int {

}
```

Kotlin Solution:

```
class Solution {
    fun minBitwiseArray(nums: List<Int>): IntArray {

    }
}
```

Swift Solution:

```
class Solution {
    func minBitwiseArray(_ nums: [Int]) -> [Int] {

    }
}
```

Rust Solution:

```
// Problem: Construct the Minimum Bitwise Array II
// Difficulty: Medium
// Tags: array
//
// Approach: Use two pointers or sliding window technique
// Time Complexity: O(n) or O(n log n)
// Space Complexity: O(1) to O(n) depending on approach
```

```

impl Solution {
  pub fn min_bitwise_array(nums: Vec<i32>) -> Vec<i32> {

  }
}

```

Ruby Solution:

```

# @param {Integer[]} nums
# @return {Integer[]}
def min_bitwise_array(nums)

end

```

PHP Solution:

```

class Solution {

    /**
     * @param Integer[] $nums
     * @return Integer[]
     */
    function minBitwiseArray($nums) {

    }

}

```

Dart Solution:

```

class Solution {
  List<int> minBitwiseArray(List<int> nums) {

  }
}

```

Scala Solution:

```

object Solution {
  def minBitwiseArray(nums: List[Int]): Array[Int] = {

```



```
}  
}
```

Elixir Solution:

```
defmodule Solution do  
  @spec min_bitwise_array(nums :: [integer]) :: [integer]  
  def min_bitwise_array(nums) do  
  
  end  
end
```

Erlang Solution:

```
-spec min_bitwise_array(Nums :: [integer()]) -> [integer()].  
min_bitwise_array(Nums) ->  
.
```

Racket Solution:

```
(define/contract (min-bitwise-array nums)  
  (-> (listof exact-integer?) (listof exact-integer?))  
)
```